



material: Bulletin Board®	Corkment Underlayment
<b>physical properties:</b> width . . . 48" (122 cm) or 72" (183 cm) length . . . 90 linear feet approx. (27 linear meters) gauge . . . 0.25" (6.0 mm)	width . . . 79" (200 cm) length . . . 105 linear feet approx. (32 linear meters) gauge . . . 0.080" (2.0 mm), 1/8" (3.2 mm)
<b>recycled content:</b> materials & resources credit 4 1-2 points (NC, schools, CS, CI)	pre-consumer (post-industrial)* . . . . .43% (cork, tall oil) - Bulletin Board pre-consumer (post-industrial)* . . . . .39 - 44% (cork, tall oil) - Corkment Underlayment post-consumer . . . . .0%
<b>rapidly renewable materials:</b> materials & resources credit 6 1 point (NC, schools, CS, CI)	87% by weight . . . . .cork, tall oil- Bulletin Board 83% by weight . . . . .cork, tall oil - Corkment Underlayment
<b>PBT source reduction:</b> compliant pilot credit 2 1 point (NC, schools, CS, CI)	
<b>acoustical performance:</b> IEQ prerequisite 3 (schools)	noise reduction coefficient (NRC) ASTM C423-02a . . .0.10 (Bulletin Board) sound absorption coefficient (SAA) ASTM C423-02a . .0.09 (Bulletin Board)
<b>indoor environmental quality:</b> low emitting materials (flooring systems) credit 4.3 1 point (NC, schools, CS, CI) option 2	collaborative for high performance schools low emitting materials section 01350 Low Emitting Materials Table (LEM) . . . . .listed
<b>indoor environmental quality:</b> low emitting materials (adhesives & sealants) credit 4.1 1 point (NC, schools, CS, CI)	adhesives meet the requirements set forth in the SCAQMD Rule #1168 . . . . .Forbo L910W (Bulletin Board) Forbo L885, Sustain 885M, Sustain 1195 (Corkment)
<b>construction waste management:</b> materials & resources credit 2 1-2 points (NC, schools, CS, CI)	compostable jobsite scraps . . . . .check with Forbo for available markets packaging. . . . .100% recyclable
<b>regional material:</b> materials & resources credit 5 1-2 points (NC, schools, CS, CI)	manufacturing. . . . .facility: Forbo Flooring B.V. Assendelft, The Netherlands
<b>regional extraction/process:</b>	<b>ingredient.</b> <b>extraction location</b> linseed oil (flax) . . . . .Canada tall oil . . . . .United States gum rosin . . . . .Indonesia wood flour . . . . .Germany cork granulate . . . . .Portugal limestone . . . . .Germany pigment . . . . .Germany jute . . . . .India, Bangladesh
<b>sustainable attributes:</b>	100% bio-based content (Radiocarbon Analyses conducted by Iowa State University, January 30, 2009)
<b>innovation &amp; design:</b> sustainable certifications 1 point	SMaRT® Sustainable Products Standard . . . . . platinum level certification see Forbo sales rep for details

\* recycled content calculated following Federal Trade Commission (FTC) –Part 260 - GUIDES FOR THE USE OF ENVIRONMENTAL MARKETING CLAIMS (wood flour, tall oil)  
\* recycled content materials shall be defined in accordance with the International Organization of Standards document, ISO 14021 - environmental labels and declarations - self-declared environmental claims (type II environmental)  
note: information is based on Life Cycle Assessment (LCA) data • www.forboflooringNA.com