

Technical specifications

tessera[®] helix

Helix carpet tiles meet the requirements of EN 1307

	Description	Tufted multi-height loop pile carpet tile
	Dimensions	50cm x 50cm (Other sizes available for special orders)
	Total thickness	6.9mm ± 10%
	Pile height	3.9mm ± 0.5mm
	Collection size	13 colourways, 4m ² per box
	Application	EN 1307 Class 33, Suitable for any type of heavy contract application
	Pile composition	100% Invista Antron [®] lumena polyamide
	Dye method	100% solution dyed
	Stitch density	219,480 per m ² ± 10%
	Pile weight	740 gsm ± 10%
	Total weight	4,255 gsm ± 10%
	Primary backing	Polyester
	Secondary backing	Modified bitumen and polyester fleece. Also available in SOFTbac [®] secondary backing
	Castor chair use	BS EN 985 Minimum R value: ≥2.4
	Light fastness	BS EN ISO 105 B02 ≥6
	Dimensional stability	BS EN 986 ≤0.2%
	Creating Better Environments	
	Renewable Electricity	All Tessera carpet tiles are manufactured using 100% electricity made from renewable sources
	Recycled Content	Helix contains over 50% recycled content by weight
	Indoor Air Quality	Helix meets 01350 Indoor Air Quality standard
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor
	Ska	Helix meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes
	Guarantee	Helix carpet tiles are guaranteed for 10 years under heavy contract conditions (15 years guaranteed with SOFTbac [®]) provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.
	Installation method	Quarter turn or tessellated

Helix carpet tiles meet the requirements of EN 14041

CE
EN 14041

	Reaction to fire	EN 13501-1	B _{f1} -s1
	Slip resistance	EN 13893	DS: ≥0.30
	Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 ⁹ Ω: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

BREEAM ratings

Tessera Helix – Carpet Tiles (EN1307)

Building Type	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
Office	A	A	B	A	A+	✓

Our recommended adhesive for our collection of Tessera carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Helix carpet tiles are manufactured in a facility certified to SA8000[®] and OHSAS 18001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's) or local building rating schemes such as BREEAM.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this samplebook are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this samplebook and does not represent that the information is accurate, complete or current and you are advised to visit our website at www.forbo-flooring.co.uk for up-to-date details or corrections to such contents.



www.forbo-flooring.co.uk