



	Type of floor covering	Homogeneous vinyl flooring
	Binder content	Type 1 (> 55%)
	Wear resistance	Group T
	Commercial use	34
	Industrial use	43
	Total thickness	2.0 mm
	Roll width	2 m
	Roll length	> 25 m
	Weight	2,6 kg/m ²
	Dimensional stability	≤ 0,4 %
	Residual indentation	≤ 0,06 mm
	Castor wheel test	Pass
	Light colour fastness	≥ 6
	Flexibility	10 mm

	Slip rating	R9
	Surface finish	PUR Evolve
	Resistance to chemicals	Very good Resistant to disinfectant Ethanol 70-96 %
	Emission	Pass
	Possibility to install on floor heating	Yes
	Wetroom application	Yes
		EN 14041 CE 0200700-Dop_306
Nordstar Evolve meets the requirements of EN 14041		
	Fire class	B _{fl} - S1
	Body voltage	< 2 kV
	Electrical resistance	R1 < 10 ⁹ Ohm (vertical resistance)
	Thermal conductivity	0,25 W/m.K
	Slip rating	DS: ≥ 0,3

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

