## **nuway**<sup>®</sup>tuftiguard



Maximum length per module	2500mm (Bamboo 2400mm)																
Maximum width per module	750mm																
Maximum weight per module	23kg/m <sup>2</sup>																
Depth	12mm	12mm								17mm							
Scraper bar material	Aluminium / Black Anodised Aluminium				Bamboo				Aluminium / Black Anodised Aluminium				Bamboo				
Construction	Open		Closed		Open		Closed		Open		Closed		Open		Closed		
Number of wiper strips	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2	
Total weight (kg/m²)	11	12	14	15	10	11	13	14	14	15	16	17	13	14	15	16	
Max static load (kg/cm²)	200				100				200								
Dynamic load (kg) 2 wheels 80mm, 20,000 passes	200				100				200								
Frames	A selection of recessed matwell frames are available, please see page 4.0.2 for details																
Ramp frame model	ARF 50								ARF 70								
Manufacturing method	Entran	Entrance flooring system with scraper bars and rubber wiper strips															
Wiper designs	Plain, r	natural fi	bres, col	oured fit	ores												
Wiper material	Rubbe	r															
Pile material	100%	Polyamio	de BCF														



## CONSIDERATIONS

**Bamboo** is a natural product so there will be a variance of colour within the scraper bars and although the Bamboo may fade and lose small 'splinters', the structural integrity of the mat will not be affected.

In very brightly lit areas, the strong contrast between a light aluminium scraper bar and a dark wiper strip can sometimes create a strobe effect, which should be avoided.


To prevent this type of occurrence, consider using scraper bars in **Bamboo** or **Black Anodised Aluminium**.



## TECHNICAL SPECIFICATIONS




## Tuftiguard Classic and Design – dimensions




12mm single closed All dimensions are approximate.


Bamboo (Classic & Design)



12mm single open



17mm single closed



17mm single open

7mm



For more detailed information on the dimensions of our Nuway Tuftiguard Entrance Systems, please visit **www.forbo-flooring.co.uk/downloads**, or contact our Entrance Flooring Systems Customer Service team on **01773 740 688.**