

NUWAY® ENTRANCE FLOORING TECHNICAL DATA

1. PRODUCT NAME / MANUFACTURER

1.1 Product:

Nuway® entrance flooring

1.2 Manufacturer:

Forbo Flooring Systems
 8 Maplewood Dr.
 Hazleton, PA 18202
www.forboflooringNA.com
 Phone: 1-800-842-7839
 Fax: 570-450-0258

1.3 Product Description:

Construction: Nuway® engineered entrance flooring is constructed of profiles, scrapers and insert materials connected by high tensile steel wire. Nuway® is designed for use outside doorways and immediately inside heavily trafficked entrance areas to scrape off the worst of soil being tracked in on the soles of shoes or wheeled vehicles.

1.4 Physical Characteristics: (dimensions are approximate)

Height ----- 12 mm (7/16") or 17 mm (11/16")
 Scraper Bars----- Aluminum
 Connectors----- High Tensile Steel Wire
 Size ----- Made to specifications

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1 Application Areas:

Zone 1: Outside and Inside entrances to the building.
 See Forbo's Entrance Systems brochure for additional information.

2.2 Environmental:

Nuway® contributes to LEED® v4 credits. For additional information, contact Forbo Flooring Systems.

2.3 Slip Resistance:

Meets or exceeds the industry recommendation of >0.5 for flat surfaces when tested in accordance with ASTM D 2047, Standard Test Method for Static Coefficient of Friction.

2.4 Durability:

100 hours of salt fog with no notable change in appearance when tested in accordance with ASTM B 117, Corrosion Resistance Test.

2.5 Fire Testing:

Class 1 when tested in accordance with ASTM E 648/NFPA 253, Standard Test Method for Critical Radiant Flux.

3. INSTALLATION

Refer to the Forbo Installation Guide for complete installation recommendations.

4. AVAILABILITY AND COST

Available through authorized Forbo Flooring suppliers throughout North America. Contact Forbo Flooring or an authorized supplier for cost information.

5. WARRANTY

Limited 15-year warranty. For complete details, contact Forbo Flooring Systems.

6. CARE AND CLEANING

After installation is completed, allow a minimum of 5 days for the adhesive to properly bond and cure before conducting wet cleaning procedures. See Forbo Flooring's Floor Care Guide for additional information.