



FLOORING SYSTEMS

matte floor finish

DESCRIPTION

This new generation of environmentally responsible synthetic floor finish has exceptional durability and flexibility. This synthetic floor finish is specifically formulated with elastic properties that will prevent cracking. It meets today's need for a product that contains no zinc or other heavy metals that can be harmful to wastewater treatment systems. This low odor finish has the flexibility needed to protect a the floor, while being tough enough to stand up to excessive wear. Average coverage per gallon is approximately 1,800 – 2,200 square feet.

DIRECTIONS

If the floor is in good condition, sweep up excess dirt and dust and then clean with a quality neutral pH cleaner to remove dirt and oils. Follow with a thorough rinsing and allow the floor to dry completely. Apply 1 – 2 coats of floor finish using a clean a micro-fiber applicator or clean finish mop. Allow a minimum of 45 minutes drying time between coats.

CAUTION

MAY CAUSE EYE OR SKIN IRRITATION WITH DIRECT CONTACT. Avoid contact with skin, eyes and clothing. Wear protective footwear when applying to floor. Avoid breathing of vapors. Use in well ventilated areas at all times. Floors are slippery when wet; keep all unauthorized persons away. Do not take internally. Wear rubber gloves when handling. Wash thoroughly with soap and water after handling. Keep out of reach of children.

FIRST AID

EYE CONTACT: Immediately flush with water for 15 minutes. If irritation persists, seek medical attention.

SKIN CONTACT: Flush with water followed by washing with mild soap and water. Remove contaminated clothing and launder before reuse. Seek medical attention if irritation develops.

INHALATION: Remove to fresh air. Seek medical attention if symptoms persist.

INGESTION: Call physician immediately.

DISPOSAL: Dispose of product (concentrate or diluted) by any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose.

La DISPOSICION: Deshágase del producto (el concentrado o diluido) por cualquier método de acuerdo con local, el estado y las leyes federales. Mejor método es de reciclar o volver a emplear para el propósito destinado.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer container for recycling, or if not available, puncture and dispose of in a sanitary landfill.

La DISPOSICION del CONTENEDOR: Triplíquese el aclarado (o el equivalente). Entonces contenedor de oferta para reciclar, o si no disponible, rompe y se deshace de en un vertedero sanitario.

CONTAINS

Metal-free Acrylate Copolymer Dispersion (N/A), Modified Propylene Copolymer (25722-45-6), Ethylene Acrylic Acid Copolymer (9010-77-9), Tributoxethyl Phosphate (78-51-3), Diethylene Glycol Ethyl Ether (111-90-0), Water (7732-18-5).

PRECAUCION

AL USARIO: Si usted no lee inglés, no use este producto hasta que la etiqueta le haya sido explicada ampliamente.

(TO THE USER: If you cannot read English, do not use this product until the label has been fully explained to you).

For additional information, Forbo's Floor Care Guidelines are available for download at www.forboflooringna.com, or contact Forbo Technical Services at +800 842 7839.

PRODUCT SPECIFICATIONS

Non-volatile Solids:	18.0 ± 0.5%
Color:	Milky emulsion
Odor:	Low
pH:	8.0 – 8.5
Dry/Recoat Time:	45 minutes min.
Slip Resistance:	0.5 min. by ASTM-D2047
Durability:	Excellent
Buffability:	Spraybuffing or high speed burnishing
Removability:	With instant type strippers
Detergent Resistance:	Excellent
VOC Content:	0.54 lbs./gal.
Storage/Stability:	1 year
Weight Per Gallon:	8.54 lbs./gal.
Freeze/Thaw Stability:	Keep from freezing