


















# Technical specifications




**tessera**<sup>®</sup> create space 1

Tessera Create space 1 carpet tiles meet the requirements of EN 1307

	Description	Tufted low level loop pile carpet tile	
	Dimensions	50cm x 50cm (Other sizes available for special orders)	
	Total thickness	5.5mm ± 10%	
	Pile height	2.7mm ± 0.5mm	
	Collection size	18 colourways, 5m <sup>2</sup> per box	
	Application	EN 1307	Class 33, Suitable for any type of heavy contract application
	Pile composition	100% ECONYL <sup>®</sup> /Altochroma regenerated polyamide 6	
	Dye method	100% solution dyed	
	Stitch density	212,760 per m <sup>2</sup> ± 10%	
	Pile weight	500 gsm ± 10%	
	Total weight	3,815 gsm ± 10%	
	Primary backing	Polyester	
	Secondary backing	Modified bitumen and polyester fleece. Also available in SOFTbac <sup>®</sup> secondary backing	
	Castor chair use	BS EN 985	Minimum R value: ≥2.4
	Light fastness	BS EN ISO 105 B02	≥5
	Dimensional stability	BS EN 986	≤0.2%
	Creating Better Environments		
	Renewable Electricity	All Tessera carpet tiles are manufactured using 100% electricity made from renewable sources	
	Recycled Content	Create space 1 contains over 50% recycled content by weight	
	BRE	Create Space 1 is awaiting BREEAM assessment, please find the latest information at <a href="http://www.forbo-flooring.co.uk/createspace">www.forbo-flooring.co.uk/createspace</a>	
	Indoor Air Quality	Create space 1 meets 01350 Indoor Air Quality standard	
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor	
	Ska	Create space 1 meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes	
	Guarantee	Create space 1 carpet tiles are guaranteed for 10 years under heavy contract conditions (15 years guaranteed with SOFTbac <sup>®</sup> ) provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.	
	Installation method	Monolithic, quarter turn, tessellated	

Create space 1 carpet tiles meet the requirements of EN 14041



	Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1
	Slip resistance	EN 13893	DS: ≥0.30
	Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 <sup>9</sup> Ω: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

### BREEAM ratings

Tessera Create Space 1 – Carpet Tiles (EN1307)

Building Type	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
Office	A+	A+	A	A	A+	✓

[www.forbo-flooring.com](http://www.forbo-flooring.com)

Our recommended adhesive for our collection of Tessera carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Create Space 1 carpet tiles are manufactured in a facility certified to SA8000<sup>®</sup> and OHSAS 18001.