






















# Technical specifications

Create Space 1 carpet tiles meet the requirements of EN 1307

	Description	Tufted low level loop pile carpet tile	
	Dimensions	50cm x 50cm	
	Total thickness	5.5mm ± 10%	
	Pile height	2.7mm ± 0.5mm	
	Collection size	18 colourways. 5m <sup>2</sup> per box	
	Application	EN 1307	Class 33, Suitable for any type of heavy contract application
	Pile composition	100% ECONYL®/Altochroma polyamide 6	
	Dye method	100% solution dyed	
	Tuft density	212,760 per m <sup>2</sup> ± 10%	
	Pile weight	500gsm ± 10%	
	Total weight	3,815gsm ± 10%	
	Primary backing	Polyester	
	Secondary backing	ProBac recycled mineral filler with low amount of modified bitumen and polyester fleece. Contains over 76% recycled content. Also available in SOFTbac® secondary backing	
	Impact sound reduction	ISO 10140-3	ΔLw = 21 dB
	Castor chair use	EN 985	Minimum R Value: ≥ 2.4
	Light fastness	EN ISO 105-B02	≥ 5
	Dimensional stability	EN 986	≤ 0.2%
	Creating Better Environments		
	Renewable Energy	All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas)	
	Recycled Content	Create Space 1 carpet tiles contain 71% recycled content by weight	
	Indoor Air Quality	Create Space 1 carpet tiles products comply to 01350 Indoor Air Quality Standard	
	Back to the Floor	Installation off cuts can be collected via Back to the Floor	
	Ska Rating	Create Space 1 meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes	
	Guarantee	Create Space 1 carpet tiles are guaranteed for 10 years under heavy contract conditions (15 years guaranteed with SOFTbac®) provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.	
	Installation method	Monolithic, quarter turn or tessellated	

Create Space 1 carpet tiles meet the requirements of EN 14041

	Product code	EN 14041	1170100-DoP-306 / 1170200-DoP-306 (SOFTbac®)
	Reaction to fire	EN 13501-1	B <sub>f1</sub> -s1, L, NCS
	Slip resistance	EN 13893	μ ≥ 0.30
	Body voltage	ISO 6356	< 2kV

## BREEAM ratings

Tessera – Create Space 1 – Carpet Tiles (EN1307)

Commercial	Education	Health	Domestic	Retail (Durability)	Retail (Fashion)
A	A+	A+	A	A	A+

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Tessera Diffusion is manufactured in a facility certified to SA8000® and OHSAS 18001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's) or local building rating schemes such as BREEAM.