

Technical specifications

Furniture linoleum meets the requirements of EN 688



	Total Thickness	EN-ISO 24346	2.0 mm
	Roll width	EN-ISO 24341	1.83 m
	Collection size		21 colourways
	Roll length	EN-ISO 24341	≤ 30 m
	Total weight	EN-ISO 23997	2.1 kg/m ²
	Indentation-residual	EN-ISO 24341	< 0.20 mm
	Light fastness	EN ISO 105 B-02	Method 3: blue scale minimum 6
	Gloss level	ISO 2813	< 5
	Flexibility	EN-ISO 24344	ø 50 mm
	Resistance to chemicals	EN-ISO 26987	Resistant to diluted acids, oils, fats and to the conventional solvents. Not resistant to prolonged exposure to alkalis.
	Heat resistance		70 ° C
	Reaction to fire	AS 3837	Group 3
	Body Voltage	EN 1815	< 2 kV
	Creating better environments		
	Renewable electricity		Marmoleum is manufactured using 100% electricity from renewable sources.
	Recycled Content		Furniture Linoleum contains 28% recycled content by weight
	Life Cycle Assessment**		LCA is the foundation for securing the lowest environmental impact

** For verification and details please consult our Marmoleum EPD.

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.



Downloads

- FURNITURE LINOLEUM FIRE REPORT
- FURNITURE LINOLEUM GECA CERTIFICATE
- FURNITURE LINOLEUM CLEANING GUIDE
- FURNITURE LINOLEUM INSTALLATION GUIDE

For more information contact your Forbo representative or call 1800 224 471.