



furniture linoleum  
climate positive  
CRADLE TO GATE

## Technical specifications

	Total thickness	EN-ISO 24346	2.0 mm
	Collection size		21
	Roll width	EN-ISO 24341	1.83 m
	Roll length	EN-ISO 24341	~ 30 m
	Total weight	EN-ISO 23997	2100 g/m <sup>2</sup>
	Residual indentation	EN-ISO 24341-1	~ 0.20
	Colour fastness to light	EN ISO 105-B02 method 3	° 6
	Gloss level	ISO 2813	< 5
	Flexibility	EN-ISO 24344	ø 50 mm
	Resistance to chemicals	EN-ISO 26987	Resistant to diluted acids, oils, fats and to the conventional solvents. Not resistant to prolonged exposure to alkalis.
	Heat resistance		70 ° C
	Antistatic	EN 1815	~ 2.0 kV
	Reaction to fire	AS 3837	Group 3 - Average specific extinction area: 47.7 m <sup>2</sup> /kg
	Creating better environments		Furniture Linoleum is climate positive cradle to gate*.
	Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact.

\* For details, please consult the Furniture Linoleum EPD.

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

