

# 540 EUROSAFE SPECIAL

Solvent-free, floor covering adhesive with a fast adhesion

## product advantages

- Entirely solvent-free
- Non-flammable
- Easy and safe to apply
- High initial adhesion strength and final bond strength
- Favourable spreading capacity
- Roller-castor-chair resistant

## application

### For installing:

- PVC floor covering in sheets and tiles
- cushion vinyl
- carpets with a back of PVC-foam
- carpets with a back of PU-foam
- rubber floor covering in sheets and tiles with a smooth back
- polyolefin floor covering.

## technical facts

<b>Basis</b>	Superior acrylic dispersion.
<b>Colour</b>	Beige.
<b>Consistency</b>	Thick liquid.
<b>Specific weight</b>	1.3 kg/ltr.
<b>Tools</b>	Eurocol adhesive spreader no. 852/A2. Type of adhesive spreader depends on the floor covering to be fixed.
<b>Spreading capacity</b>	250-350 g/m <sup>2</sup> , depending on the back of floor covering and condition of the subfloor.
<b>Waiting time</b>	10-20 Minutes.*
<b>Open time</b>	60 Minutes.*
<b>Drying time</b>	48 Hours.*
<b>Storage</b>	Store cool and free from frost.
<b>Shelf life</b>	12 Months, in unopened packaging.
<b>Flammability</b>	Non-flammable.
<b>Danger class</b>	None.
<b>Safety data sheet</b>	Available on request.

\* These times have been established in our laboratory and must be considered as guidelines in view of possible variations in climatic conditions, subfloor compositions and layer thickness.

## working conditions

Minimum working temperature PVC floor covering	: 15° C.
Minimum working temperature rubber and polyolefin floor covering	: 18° C.
Minimum subfloor temperature	: 15° C.
Maximum relative humidity	: 70%.

# 540 EUROSAFE SPECIAL

## subfloor

- 540 Eurosafe Special is suitable for any type of subfloor that has good tensile and compression strength. The subfloor should also be smooth, clean, permanently dry and free from grease and dirt, according to the requirements of BS 8203 or DIN 18 365
- When installing on impervious subfloors, a 2 mm layer of levelling compound must be applied.
- If in doubt about the application ask for technical advice and refer to our technical data sheets for additional product information.

## directions for use

- Apply the adhesive with a fine-toothed adhesive spreader (Eurocol no. 852/A2).  
Type of spreader depends on the type of floor covering and circumstances of the subfloor.
- When installing a polyolefin floor covering, wait until the top of the adhesive stripes have dried transparent.
- When installing on impervious subfloors, a 2 mm layer of levelling compound must be applied.
- Roll the floor covering well. Sheet-ends and seams are to be pressed firmly.
- Remove any adhesive spots immediately with water.

## underfloor heating systems

540 Eurosafe Special can be applied on underfloor heating systems. Turn off the heater 24 hours before application. Do not heat again until at least 48 hours after installation, in steps of 5° C per day.

## packaging

13 kg environmental bucket (PE-basis).

Our directions for use are based on careful tests made in laboratory and practice. However, we can not take responsibility for executed work and therefore we advise to make tests at the place of application. Otherwise we refer to our general sales conditions.



Eurocol BV • P.O. Box 130 NL-1520 AC Wormerveer • The Netherlands  
T +31 75 627 16 00 • F +31 75 622 39 16 • E sales@eurocol.nl