



coral[®] logo

Technical specifications

Coral Logo (43xx)*

	Total thickness	ISO 1765	Approx. 8 mm
	Wear classification	EN 1307	31, commercial light
	Available sizes (all sizes are approx.) Roll sizes with 2.5 cm edge each side	Standard mat sizes (sizes with edges)	
		Special sizes (sizes without edges)	
		55 x 90 cm	any width, any length
		105 x 155 cm 105 x 300 cm	
	Mat sizes with 2.5 cm edge all sides	155 x 197 cm 155 x 300 cm	
		197 x 197 cm 197 x 300 cm	up to 192 cm wide
Colour fastness ratings:			
	Light	EN ISO 105/B02	> 5
	Rubbing	EN ISO 105/X12	4-5
	Water	EN ISO 105/E01	4-5
Manufacturing method/type		Tufted, 1/8" cut-pile	
Designs		Hi-definition custom print	
Pile material		100% High Twist Nylon polyamide	
Tuft base		Non-woven polyester	
Backing phthalate free vinyl		EVERFORT vinyl	
	Total weight	ISO 8543	Approx. 3350 gram/m ²
	Pile installation weight	ISO 8543	Approx. 680 gram/m ²
	Pile thickness	ISO 1766	Approx. 5 mm
	Pile density	ISO 8543	0.113 gram/cm ³
	Number of tufts	ISO 1763	Approx. 110.000/m ²
	Comfort class	EN 1307	LC2
	Other remarks	Dirt absorption capacity: 600 g/m ² Moisture absorption capacity: 3-4 l/m ² Production tolerance of 5% on size and colour	
All Coral products meet the requirements of EN 14041, excluding loose-laid mats and rugs			 EN 14041
	Fire behaviour	EN 13501-1	B _{f1} -s1
	Slip resistance	EN 13893	DS
	Personal charging		< 2 kV

