

Marmoleum Modular

LRV & DSDC product accreditation

Please note: ratings only apply when the tiles are installed broadloom/brick bond and in one colour.

Design	Colour number	Colour name	NCS	LRV Y (BS8493)	DSDC Rating*	DSDC Comments*
Linear	t5232	rocky ice	NCS S 3005-Y20R	44	1b	
	t3573	trace of nature	NCS S 5005 - Y20R	27	2	Striped pattern range resembles timber, making is suitable due to its familiar nature
	t5217	withered prairie	NCS S 5010 - Y30R	23	1b	
	t5231	cliffs of moher	NCS S 6005-Y20R	17	2	
	t5253	bleached gold	NCS S 3010-Y20R	42	1b	Striped pattern range resembles timber making it suitable due to its familiar nature.
	t5255	desert sand	NCS S 2010-Y20R	48	1b	Due to subtle mottled but relatively mild and consistent pattern.

Neutral	t3717	moon rock	NCS S 2502 - Y	38	2	
	t3718	quantum	NCS S 3502 - Y	30	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3136	concrete	NCS S 3005-G80Y	47	1b	Due to subtle mottled and familiar concrete pattern.
	t3146	serene grey	NCS S 4502-Y	27	2	Due to apparent mottled and relatively consistent pattern.
	t3048	graphite	NCS S 7502 - Y	14	x	Due to strong contrasting and patchy pattern.
	t3860	silver shadow	NCS S 2005-G70Y	48	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3757	pluto	NCS S 2010-G70Y	51	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3289	sandstone	NCS S 5005-G50Y	48	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3889	cinder	NCS S 3502-Y	30	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3890	oat	NCS S 3010-Y20R	31	x	Due to strong contrasting and patchy pattern.
	t3866	eternity	NCS S 5502-G	21	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3252	sparrow	NCS S 4010 - Y10R	29	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3872	volcanic ash	NCS S 7500-N	10	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3705	meteorite	NCS S 6502-Y	16	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3254	clay	NCS S 6010-Y30R	17	1b	Due to subtle mottled but relatively mild and consistent pattern.

Colour	t3768	linseed	NCS S 3030-Y20R	34	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3774	corn silk	NCS S 2030-Y10R	52	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3772	tiger's eye	NCS S 4030-Y30R	25	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3769	fresh thyme	NCS S 2010-G30Y	48	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3750	pine forest	NCS S 4010-G10Y	32	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3752	taiga	NCS S 6010-B90G	16	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3770	flint	NCS S 3010-B50G	52	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3753	blue ice	NCS S 4010-B10G	29	1b	Due to subtle mottled but relatively mild and consistent pattern.
	t3754	Sirius	NCS S 6020-B10G	12	1b	Due to subtle mottled but relatively mild and consistent pattern.

Marmoleum Modular

LRV & DSDC product accreditation

	2016-074 FORBO FLOORING	
	DSDC RATING KEY	
	NOV-16	
*RATING	*RATING DESCRIPTION	
Class 1a	Flooring within this rating is plain and can be used indiscriminately. That said, bear in mind the need to contrast flooring and walls, skirtings, doors/frames, furniture and sanitary ware. Contrast is the key word. We recommend a minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.	
Class 1b	Flooring within this rating is semi-plain (minimal texture or fleck/pattern, wood effect with no knots) and in general, can be used throughout. Natural patterns such as timber and stone may be used in most areas due to their familiarity but with a degree of caution. Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.	
Class 2	Flooring within this rating has some pattern and needs to be used with caution. The natural patterns such as timber and stone in this range are more figured/patinated and although still familiar they need to be used with more caution than the above range. Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.	

For an environment to be considered 'dementia-inclusive' or 'dementia-friendly', careful consideration must be given to the entire specification, not just the flooring.

As with many design features, individual needs and preferences should also be considered. What is fine for one person, may not be the case for another.

For more information and to download our 'Designing for dementia care' brochure visit www.forbo-flooring.co.uk/care