

HOPSCOTCH, HEMINGBONE, MIX AND MATCH AND FRESH CUT GRAPH IN DIGITALLY PRINTED FLOTEX

HEMINGWAYDESIGN



forbo

FLOORING SYSTEMS

Technical specifications

The Hemingway collection of digitally printed Flotex meets the requirements of EN1307

	Total thickness	ISO 1765	4.3 mm
	Commercial use	EN 685	Class 33 heavy
	Roll width		2.0 m
	Roll length		30 m
	Total weight	ISO 8543	1.8 kg/m ²
	Dimensional stability	ISO 2551 / EN 986	< 0.2%
	Abrasion resistance	EN 1307 annex F	> 1000 cycles
	Castor chair continuous use	EN 985	r = ≥2.4 continuous use
	Light fastness	EN ISO 105-B02	≥ 6
	Slip resistance	Pendulum test	Dry – very low slip risk Wet – low slip risk
	Acoustical	EN-ISO 717-2	Impact sound ΔLw = 20 dB
		ISO 354	Sound absorption = 0.10
	Water tightness	EN 1307 annex G	Pass
	Creating better environments		
	Renewable electricity	Flotex is manufactured using 100% electricity made from renewable sources	
	Recycled content	Flotex sheet contains approximately 20% recycled content by weight	
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor	
	Ska	Flotex meets the Ska Rating criteria for M12 soft floor coverings in both office and retail schemes	
	LCA	LCA is a foundation for securing the lowest environmental impact	

Flotex meets the requirements of EN 14041

CE
EN 14041

	Reaction to fire	EN 13501	B _{fl} -s1
	Slip resistance	EN 13893	DS: ≥ 0.30
	Body voltage	ISO 6356	< 2 kV
	Thermal resistance	ISO 8302	0.048 m ² K/W

For details of pattern repeats, please visit www.forbo-flooring.co.uk/hemingwaydesign

Recommended adhesives

Our recommended adhesive for the Flotex collection is Eurosafe Special 540 or Eurostar Special 640.

BREEAM ratings

Forbo digitally printed Flotex – Flotex F200 HD sheet with PVC backing

Building Type Office	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
A	A	A	B	B	A+	✓

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

Flotex is manufactured in a facility certified to SA8000®.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) or local building rating schemes such as BREEAM.



Contact:

Email: info.flooring.uk@forbo.com
www.forbo-flooring.co.uk

Samples:

Tel: 0800 731 2369