

## Forbo Environmental Data Sheet

<b>Product name</b>	<b>HemingwayDesign X Forbo Mid Century Weave</b>
Product description	HemingwayDesign X Forbo Mid Century Weave features a subtle directional grain and every colourway is constructed using 100% Econyl regenerated polyamide. HemingwayDesign X Forbo Mid Century Weave complies with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets.
Manufacturing location	Bamber Bridge, United Kingdom
Site accreditation	ISO14001, ISO 9001, OHSAS 18001, SA8000®



### Our footprint – how it's made

#### Environmental data

Total recycled content of product by weight	78%
Post industrial recycled content	78%
Post consumer recycled content	0%
Recycled content of yarn	100%
% renewable electricity used	100%

#### Independent assessment and rating

ISO 9001 Quality Management System



ISO 14001 Environmental Management System



OHSAS 18001 Occupational Health and Safety Management



HemingwayDesign X Forbo Mid Century Weave is made in an SA8000® certified facility



#### Carbon footprint

Estimated carbon footprint using data from Environmental product declaration according to ISO 14025

Awaiting data

### Your footsteps – how it performs

#### Health and well being

Air quality  
CHPS 01350

HemingwayDesign X Forbo Mid Century Weave products comply to 01350 Indoor Air Quality Standard

Impact sound reduction

25dB

#### Installation

Recommended adhesives

Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a **solvent free** release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 540 Eurosafe Special, again a **solvent free** adhesive, is recommended.

Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent nonrelease bond.

Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 542 Eurofix tack plus should be used. If a permanent bond is required, please use Eurocol 640 Eurostar special.

**Maintenance**

Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems. HemingwayDesign X Forbo Mid Century Weave carpet tiles are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.

**End of life**

Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle old carpet tiles in the UK.

**Contribution to Green Building Schemes**

**BREEAM**

BREEAM ratings	Building Type			Multi-Residential	Retail (Durability)	Retail (Fashion)
	Office	Education	Healthcare			
	A	A+	A+	A	A	A+

**Ska scheme (RICS)**

M12 soft floor covering criteria (Ska offices Vs 1,2.2013)	Meets
M12 soft floor covering criteria (Ska retail Vs 1,0.2012)	Meets

**LEED (version 2.2)**

Potential direct or indirect contribution to following categories and credits:	<b>Materials and Resources</b>	Materials and resources - construction waste management through Back To The Floor, credit 2
		Regional materials, credit 5
	<b>Indoor environmental quality</b>	Indoor environmental quality, low emitting materials – credit 4.3

**Forbo design principles (Reduce, Recycle, Reuse, Renew)**

<b>Reduce</b>	Investment in an extruder has reduced our bitumen usage by 50%.
<b>Reuse</b>	Yarn ends are rewound and used in the production of new Tessera Carpet tiles. Cutting waste and imperfect tiles can be reprocessed and turned into backing at our Bamber Bridge plant – creating a closed loop process. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin material.
<b>Recycle</b>	Yarns, fillers and compounds all contain recycled materials. All tufted Tessera carpet tiles made in the UK contain at least 50% recycled content by weight.
<b>Renew</b>	All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable electricity.