

coral[®] move FR


Carpet custom made to
your design requirements

coral[®] move FR

Coral Move FR is a tufted carpet solution for rail interiors offering great customisation possibilities to complement interior design and colour schemes.


Benefits:

- Warm and comfortable
- Reaction to fire EN 45545 : HL2
- Excellent soil hiding
- Slip resistant
- Acoustic properties



coral[®] move FR


Coral Move FR is a bespoke made to order product and our design team will work to match design and colour requirements on an individual project by project basis.





Above is only a selection of the colours available, for further information on the full range, please contact us.

Below are just some examples of the designs you can create with Coral Move FR.

Coral Move is available in 136 colours



All Coral Move material is made to order.



coral[®] move FR









TECHNICAL SPECIFICATIONS

Technical specifications





Coral meets the requirements of EN 1307

Coral move FR

	Total thickness	ISO 1765	8 mm
	Roll width	EN-ISO 24341	185 cm (customizable)
	Roll length	EN-ISO 24341	27.5 m (customizable)
	Minimum order quantity		500 m ²
	Total weight	ISO 8543	3000 gram/m ²
	Pile installation weight	ISO 8543	750 gram/m ²
	Pile thickness	ISO 1766	5.5 mm
	Pile material		100% polyamide BCF ECONYL [®]
	Colour fastness ratings:		
	Light	EN ISO 105/B02	8
	Rubbing	EN ISO 105/X12	4-5
	Water	EN ISO 105/E01	4-5
	Seawater	EN ISO 105/E02	5
	Water stains	EN 1307 annex G	5
	Shampoo	BS 1006	4-5
	Organic solvents	EN ISO 105/X05	5
	sted flammability standards	EN 45545-2	HL2

Coral meets the requirements of EN 14041



	Fire behaviour	EN 13501-1	B _{fl} -s1
	Slip resistance	EN 13893	DS: ≥ 0.30
	Body voltage	ISO 6356	< 2 kV
	Thermal conductivity	EN 12524	0.108 m ² K/W

Coral move FR is made to order