






















Technical specifications

Solidstep meets the requirements of EN 13845

	Total Thickness	EN - ISO 24346	2.00 mm
	Thickness wear layer	EN - ISO 24340	0.35 mm
	Commercial very heavy	EN 13845	Class 34
	Light industrial	EN 13845	Class 43
	Collection size		13
	Roll Width	EN - ISO 24341	2.00 m
	Roll Length	EN - ISO 24341	20 - 27 m
	Total Weight	EN - ISO 23997	2.75 kg/m ²
	Dimension Stability	EN - ISO 23999	< 0.1%
	Residual Indentation	EN - ISO 24343-1	≤ 0.05 mm
	Castor Chair	EN-ISO 4918	No effect
	Use in Wet areas	EN 13533	Yes
	Light fastness	EN - ISO 105 B-02	≥ 6
	Flexibility	EN - ISO 24344	ø 10mm
		EN 13845 Annex C	ESf
	Slip resistance	EN 13845 Annex D 50.000 revolutions <10% loss	Class 34/43
		DIN 51130	R10
	Chemical resistance	EN-ISO 26987	Very Good
	Electrical resistance	EN 1081 (R1)	> 1.10 ⁹ Ω

Solidstep meets the requirements of EN 14041



	Reaction to fire	EN 13501-1	B ₁ -s1
	Body Voltage	EN 1815	< 2kV
	Thermal Conductivity	EN 12524	0.25 W/m.K
	Slip resistance	EN 13893	DS ₁ ≥ 0.30

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
 All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
 The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPDs) which can be found on all of our websites.

