













Technical specifications

flotex[®] classic

Flotex classic meets the requirements of EN 1307

	Total thickness	EN 428 / ISO 1765	4.3 mm
	Roll width	EN 426	200 cm
	Roll length	EN 426	30 m
	Total weight	EN 430 / ISO 8543	1800 gram/m ²
	Pile installation weight	ISO 8543	Approx 250 gram/m ²
	Pile thickness	ISO 1766	Approx 2 mm
	Pile material		100% polyamide
	Dimensional stability	EN 434 ISO 23999 / ISO 2551	≤ 0.2%
	Light fastness	EN ISO 105/B02	≥ 6
	Resistance to chemicals	EN 423 / ISO 26787	Very good
	Contact sound insulation	ISO 140-8	ΔLw = 20 dB
	Slip resistance	DIN 51130 / 51131 EN 13893	R13 DS: > 0.30
	Fire resistance	ECE-R 118 / FMVSS 302	Approved
	Personal charging	ISO 6356	< 2 kV
	Heat transmission resistance	EN 12524	0.048 m ² K/W

All countries

Forbo Flooring Systems
 High Holborn Road
 Ripley
 Derbyshire DE5 3NT
 UK
 Tel: +44 (0) 1773 744121
 Fax: +44 (0) 1773 744142
 Email: info@forbo-transportflooring.com
www.forbo-flooring/transportation

Registered Office:

Forbo Flooring UK Limited
 High Holborn Road, Ripley
 Derbyshire DE5 3NT
 Registered in England: 9200318