













Technical specifications

coral[®] classic FR

Coral classic FR meets the requirements of EN 1307

| | | | |
|---|-------------------------------|----------------------------------|----------------------------------|
|  | Total thickness | EN 428 / ISO 1765 | Approx 8.5 mm |
|  | Roll width | EN 426 | 185 cm (customizable) |
|  | Roll length | EN 426 | 27.5 m (customizable) |
|  | Total weight | EN 430 / ISO 8543 | Approx. 3400 gram/m ² |
| | Pile installation weight | ISO 8543 | Approx. 900 gram/m ² |
| | Pile thickness | ISO 1766 | Approx. 6.0 mm |
| | Pile material | 100% polyamide-BCF solution dyed | |
|  | Light fastness | EN ISO 105/B02 | 7-8 |
|  | Flexibility | EN 435 / ISO 24344 | |
|  | Resistance to chemicals | EN 423 / ISO 26787 | |
|  | Electrical resistance | EN 1081 / ISO 10965 | Approx. 10 ¹⁰ Ω |
|  | Contact sound insulation | ISO 717-2 ISO 140-8 | Δ Lw = approx. 31 dB |
|  | Tested flammability standards | EN 45545-2 | HL2 |
| | | BS6853 | 1b |
| | | DIN 5510-2 | SF 1-3 |
| | | ASTM E.648-08 ASTM E.662-06 | Class 1 pass |
| | | NF P 92-501 NF F 16-101 | M2 F1 |
| | | | |
|  | Personal charging | ISO 6356 | < 2 kV |
|  | Heat transmission resistance | EN 12524 | 0.13 m ² K/W |

All countries

Forbo Flooring Systems
 High Holborn Road
 Ripley
 Derbyshire DE5 3NT
 UK
 Tel: +44 (0) 1773 744121
 Fax: +44 (0) 1773 744142
 Email: info@forbo-transportflooring.com
www.forbo-flooring/transportation

Registered Office:

Forbo Flooring UK Limited
 High Holborn Road, Ripley
 Derbyshire DE5 3NT
 Registered in England: 9200318