

eurocol **543 eurosafe deco**

High quality solvent-free adhesive for the installation of PVC strips and tiles.

Product advantages

- Non-flammable
- Solvent-free
- Roller-castor-chair resistant
- Favourable spreading capacity
- No grin through of adhesive trowel marks
- Easy and safe to apply
- High final bond strenght

Basis	Acrylic dispersion.
Colour	Blue.
Consistency	Liquid.

Application

For the installation of PVC strips and tiles on smooth subfloors.

543 eurosafe deco

Working Process

Subfloor

- 543 Eurosafeco Deco is suitable for any type of subfloor that has good tensile and compression strength. The subfloor should also be even, clean, permanently dry and free from grease and dirt according to the requirements of BS 8203 or DIN 18 365.
- Anhydrite floors should be sandpapered. Thereafter make the floor dust free and prime with 044 Europrimer Multi. This layer has to dry sufficiently.
- For an optimal final result, apply a 2 mm levelling compound layer on the subfloor.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

Working conditions

Required surrounding temperature: 18° - 23 °C
Temperature for material and subfloor: min. 15° C - max. 20° C.
Relative humidity: 40-80%.

Directions for use

- Apply 543 Eurosafeco Deco equally in the recommended quantity with a lambswool roller or brush on the subfloor.
- The strips or tiles can be placed directly into the wet, semi moist or dry adhesive.
- Drying time is depending on temperature, relative humidity and the porosity of the subfloor.
- After applying carefully roll and firmly rub the strips or tiles in to the adhesive line.
- Drying time minimal 24 hours.
- Remove fresh adhesive spots immediately with a clean damp cloth.

Underfloor heating systems

543 Eurosafeco Deco can be applied on underfloor heating systems. Turn off the heater 24 hours before fixation. Do not heat again until at least 24 hours after fixation, in steps of maximum 5 °C water temperature per day. If there is the possibility that the PVC- strips or tiles can be warmer than 30 °C (also by sunlight), you have to choose for a polyurethane bonding.

Packaging

10 kg bucket.

OUR DIRECTIONS FOR USE ARE BASED ON ACCURATE LABORATORY TESTS AND EXTENSIVE PRACTICAL EXPERIENCES. HOWEVER, WE CANNOT TAKE RESPONSIBILITY FOR EXECUTED WORK AND THEREFORE WE ADVISE YOU TO MAKE TESTS AT THE PLACE OF WORK. OTHERWISE WE REFER TO OUR GENERAL SALES CONDITIONS.

