

MARMOLEUM ACCESSORIES

Adhesives

► MANDATORY




	Adhesives	Weight	Cons. m ²	Spatula	Waiting time	Opening time	Observations
Marmoleum	418 Euroflex lino polaris	14 kg	400 g	B1	10 min	30 min	For all Marmoleum ranges in jute strips
	611 Eurostar lino plus	11 kg	280 g	B1	10 min	30 min	For all Marmoleum ranges on jute backing, EMICODE EC1 ^{PLUS}
	644 Eurostar multi plus	12 kg	390 g	B1	15 min	40 min	Fiber-reinforced universal adhesive, EMICODE EC1 ^{PLUS} . High performance
	540 Eurosafe special	13 kg	350 g	A2	15 min	60 min	Technical adhesive High performance
Marmoleum modal	640 Eurostar special	13 kg	250 g	A2	15 min	60 min	Technical adhesive EMICODE EC1 ^{PLUS} . High performance
Marmoleum decibel	528 Eurostar all round	13 kg	300 g	A2	15 min	40 min	Construction adhesive EMICODE EC1 ^{PLUS} , multi-purpose
	644 Eurostar multi plus	12 kg	390 g	B1	15 min	40 min	Fiber-reinforced universal adhesive, EMICODE EC1 ^{PLUS} . High performance
Marmoleum sport	611 Eurostar lino plus	11 kg	280 g	B1	10 min	30 min	Combine with 863 Eurofinish sport (sport lacquer system) and use 897 Euroclean sport for initial and complete maintenance
Marmoleum ohmex	615 Eurostar lino EC	11 kg	260-300 g	S2	10 min	20 min	To be with 041 Europrimer EC and 801 self-adhesive copper tape
	611 Eurostar lino plus	11 kg	350 g	B1	10 min	30 min	Apply 611 to the entire surface and, for the edges, apply 650 to approximately 30 cm (to reinforce large widths).
Bulletin board	650 Eurostar fastcol	7,5 kg	500 g	Tools included	1-2 h	4 h	

520 Linoleum doctor

520 Linoleum doctor renovation adhesive is a kit for repairing bubbles on the underside of Marmoleum with jute or polyoeffin backing (Marmoleum decibel).

Kit containing a 500 ml bottle of adhesive and 2 syringes

Ref.: 520



Welding

► IMPORTANT

LINO welding rod

Welding allows the junction between strip edges. Marmoleum achieves E2 rating. A groove is formed, and the weld is then applied using a hot air gun fitted with a LINO fast welding nozzle.

Coil of 50 m, round welding rod for uni references

Ref.: LD + floorcovering reference

Coil of 50 m, square welding rod for multicolored references

Ref.: MC + floorcovering reference



MARMOLEUM ACCESSORIES

Profiles


► IMPORTANT

Cove former

- 3009 = 15 x 15 : this profile is used vertically in internal corner to that the wall covering matches corners perfectly.
- 3109 = 20 x 20 : this profile is used at the bottom of partitions. Provides backing for the floorcovering to rise with a rounded profile, thus making corners last longer and improving aesthetics, while preventing perforation.
- 3209 = 25 x 25 : same using as the 20x20 profile but appropriate for more rigid floorcovering.

Box of 20 lengths of 2,5 m namely 50 m/box.


Ref. : 3009 blanc / 3109 noir / 3209 noir




Stairnosing to install before and after floorcovering

Phosphorescent PVC stairnosing with structured support surface to be installed before (xxxxTF) or after (xxxxTJ) the floorcovering is laid.

Box of 10 lengths of 2,5 m namely 25 m/box



Ref : xxxxTF (before)



Ref : xxxxTJ (after)



0110 - noir



0138 - gris clair



0146 - gris foncé



0130 - beige




0132 - brun

PVC capping profile EL3.5

PVC capping strip is the right finishing profile when you would like to have a perfect finishing with coving installation. Ideal for Linoleum floorcovering.

Box of 20 lengths of 2,5 m namely 50 m/box



0110 - noir



0146 - gris foncé



1137 - blanc



0132 - brun



0130 - beige



0138 - gris clair

MARMOLEUM ACCESSORIES



Skirtings

► RECOMMENDED

Soft complete skirting for old and new support

Flexible finishing profile for corner support and finishing. Its flexibility makes it suitable for both new and old substrates.

Box of 20 lengths of 2,5 m namely 50 m/box



3251 - gris



3252 - blanc



3253 - beige



Marmoleum 3588 | eucalyptus

Marmoleum click skirting

Marmoleum click MF skirting of 55 mm in height. MDF skirting with Marmoleum facing. It is applied using a type 882 Eurobond Hightack mounting adhesive.

Box of 4 lengths of 2,4 m namely 9,6 m

Ref : MFxxxx



MF3355
rosemary green



MF3358
petrol



MF3573
trace of nature



MF3702
liquid clay



MF3707
black hole



MF3858
barbados



MF3860
silver shadow



MF3866
eternity



MF5217
withered prairie

Mounting adhesive

Enables the installation of PVC and Marmoleum click skirtings.

Technical characteristics:

- Skin formation time : approx. 10 min at 23°C and 55 % relative humidity.
- Setting time : approx. 24 h.

Box of 12 cartridges of 290 ml

Ref. : 882 Eurobond hightack

