

Care Guidelines for Forbo Marmoleum® with Topshield2™ Wall Applications

The Forbo Marmoleum® features Topshield2™, a waterborne UV cured double layer factory coating. This finish has been designed to meet the demands of everyday use and is even more resistant to dirt absorption, less prone to wear and has improved resistance to scratches and stains, and thus demonstrating lasting performance over time.

KEY POINTS

- Stains should be removed as quickly as possible to eliminate permanent damage.
- Excess soiling materials such as chewing gum, nail polish, lipstick, asphalt, crayon, ink, marker, paint, lacquer, enamel, tar or foodstuffs should be removed or carefully scraped off the flat side of a plastic scraper prior to any other cleaning attempts below. For tough soiling materials, Forbo Adhesive Remover may be used.

CLEANING RECOMMENDATIONS

1. Remove all surface dust and debris by dusting.
2. Mix a neutral pH cleaning solution according to the label directions.
IMPORTANT: The pH of the cleaner in solution must be between 6 – 8 pH. Please refer to the list at the end of this document for recommended products.
3. Apply the solution with a microfiber cloth or sponge.
4. Wipe the area to loosen and remove any soil.
NOTE: For heavy soil loads or difficult to remove soil deposits, the use of a soft bristled brush is recommended.
5. Rinse the area thoroughly with clean, cool water. Change the water often to ensure it remains clean and clear.
6. Dry the area thoroughly with an absorbent cloth so it can be examined to ensure proper cleaning.

RECOMMENDED PRODUCTS

Neutral pH Cleaners

Forbo Neutral pH Cleaner
ProLink Level 7
Spartan Damp Mop
3M Neutral Cleaner 3H
Diversey Stride

Spot Cleaner

Forbo Adhesive Remover

Forbo's Floor Care Guide contains additional information about floor care and is available for download at www.forboflooringna.com. For a hard copy, or for additional information on Topshield2™, contact Forbo's Product Support & Education Services at +800 842 7839.