

Floor Care Guidelines for Forbo Marmoleum® Sheet & Tile with Topshield2™

The Forbo Marmoleum® product range includes: Marmoleum® sheet (including Marmoleum® Striato Textura), Marmoleum® Decibel sheet, Marmoleum® Composition Sheet (MCS), Walton sheet, Marmoleum® Modular (including Marmoleum® Modular Striato Textura) and Marmoleum® Composition Tile (MCT).

Forbo Marmoleum® and linoleum products are a homogeneous floor covering made from natural ingredients including linseed oil, rosin binders, wood flour, limestone and dry pigments which are mixed and then calendared onto a natural jute backing and they feature Topshield2™. Topshield2™ is a high performance finish. Its double layer UV cured technology delivers extraordinary performance and clear and vibrant colors that remain over time. Marmoleum® with Topshield2™ requires no initial maintenance or polymer application. This means that at the time of installation, cleaning with a neutral pH cleaning solution is all that is necessary. The surface can be repaired or refreshed in cases of accidents or after years of intensive use.

IMPORTANT!

Before starting any cleaning procedures on any Forbo products, contact Forbo's Product Support & Education Services for additional information, recommendations or to schedule a site visit. The best results may not be achieved if the chemical and equipment types recommended below are not used. The size of the equipment recommended may also vary based on the size of the space or application type.

INITIAL CLEANING

Cleaning performed for new installations exposed to normal construction soil and traffic. In order to allow the adhesive to dry and cure properly, wait a minimum of five days following the installation before conducting initial cleaning or other wet cleaning procedures. For installations over non-porous substrates, additional time may be necessary because the adhesive may take longer to dry and cure.

1. Remove all surface soil, debris, sand and grit by dust mopping the floor with 3M™ Easy Trap, sweeping or vacuuming.
2. Mix a neutral pH cleaning solution according to the label directions. The pH of the cleaner in solution must be between 6 – 8 pH. Refer to the list at the end of this section for recommended products.
3. Apply the solution to the floor. Do NOT flood the floor. The solution can be applied with either a mop or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent.
4. Scrub the floor with either a low speed rotary machine such as Tennant/Nobles FM-17-SS or equivalent or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent using a 3M™ Red Buffer Pad #5100 or equivalent. If using an automatic scrubber, it is recommended to double scrub the floor.

NOTE: For heavier soil loads or to remove adhesive residue, use a 3M™ TopLine Autoscrubber Pad #5000 or equivalent.

5. Pick up the scrubbing solution with a wet vacuum such as Tennant/Nobles V-WD-15S or equivalent or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent.

NOTE: For flooring with embossment, it is easier to recover the solution by running the equipment perpendicular to the embossment.

6. Rinse the entire floor surface with a clean mop using clean, cool water. Pick up rinse water with wet vacuum such as Tennant/Nobles V-WD-15S or equivalent or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent.
7. Allow the floor to dry thoroughly before allowing traffic.

ROUTINE CLEANING

Cleaning performed a minimum of once a day, depending on the application, type of traffic and hours of operation.

1. Stains or spills should be wiped or mopped up immediately with a damp mop using a neutral pH cleaning solution. Rinse the affected area with clean, cool water. Be sure to allow the floor to dry thoroughly before allowing traffic. The pH of the cleaner in solution must be between 6 – 8 pH. Refer to the list at the end of this section for recommended products.
2. Remove all surface soil, debris, sand and grit by dust mopping the floor with 3M™ Easy Trap, sweeping or vacuuming.
3. Mix a neutral pH cleaning solution according to the label directions. The pH of the cleaner in solution must be between 6 – 8 pH. Refer to the list at the end of this section for recommended products.
4. Apply the solution to the floor. Do NOT flood the floor. The solution can be applied with either a mop or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent.
5. Scrub the floor with either a low speed rotary machine such as Tennant/Nobles FM-17-SS or equivalent or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent using a 3M™ Red Buffer Pad #5100 or equivalent. If using an automatic scrubber, it is recommended to double scrub the floor.

Floor Care Guidelines for Forbo Marmoleum® Sheet & Tile with Topshield2™

NOTE: For heavier soil loads, a 3M™ TopLine Autoscrubber Pad #5000 or equivalent may be used.

- Pick up the scrubbing solution with a wet vacuum such as Tennant/Nobles V-WD-15S or equivalent or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent.

NOTE: For flooring with embossment, it is easier to recover the solution by running the equipment perpendicular to the embossment.

- Rinse the entire floor surface with a clean mop using clean, cool water. Pick up rinse water with wet vacuum such as Tennant/Nobles V-WD-15S or equivalent or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent.
- Allow the floor to dry thoroughly before allowing traffic.

INTERIM CLEANING

Cleaning performed as needed, depending on the application, type of traffic and hours of operation. The following processes should be followed when the routine cleaning is not removing the soil from the floor.

- Remove all surface soil, debris, sand and grit by dust mopping the floor with 3M™ Easy Trap, sweeping or vacuuming.
- For light soiling, mix a neutral pH solution according to the label directions. The pH of the neutral cleaner in solution must be between 6 – 8 pH. For medium or heavy soiling, mix 2 oz. of a general purpose cleaner per gallon of water. The pH of the general purpose cleaner in solution must be between 8 – 10.4 pH. Please refer to the list at the end of this section for recommended products.
- Apply the solution to the floor. Do NOT flood the floor. The solution can be applied with either a mop or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent.
- Scrub the floor with either a low speed rotary machine such as Tennant/Nobles FM-17-SS or equivalent or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent using either a 3M™ Red Buffer Pad #5100 or equivalent for light soiling or a 3M™ TopLine Autoscrubber Pad #5000 or equivalent for medium or heavy soiling.
- Pick up the scrubbing solution with a wet vacuum such as Tennant/Nobles V-WD-15S or equivalent or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent.

NOTE: For flooring with embossment, it is easier to recover the solution by running the equipment perpendicular to the embossment.
- Rinse the entire floor surface with a clean mop using clean, cool water. Pick up rinse water with wet vacuum such as Tennant/Nobles V-WD-15S or equivalent or an automatic scrubber such as Tennant T300, Nobles Speed Scrub EX or equivalent.
- Allow the floor to dry thoroughly before allowing traffic.
- If desired, one of the following procedures can be performed:
 - Spray buff the floor using a low speed rotary machine such as Tennant/Nobles FM-17-SS or equivalent and a 3M™ Red Buffer Pad #5100 or equivalent, followed by dust mopping.
 - Apply a mop-on restorer according to the label directions. Burnish the floor using a burnisher such as Tennant/Nobles BR-2000-DC or equivalent with a 3M™ Eraser Pad #3600 or equivalent, followed by dust mopping.
 - Burnish / Dry Buff the floor using a burnisher such as Tennant/Nobles BR-2000-DC or equivalent with a 3M™ Eraser Pad #3600 or equivalent, followed by dust mopping.
- If the floor requires restoration cleaning procedures, contact Forbo Product Support & Education Services.

NOTE:

Weather, traffic and geographical location will influence the required frequency of this procedure. For example, in areas where there are large amounts of snow and chemicals used in the winter months it will likely be necessary to perform this procedure more frequently. In dry climates, or where there is less dirt traffic, it may not be necessary to perform this procedure as frequently.

CAUTION:

Marmoleum® with Topshield2™ can be damaged by traditional wet stripping methods. If the above floor care recommendations are followed, wet stripping will NOT be necessary. If wet stripping methods are or have been used on the floor, contact Forbo Product Support & Education Services for additional information.

Floor Care Guidelines for Forbo Marmoleum® Sheet & Tile with Topshield2™

Forbo Marmoleum® should be cared for by a staff trained to understand the following:

- A regular floor care program, as described above, should be followed closely.
- Forbo Marmoleum® with Topshield2™ is OCCUPANCY READY following installation.
- The removal of Topshield2™ is NOT recommended.
- If finish is applied, Topshield2™ is no longer the wear surface and the properties it provides to Marmoleum® will be compromised.
- If applying a third party polymer to Marmoleum®, follow the manufacturer's recommended guidelines.
- It is the responsibility of the chemical manufacturer to provide a resolution for any issues that may arise when using their product on Forbo Marmoleum® and linoleum products.

RECOMMENDED FLOOR CARE PRODUCTS

Neutral pH Cleaners:

Forbo Neutral pH Cleaner
 3M™ Neutral Cleaner 3H
 Pro-Link Level 7
 Spartan Damp Mop
 Diversey Stride

Spray Buffs:

Forbo Spray Buff
 3M™ Top Line Pre-Burnish Conditioner
 Pro-Link Enhance
 Spartan Spray Buff

Mop on Restorers:

Forbo Mop on Restorer
 3M™ Top Line Pre-Burnish Conditioner
 Pro-Link Optimum Response
 Spartan SunSwept
 Diversey Revive

General Purpose Cleaners

Forbo Heavy Duty Cleaner
 3M™ General Purpose Cleaner/Concentrate 8H
 Pro-Link Synthetic Floor HD Cleaner
 Spartan Industrial Pathmaker
 Diversey Profi
 Diversey GP Forward

For additional information on a product or for your local supplier, contact:

Forbo Flooring Systems
 US+800 842 7839
 CA +800 268 8108
www.forboflooringNA.com

Tennant Company
 US/CA +800 553 8033
 QC +800 361 9050
www.tennantco.com

3M™
 +800 852 9722
www.3m.com/building

ProLink
 +800 745 4657
www.prolinkhq.com

Spartan
 +800 537 8990
www.spartanchemical.com

Diversey
 +800 558 2332
www.diversey.com

Forbo's Floor Care Guide contains additional information about floor care and is available for download at www.forboflooringNA.com. For a hard copy, or for additional information on Topshield2™, contact Forbo's Product Support & Education Services at +800 842 7839.