

Technical Bulletin

Cove Ezi - Australian Pre-Formed Marmoleum Coving

Cove - Ezi is manufactured Marmoleum pre-formed coving in 2.40 lineal metre lengths in 2.50 mm and 2.00 mm **thickness** which has an integrated profile support backing.

Cove - Ezi comes with **Forbo Warranty**.



The benefits of Cove - Ezi

1. Cove - Ezi offers ease of installation, speed, cost effectiveness and the opportunity for the designer to use a coloured boarder off set to that of the field colour. A contrasting coloured welding rod can then be used as a design feature around the perimeter of the installation.
2. Cove - Ezi can be manufactured to order in various cove heights and base widths in 2.40 L/m lengths
3. Cove - Ezi can be manufactured to accommodate separate internal and external corners
4. Cove - Ezi can be manufactured to order in the complete Marmoleum colour range
5. Cove - Ezi is cleaning machine bump resistant, avoiding mechanical damage
6. Cove - Ezi is stair riser toe kick resistant, avoiding mechanical damage at the riser, tread junction
7. Cove - Ezi has a 10 mm cove base radius which gives it strength and uniform neatness against door jambs and other internal and external protrusions.

Note: Cove - Ezi has minimum order requirements for varying cove heights and base widths.

Technical Bulletin

Cove Ezi - Australian Pre-Formed Marmoleum Coving



Cove - Ezi Installation

1. Cove - Ezi should be unpacked and acclimatized at 18 degrees C as per AS 1884-1985 recommendations.
2. Cove - Ezi lengths should be laid out with the jute side and support backing facing upwards in the form of tents.
3. Cove - Ezi can be stacked in multiple lengths one on top of the other, in this way it will help to alleviate some tension brought about by the packaging, storage and freighting process.
4. Cove - Ezi can be installed using **high solid contact adhesives**, sprayed, rolled or brushed on. In most cases **two coats of adhesive should be applied** to the cove backing to achieve a thick adhesive build up. Low solid skirting contact adhesive should not be used as some adhesive solids may be lost / absorbed into the Marmoleum back and have an inferior adhesive build up.
5. Cove - Ezi can also be installed using Forbo Fix 414 adhesive, brushed, rolled or trowelled on with a 2.4 x 2.4 mm "V" notch trowel. Please test a small area of coving to familiarize yourself when using Forbo Fix 414 adhesive process.