Technical specifications


Coral classic tile meets the requirements of EN 1307





Total thickness	ISO 1765	Approx 9 mm
Wear classification	EN1307	33, commercial heavy
Colours		13
Tile sizes		50 x 50 cm (12 tiles in a box = 3m ²)
Colour fastness ratings:		
Light	EN ISO 105/B02	7-8
Rubbing	EN ISO 105/X12	4-5
Water	EN ISO 105/E01	4-5
Seawater	EN ISO 105/E02	4-5
Waterstains	EN 1307 annex G	4-5
Shampoo	BS 1006	4-5
Organic solvents	EN ISO 105/X05	4-5
Manufacturing method/type		Tufted, 5/32" cut-pile
Designs		Multi coloured designed/coloured
Pile material		100% polyamide-BCF solution dyed
Tuft base		Non-woven polyester
Backing (phtalate free vinyl)		EVERFORT® vinyl (also available with bitumen backing)
Total weight	ISO 8543	Approx 4700 gram/m ²
Pile installation weight	ISO 8543	Approx 870 gram/m²
Pile thickness	ISO 1766	Approx 7 mm
Pile density	ISO 8543	0.100 gram/cm ³
Number of tufts	ISO 1763	Approx 61,500/m²
Comfort class	EN 1307	LC3





All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Coral is manufactured in a facility certified to SA8000® and OHSAS 18001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's) or local building rating schemes such as BREEAM.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this samplebook are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this samplebook and does not represent that the information is accurate, complete or current and you are advised to visit our website at **www.forbo-flooring.co.uk** for up-to-date details or corrections to such contents.







