

898

LOGLIFE BASIC PROTECTION

PRODUCT DESCRIPTION

Highly durable protective coating for initial care and refreshing for:

- parquet and cork floorings, which were manually sealed with water-based Eurocol products
- elastic floorings, which were renovated with Eurocol CFloor
- Eurocol BetonDesign surfaces, which were coated with Eurocol Top Coat.

To use for refreshing of used, waterproof floorings after careful base cleaning.

Anti-slip and dirt-repellent, resistant to scuff-marks.

Different gloss levels available.

PRODUCT SPECIFICATIONS

- Highly durable
- Highly resilient
- Satin-gloss, matt

AREAS OF USE



Protection agent suitable for:

- initial care of water-resistant floor coverings e.g. sealed parquet, linoleum, PVC, (plastic coating coat for surface protection)
- Initial care of manually sealed (with aqua lacquer) parquet and cork
- plastic hard coating of elastic floorings, which were renovated with Eurocol CFloor
- plastic hard coating for BetonDesign surfaces, which re coated with Eurocol Top Coat
- refreshing old, water-resistant floor coverings and old plastic coating coats

NOT for use on rubber, on floor coverings/parquet with PU and UV sealants

TECHNICAL DATA

Base	polyacrylate
Colour	milky
Density	approximately 1,02 g/cm ³
pH-Value	9
Cleaning agent	water (fresh 898)

898

Euroclean Longlife

	891 Euroclean Basic (dried 898)
Processing conditions	not below 15 °C on the subfloor material- and room temperature not below minimum 18°C material- and room temperature 35-75% relative air moisture, recommended <65%,
Consumption	1 l for approximately. 40 m ² (1 coat)
Shelf-life	within 24 months if stored in its original packing once opened packaging to be tightly closed and product to be used as soon as possible
Frost resistance	not
Storage condition	packaging to be tightly closed at a dry place, temperature: (5 – 30) °C,
Code acc. to GHS	no
Environment/Work safety	GISCODE: GE10 DGNB: VOC 2,9-5,0 %, quality level: 3, depending on the degree of gloss LEED: VOC 29-52 g/l, depending on the degree of gloss Contains: 1,2-Benzisothiazol-3(2H)-on. May cause allergic reaction.

INSTRUCTIONS FOR USE

- Shake well before use in order to achieve an equally matt finish on the whole floor.
- After professional cleaning with e.g. Eurocol 891 Euroclean Basic, please use wipe with fresh, clean water.
- Then 898 Euroclean Longlife is to be applied with a lint-free cloth or Eurocol wipe (Art. 78247) undiluted once or twice.
- Please apply 898 Euroclean Longlife onto the floor always in one operation to avoid overlapping.
- For absorbent floors and floors with open pores, several coats of 898 Euroclean Longlife might be necessary to get a closed film of 898 Euroclean Longlife.
- The drying time of each coat at normal room climate is 1 – 3 hours (ready for foot traffic).
- If heavy traffic is to be expected, approximately 12 hrs. drying time over night is recommended.
- Refreshing old floors: Please make sure that the old floors are free of cleaning product residues (professional base cleaning has to be carried out). Afterwards please wipe the floor off twice with cold, fresh water. Before applying 898 Euroclean Longlife, allow the floor to dry for a minimum of 12 – 24 hours.

SAFETY NOTE

- Pay attention to the technical Information and safety data sheets of the used floorings and parquets.
- Initial care of lacquered parquet can only be done once the lacquer has completely dried.
- Initial care of elastic floor coverings should be done prior to start of traffic.
- Please pay attention to the care instruction for maintenance care.
- Old residues of 898 Euroclean Longlife have to be removed with Eurocol 891 Euroclean Basic (professional cleaning).
- Relevant norms and regulations of the branch are to be respected.
- Outside Germany relevant national regulations have to be applied which have to be known by the installer.

PACKAGING

0,75 l, 10 l nonreturnable package

SPECIAL NOTE

Any other application than those specified in this Technical Information requires our explicit approval. Otherwise no liability can be assumed.

The information contained in this product information has been based on experiences derived from laboratory and practical work. The great versatility of materials, many different processing and storage methods and local conditions beyond our control make it impossible to give guarantees for processing results. Therefore, customers are recommended to find the optimum for their particular application case by suitable self-made tests. The General Terms and Conditions of our company shall apply.

Forbo Eurocol Deutschland GmbH
August-Röbling-Straße 2
99091 Erfurt, Germany

Phone +49 361 7 30 41 0
Fax +49 361 7 30 41 90
info.erfurt@forbo.com
www.forbo-eurocol.de

Geschäftsführer: Rüdiger Beez
Handelsregister HRB 100351 Jena (D)
Ust.-IdNr. DE 811 178 280

898

Euroclean Longlife

This Technical Information supersedes all other application data sheets and product information published before.

Last updated 2016-02-29
Supersedes issue as of 2011-02-28

Version Nr.:07
75225-06_898