

Forbo Environmental Data Sheet

Product name	Marmoleum 2.0mm Sheet
Product description	Marmoleum is a linoleum floor covering complying with all the requirements of EN-ISO 24011: Specification for plain and decorative linoleum
Manufacturing location	Assendelft, Netherlands Kirkcaldy, United Kingdom
Site accreditation	ISO14001, ISO 9001, ISO 45001, SA8000®
Range names	Marmoleum Real Vivace Fresco Walton Cirrus Piano Cocoa Concrete Slate



Our footprint – how it's made

Environmental data

Total recycled content of product by weight	43%
Post industrial recycled content	43%
Post consumer recycled content	0%
% renewable electricity used	100%

Independent assessment and rating

Nordic Swan	
Allergy UK Seal of Approval	
ISO 9001 Quality Management System	
ISO 14001 Environmental Management System	
ISO 45001 Occupational Health and Safety Management	
Marmoleum is manufactured in a SA8000® certified facility	

Carbon footprint

Estimated carbon footprint using data from Environmental product declaration according to ISO 14025	Cradle to gate (A1-A3)	-0.111 kg CO ₂ eq/m ²
	Use (1 year) (B2)	0.0635 kg CO ₂ eq/m ²

Your footsteps – how it performs

Health and well being

Marmoleum is an Indoor Air Comfort GOLD certified product	
Allergy UK	Marmoleum achieves the Allergy UK Seal of Approval
Impact sound reduction	4 dB
Bacteriostatic properties	Marmoleum has independent tests to prove that it inhibits bacteria such as MRSA, C Difficile, Norovirus, Acinetobacter baumannii

Installation

Recommended adhesives	Forbo recommends the use of 414 Euroflex Lino Plus. Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 611 Eurostar Lino plus should be used.
	Installation off-cuts of Marmoleum can be collected via our Back to the Floor scheme and recycled back into Marmoleum at our plant in Scotland.

Maintenance

Topshield Pro Unique dual layer finish. Resistant to staining and scuffing so reducing the amount of cleaning required. Can be completely renovated, unlike PUR finishes.

End of life

Marmoleum can be recycled or composted.

Contribution to Green Building Schemes

BREEAM 2018

Compliant through declaration number 4790690881.101.1 – Valid until April 1 2028

Ska scheme (RICS)

M12 soft floor covering criteria	(Ska Offices Vs 1.2 2013) Meets	(Ska Retail Vs 1.0 2012) Meets	(Ska Higher Education Vs 1.0 2016) Meets
----------------------------------	------------------------------------	-----------------------------------	---

LEED (version 4.1)

Potential direct or indirect contribution to following categories and credits:	Materials and Resources	Building product disclosure and optimisation - EPD up to 2 points
		Building product disclosure and optimisation - sourcing of raw materials - up to 1 point
		Construction and demolition waste management up to 2 points
	Indoor environmental quality	Low emitting materials up to 3 points
		Acoustic performance up to 1 point

Forbo design principles (Reduce, Recycle, Reuse, Renew)

Reduce Marmoleum's Topshield Pro finish significantly reduces cleaning and maintenance costs in life. Marmoleum is made from 97% natural raw materials.

Reuse All Marmoleum site offcuts can be returned to Forbo for reprocessing using our **Back to the Floor** initiative. After Marmoleum's long life it can be incinerated for landfill and this reclaims more energy that is used in production. It is also biodegradable in a controlled environment.

Recycle Packaging used to deliver raw materials is separated and recycled externally.

Renew All Marmoleum is produced using 100% renewable electricity. Marmoleum contains 62% renewable materials.

Detailed environmental product declarations and full Life Cycle Analysis

visit www.forbo-flooring.co.uk/downloads for more information