

## Technical specifications

Sarlon trafic modul'up meets the requirements of EN 14041 (EN 651)



**COMMITTED  
TO THE HEALTH  
OF ONE**

WWW.FORBO-FLOORING.COM/CHO

# sarlon® trafic modul'up

## Sarlon trafic modul'up

	Total thickness	EN 428 (ISO 24346)	3,45 mm
	Wear layer thickness	EN 429 (ISO 24340)	0,67 mm
	Total weight	EN 430 (ISO 23997)	2,830 g/m <sup>2</sup>
	Impact sound reduction	EN ISO 717-2	$\Delta L_w = 19$ dB
	Acoustic absorption	EN ISO 354 EN ISO 11654	$a_w = 0.05$
	Residual indentation <i>Measured minimum value Requirement</i>	EN 433 (ISO 24343-1)	0,08 mm <i>0.06 mm ≤ 0.20 mm</i>
	Slip resistance	DIN 51130	R9
	Abrasion resistance	EN 660-2 (ISO 24338)	T
	Specifications		EN 651 (ISO 11638)
	Residential use	EN 685 (ISO 10874)	-
	Commercial use	EN 685 (ISO 10874)	34
	Industrial use	EN 685 (ISO 10874)	42
	Packaging		Rolls
	Roll length	EN 426 (ISO 24341)	25 lm
	Roll width	EN 426 (ISO 24341)	2 m
	Castor chair resistance	EN 425 (ISO 4918)	Yes
	Furniture leg resistance	EN 424 (ISO 16581)	Compliant
	Dimensional stability <i>Requirement</i>	EN 434 ISO 23999	< 0.05 % ≤ 0.40 %
	Colour fastness to light <i>Requirement</i>	EN ISO 105-B02	≥ 7 ≥ 6
	Stain resistance	EN 423 (ISO 26987)	Good
	Surface treatment		OVERCLEAN XL
	Emissions into air : TVOC* at 28 days	NF EN ISO 16000 (ISO 10580)	< 20 µg/m <sup>3</sup>
	REACH (European regulation)	1907/2006/CE	Compliant <sup>(1)</sup>
	Raw materials		Without phthalate
	CE Compliance EN 14041		Yes
	Reaction to fire	EN 13501-1	C <sub>n</sub> - s1 <sup>(2)</sup>
	Test report		n°2015/069-2 (CRET)
	Slip resistance	EN 13893	Class DS (µ ≥ 0.30)
	Body voltage	EN 1815	E ≤ 2 kV, Antistatic
	Thermal conductivity	EN 12524 EN (ISO 10456)	0.25 W/(m.K), suitable for heating floors

<sup>(1)</sup> The articles (products) do not contain substances of the candidate list published by ECHA (SVHC substances of very high concern) to be declared in accordance with REACH.

<sup>(2)</sup> Valid on every substrate: wood, non combustible A2fl-s1 or A1fl.

\* TVOC : total volatile organic compounds