

Forbo Environmental Data Sheet

Product name	Tessera Teviot		
Product description	Tessera Teviot is one of the best selling low loop carpet tiles in the UK. Produced using 100% Aquafil polyamide, it has good soil hiding properties. Teviot complies with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets.		
Manufacturing location	Bamber Bridge, United Kingdom		
Site accreditation	ISO14001, ISO 9001, OHSAS 18001, SA8000°		



Our footprint - how it's made

Environmental data		Independent assessment and rating			
Total recycled content of product by weight	660	ISO 9001 Quality Management System			
	66%	ISO 14001 Environmental Management System	ESC SCOT Scott Statement S		
Post industrial recycled content	66%	OHSAS 18001 Occupational Health	bsi orsas		
Post consumer recycled content	0%	and Safety Management	Organization of President and Surface Management		
Recycled content of yarn	15%	To viot is made in an CA0000® cortified facility	SAI		
% renewable electricity used	100%	Teviot is made in an SA8000° certified facility			
Carbon footprint					
Estimated carbon footprint using data from Environmental product declaration according to ISO 14025	Raw materials and production 11.1 kg CO ₂ eq/m ²				
	Use (I year)	0.9 kg CO ₂ eq/m ²			

Your footsteps - how it performs

Health and well being

Impact sound reduction	23dB
AgBB/DiBt	Pass
CHPS 01350	Tessera products comply to 01350 Indoor Air Quality Standard
Air quality	

Installation

Recommended adhesives

Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a **solvent free** release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 540 Eurosafe Special, again a **solvent free** adhesive, is recommended.

Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent nonrelease bond.

Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 542 Eurofix tack plus should be used. If a permanent bond is required, please use Eurocol 640 Eurostar special.



creating better environments

Maintenance									
						n and is necessary to			
	maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.								
End of life									
	Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle old carpet tiles in the UK.								
Contribution to Green E	Building Sch	emes							
BREEAM									
BREEAM ratings	Building Type Office A	Education A	Healthcare A+	Homes A	Retail (Durability) A	Retail (Fashion) A+			
Ska scheme (RICS)									
M12 soft floor covering criteria (Ska Offices Vs 1.2 2013)	Meets								
M12 soft floor covering criteria (Ska Retail Vs 1.0 2012)	Meets								
M12 soft floor covering criteria (Ska Higher Education Vs 1.0 2016)	Meets								
LEED (version 2.2)									
Potential direct or indirect contribution to following categories and credits:	Materials and Resources			Materials and resources - construction waste management through Back To The Floor, credit 2					
			Regional materials, credit 5						
	Indoor environmental Indoor environmental quality, low emitting materials – cred quality					erials – credit 4.3			
Forbo design principles (Reduce	, Recycle, Reuse,	, Renew)							
Reduce	Investment in an extruder has reduced our bitumen usage by 50%.								
Reuse	Yarn ends are rewound and used in the production of new Tessera Carpet tiles. Cutting waste and imperfect tiles can be reprocessed and turned into backing at our Bamber Bridge plant – creating a closed loop process. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin material.								
Recycle	Yarns, backing cloth, fillers and latex all contain recycled materials. All tufted Tessera carpet tiles made in the UK contain at least 50% recycled content by weight.								
Renew	All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable electricity.								
Detailed environmental product	declarations an	nd full Life Cyc	le Analysis						
Teviot has an EPD to ISO 14025 - Declaration Number 12CA64879.114.1	To download this EPD, please visit www.forbo-flooring.co.uk/downloads								