

Forbo Environmental Data Sheet

Product name	ame Flotex Tile/Plank	
Product description	Flotex Tile is comprised of a polyamide 6.6 pile above a glass fibre reinforced recycled backing. Flotex Tile complies with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets.	
Manufacturing locations	Ripley, United Kingdom Chateau Renault, France	
Range names	Flotex Colour, Flotex Linear, Flotex Plamks	



Our footprint - how it's made

Environmental data				
Total recycled content of product by weight	up to 49%			
Post industrial recycled content	up to 49%			
Post consumer recycled content	0%			
% renewable electricity used	100%			

Independent assessment and rating

ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management Flotex sheet is made in an SA8000° certified facility



British Allergy Foundation



Ü Mark



French act Grenelle: A+

Carbon footprint

Estimated carbon footprint using data from Environmental product declaration according to ISO 14025	Raw materials and production	11.10 kg CO ₂ eq/m ²
	Use (1 year)	0.316 kg CO ₂ eq/m ²

Your footsteps - how it performs

Health and well being

riculti and well being			
Air quality AgBB/DiBt	Approved by Allergy UK Pass		
CHPS 01350	Flotex products comply to 01350 Indoor Air Quality Standard		
-			
Impact sound reduction	19 dB		
Bacteriostatic properties	Flotex sheet meets the requirements of AATCC 174-1 and 174-2		
Installation			
Recommended adhesives	Forbo recommends the use of 540 Eurosafe special, a solvent free adhesive. Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission		

Eurocol 640 Eurostar special.

adhesive Eurocol 640 Eurostar special should be used. If a permanent bond is required, please use



creating better environments

Maintenance				
	Flotex releases twice as many allergens on vacuuming as standard carpet. Flotex can be cleaned using standard cleaning materials without the need for harmful chemicals. Flotex is waterproof and can be steam or mechanically cleaned.			
End of life				
	Can be downcycled or sent t	o waste to energy		
Contribution to Green	Building Schemes			
BREEAM 2018				
Value of Credit	Compliant through EPD declaration number 4788294459.111.1			
Ska scheme (RICS)				
M12 soft floor covering criteria	(Ska Offices Vs 1.2 2013) Meets	(Ska Retail Vs 1.0 2012) Meets	(Ska Higher Education Vs 1.0 2016 Meets	
LEED (version 4)				
Potential direct or indirect contribution to following categories and credits:	Materials and resources	Building product disclosure and optimisation - EPD up to 2 points		
		Building product disclosure and optimisation - sourcing of raw materials - up to 1 point		
		Construction and demolition	n waste management up to 2 points	
	Indoor environmental quality	Low emitting materials up to	o 3 points	
		Acoustic performance up to 1 point		
Forbo design principles (Redu	ce, Recycle, Reuse, Renew)			
Reduce	All Flotex samples can be returned allowing them to be reused or recycled, reducing the need for virgin material			
Reuse	Producing a Flotex tile backing made from re-used and pre consumer waste obtained via our Back to the Floor scheme. Waste comes from other production sites within Forbo, but also from outside Forbo to optimise waste streams from external textile flooring companies			
Recycle	Installation waste can be recycled in the our plant in Ripley, Derbyshire, back into Flotex products			
Renew	Flotex tiles are produced using 100% renewable electricity			