

eurocol

Europrime Base

the strong connection

882

AQUA BASE COAT

PRODUCT DESCRIPTION

Ready-to-use primer for all permitted, standard wooden floors. Use prior to Eurocol lacquers to ensure perfect surface appearance of all types of parquets. Reduces possible finishing lacquer caused side bonding of the parquet elements. Emission-tested product according to Dibt principles. For indoor use only. Very low VOC emission.

EMICODE EC 1 Plus, GISCODE W 2+, NMP-free



Made in Germany

PRODUCT FEATURES

Ready-to use one-component primer with very good filling properties for application for areas of extreme high foot traffic. No odor.

Reduces edge-bonding between the sides of the parquet stripes. Easy applicable with a double sided spatula or an aqua roller.

TECHNICAL DATA

Base	PU acrylate
Colour	Milky
Density	approx. 1,01 g/cm ³
Consistency	Low viscosity
Cleaning agent	water
Processing conditions	not below 15 °C on the subfloor, minimum 18 °C material- and room temperature 35-75% relative air moisture, recommended <65%
Mode of application	Double sided spatula/micro fibre roller
Consumption	Roller: approx. 100 g/m ² /coat Spatual: approx. 30 g/m ² /coat
Drying time	Spatula: approx 20 min. per coat Roller: approx.. 1 h per coat
Permitted shelf-life	within approx. 12 months, opened packaging to be tightly closed and to be consumed as soon as possible
Storage condition	packaging to be tightly closed at a dry place, temperature: 5 - 30 °C,
Frost sensitivity	yes

Code acc. to GHS	no	
Environment/Work safety	GISCODE:	W3+ (NMP free)
	DGNB:	VOC 6,90 %, Qualitätsstufe:/quality level: 3
	LEED:	VOC 0,07 g/l
	Contains 1,2-Benzisothiazol-3(2H)-on. Can cause allergic reactions.	

SUBFLOOR

The subfloor needs to be clean, free of wax, oil, silicon and other residues which negatively influence the bonding power. After rough grinding, joints width are to be closed with wood-putty solution, mixed sanding dust.

INSTRUCTIONS FOR USE

Shake well before use. Apply 2 coats of forbo 882 Europrime Base equally with Eurocol Double-sided spatula or alternatively 1 coat with Eurocol micro fibre roller (75082) on the readily sanded and cleaned parquet floor.
Beech and other sensitive types of wood are never allowed to be treated with spatula but Eurocol micro fibre roller (1 coat).
Afterwards the floor is ready for applying a eurocol water-based lacquer.
Dyed or untreated cork floors. Do not apply to much lacquer in order to prevent colour changes due to the release of Tannin. Unsure constant air circulation while drying.
Avoid direct sun and excessive air draught.

NOTES

Please pay attention to the safety data sheets and technical data sheets used products and the recommendations and instructions of the parquet manufacturer.
In case of application on exotic wood, smoked oak or old parquet please apply Europrimer block plus or 865 Europrime Block.
The room climate during processing should be adjusted to the room climate later on in order to avoid shrinkage or extension of the parquet.
Check the moisture content of the wood and the wood climate!
Make sure when applying strong firing lacquers that a good priming is made with no overlapping and equal application.

PACKAGING

5 l nonreturnable package (96 per pallet)
10 l non-returnable package (60 per pallet)

SPECIAL NOTE

Any application method/conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/conditions liability by manufacturer cannot be guaranteed.
This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.
The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.
As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to follow by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!
Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.
The products delivered by the manufacturer are for professional use only. Keep away from children.
The manufacturer's terms and conditions are binding.

882

Europrime Base

Last updated 2015-06-17
Supersedes issue as of 2014-01-03

Version Nr.: 10
75102_882-11

SPACE FOR YOUR REMARKS
