

### **Forbo Environmental Data Sheet**

Product name	Allura 0.7		
Product description	Forbo's Allura luxury vinyl tiles are a heterogeneous resilient floor covering complying with all requirements of EN-ISO 10582		
Manufacturing location	Coevorden, Netherlands		
Site accreditation	ISO14001, ISO 9001, OHSAS 18001, SA8000°		



# Our footprint - how it's made

Environmental data		Independent assessment and rating		
Total recycled content of product by weight	10%	ISO 9001 Quality Management System		
		ISO 14001 Environmental Management System		
Post industrial recycled content	10%	OHSAS 18001 Occupational Health and Safety Management		
Post consumer recycled content	0%	Allura is manufactured in a SA8000®		
% renewable electricity used	100%	certified facility		
Carbon footprint				
Estimated carbon footprint using data from Environmental product declaration according to ISO 14025	Raw materials and production	9.79 kg CO <sub>2</sub> eq/m <sup>2</sup>		
	Use (1 year)	0.32 kg CO <sub>2</sub> eq/m <sup>2</sup>		

## Your footsteps – how it performs

#### Health and well being

CHPS 01350	Allura products comply to 01350 indoor air quality standard		
Impact sound reduction	6dB		
Phthalate	Phthalate free		
Installation			
Recommended adhesives	The installation of Allura should be carried out in accordance with BS8023 code of practice for the installation of resilient floor coverings. As with all resilient floor coverings, bases should be clean, smooth and permanetly dry. For standard installations Eurocol 540 Eurosafe Special is recommended. Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 640 Eurostar special should be used.		



#### creating better environments

	Forbo's Allura collection is easy to clean and maintain thanks to its smooth and highly durable PUR coated surface							
End of life								
	Can be recycled or used in waste to energy application							
Contribution to Green	Building Schemes							
BREEAM	•							
BREEAM ratings (generic)	<b>Building Type</b> Office Education A A+	Healthcare A+	Multi- Residential A	Retail (Durability) A+	Retail (Fashion) A+			
Ska scheme (RICS)								
M12 soft floor covering criteria (Ska Offices 1.2 2013)	Meets							
M12 soft floor covering criteria (Ska Retail 1.0 2012)	Meets							
M12 soft floor covering criteria (Ska Higher Education 1.0 2016)	Meets							
LEED (version v4)								
Potential direct or indirect contribution to following categories and credits:	Materials and Resources		Materials and resources - construction waste management through Back To The Floor					
		Sourcing of raw materials MRC3						
	Indoor environmental Low emitting materials EQC2 quality							
Forbo design principles (Reduc	e, Recycle, Reuse, Renew)							
Reduce	Environmental impact on printed layer is reduced through use of water based inks							
Reuse	Optimisation of scrap reuse process enables more waste to be reprocessed							
Recycle	Calendered layer contains a minimum of 20% of recycled production waste. Installation waste can be recycled at our plant in Ripley, Derbyshire, back into other Forbo products via our Back to the Floor scheme. Allura is 100% recyclable.							
Renew	100% of the electricity used is from a renewable source							
Detailed environmental produ	ct declarations and full Life Cy	cle Analysis						
EPD declaration number 12CA64879.109.1	visit www.forbo-flooring.co.uk/downloads for more information							