

Forbo Flooring Systems  
8 Maplewood Drive  
Humboldt Industrial Park  
Hazle township, PA 18202  
telephone: 1-800-842-7839  
fax: 570-450-0258  
www.forboflooringNA.com

## mct essentials | elementals

### **MCT EZvation Pricing Guarantee MCT EZon Pricing Guarantee**

#### **Guarantee includes:**

- MCT with Topshield pro carries a ten (10) year no maintenance warranty (1)
- Use of Forbo EZon 100 adhesive
  - Fastest, strongest, long-lasting, immediate-on flooring solution
  - No moisture testing, eliminating costs and conflict
  - No vapor retarder required
  - (15) years adhesive warranty (2)
  - Simplified (EZ) installation
- Flat lay
- Open areas, No patterns
- Straight lay (parallel walls)
- Forbo EZon 100 Adhesive
- 5,000 ft<sup>2</sup> minimum
- Continental 48 States

(1) MCT with Topshield pro under normal use shall not require the application of floor finish for a period of ten (10) years from the date of original installation when maintained in accordance with the version of Forbo's published floor care guidelines in effect on the date of original purchase

(2) For applications where Forbo EZ-ON 100™ are used and all substrate and testing requirements as listed on the latest version of Forbo's published Technical Data Sheet in effect on the date of original purchase are documented and strictly followed.

#### **What is assumed:**

- Substrate provided must meet industry acceptable standards for the preparation of resilient flooring installation per ASTM concrete & ASTM wood prep
- All exceptions to the above are the sole responsibility of the flooring contractor to document and are not included in cost calculations of the pricing guarantee
- Not inclusive of any GC or construction Manager mark up

#### **Recourse:**

- Forbo Flooring Systems will facilitate the installation of MCT using partnered installer as defined by Forbo to meet the pricing guarantee of \$3.90 - \$5.45 ft<sup>2</sup> (3) US as outlined above.
  - (3) Lower pricing may be available using standard Marmoleum adhesives Forbo T940 or Forbo Sustain 1195. These adhesives require testing per the latest version of ASTM F1869 or ASTM F2170 and require confirmation of vapor retarder in place for on or below grade installations.

### **COMMERCIAL APPLICATIONS ONLY**