

### E 3/1 U2/U2 BT/SMT-HW- HACCP-PS white



Sketch of cross-section (not actual size)

#### Applications

- Dough conveying
- Meat, poultry and seafood processing
- Processing of dairy products
- Fruit and vegetable processing

#### Properties/Advantages

- Both sides coated
- Special urethane coating with semi-matt top face pattern
- Broken twill (BT) pattern coated underside
- Hot water resistant (HW) up to 120 °C
- Frayfree (FF) and pre-shrunk (PS) tension member
- High laterally stiffness
- HACCP design
- Complies only to MHLW# 370 regulation

#### Basic technical data

Top face	polyurethane
Underside	polyurethane
Article no.	904473
d <sub>min</sub> (mm)	20
Total thickness (mm)	1.4
k <sub>1</sub> relaxed (N/mm width)	3
Weight (kg/m <sup>2</sup> )	1.6
Permitted operating temperature	-30 to +100 °C (120 °C)

Product Quick Info TR-904473-2 - 02/17  
FMS - Reproduction of text or parts thereof only  
with our approval.  
Modifications reserved.

Forbo Siegling GmbH  
Lilienthalstraße 6/8, D-30179 Hannover  
Telefon +49 511 67 04 0, Fax +49 511 67 04 305  
www.forbo-siegling.com, siegling@forbo.com