




















Technical specifications

Allura Click meets the requirements of EN-ISO 10582

| | | | |
|---|---|--------------|--|
|  | Total thickness | EN-ISO 24346 | 5.0 mm |
|  | Wearlayer thickness | EN-ISO 24340 | 0.55 mm |
|  | Collection size | | 38 |
|  | Domestic use | EN-ISO 10874 | 23 |
|  | Commercial use | EN-ISO 10874 | 33 |
|  | Tile size | EN-ISO 24342 | 60 x 31.7 cm |
| | Plank size | EN-ISO 24342 | 121.2 x 18.7 cm / 150.5 x 23.7 cm |
| | Packaging per carton tiles | | 1.90 m ² (10 pcs) |
| | Packaging per carton planks | | 1.81 m ² (8 pcs) / 2.14 m ² (6 pcs) |
| | Squareness and straightness | EN-ISO 24342 | < 400 mm < 0.25 mm > 400 mm < 0.35 mm |
|  | Total weight | ISO 23997 | 8300 gr/m ² |
| | Wearlayer binder content | EN-ISO 10582 | Type 1 |
|  | Slip resistance | DIN 51130 | R10 |
|  | Acoustical impact noise reduction | EN ISO 717-2 | 7 dB / 15 dB in combination with Forbo underlay |
|  | Castor chair continuous use | ISO 4918 | Good, with and without Forbo underlay |
|  | Residual indentation <i>Typical value</i> | ISO 24343-1 | ≤ 0.10 mm ~ 0.05 mm |
|  | Light fastness | ISO 105-B02 | ≥ 6 |
| | VOC emissions | ISO 16000-9 | ≤ 160 µg/m ³ |
|  | Resistance to chemicals | EN-ISO 26987 | Very good |
|  | Dimension stability (after exp. to heat) | EN-ISO 23999 | ≤ 0.05% |
| | | | EN 14041  0200132_DoP_701 |
| | Allura Click meets the requirements of EN 14041 | | |
|  | Reaction to fire | EN 13501 | B _f -s1 with and without Forbo underlay |
|  | Slip resistance | EN 13893 | DS - µ > 0.30 |
|  | Thermal conductivity | EN 12524 | 0.25 W/mK |
|  | Body voltage | EN 1815 | < 2 kV |

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPDs) which can be found on all of our websites.

