FLOORING SYSTEM

Caring for Forbo Coral®

Care Recommendations For

- Forbo Coral[®] Brush
- Forbo Coral® Brush Tile
- Forbo Coral® Duo

Floor Care Chemicals & Equipment

Forbo Coral® typically only requires water for cleaning, but in certain circumstances, a hydrogen peroxide cleaner or a degreaser may be used as a pre-spray. Cleaner should only be applied as a pre-spray, never applied with a machine. All cleaners should be diluted per the label directions and tested on a scrap piece of material to ensure compatibility with the flooring for colorfastness and to avoid damage.

IMPORTANT! Damage caused to Forbo floors from the improper use of floor care chemicals and equipment is NOT covered under Forbo's warranty

Always refer to and follow the recommendations in the **General Floor Care Guidelines** prior to starting any cleaning processes.

NOTE: Forbo Coral® requires regular care to keep it clean and prevent the accumulation of dirt and soil. Proper cleaning, such as daily vacuuming and routine self-contained water extraction can reduce contamination to virtually non-existent levels. Identify sources of soiling and react to spills immediately before they dry.

Initial / Routine Cleaning

Newly installed floors must be protected from construction soil, traffic and damage. Initial cleaning procedures should be performed on all new installations exposed to normal construction soil and traffic. It is recommended to wait a minimum of five days before conducting any wet cleaning procedures in order to allow the adhesive to dry and cure properly. This timeframe can vary, depending on the substrate, site conditions and/or the adhesive used. Routine cleaning is typically performed a minimum of once a day, depending on the application, type of traffic and hours of operation. Contact Forbo's Product Support & Education Services for additional information.



 Remove all surface debris by vacuuming using a dual motor upright vacuum with a rotating brush. The brush should be approximately 1/8" below the vacuum cleaner casing to ensure proper agitation. Make several passes with the vacuum cleaner to ensure that all loose dirt is removed. Vacuum action should be fast forward and slow backward.







2. Spot clean as necessary using the "Scrape, Scrub & Rinse" cleaning method.

Scrape, Scrub & Rinse Cleaning Method



- SCRAPE up spills and Spots using a spatula or blunt edge scraper and wipe excess soil onto a cloth.
- 2. Apply a liberal amount of clean water to the spot.



SCRUB the area using a dull putty knife or 5-in-1 tool. Don't be afraid to use
aggressive scrubbing to remove set-in spills. A stiff nylon brush can be used
to remove scuff marks or other set in spills.



Recover the water and the remains of the spill into a paper towel or cloth.
 Keep scraping until the spill is completely removed. A spotter machine may be used to perform rinsing and recovery of the spill.



Caring for Forbo Coral®





5. If the spill or spot is not completely removed, apply a general-purpose spot cleaner to a white cotton cloth and rub it into the spot. If using a cleaning agent, be certain not to leave any residue on Forbo Coral®. Any chemicals applied to the flooring must be removed. The most common problem when caring for Forbo Coral® is the overuse of cleaning chemicals. The buildup of chemicals and cleaners will deluster the Forbo Coral® fibers and leave a dull appearance. Chemical buildup also attracts dirt faster and speeds soiling. Be sure to dilute chemicals in strict accordance with the manufacturer's recommendations. Repeat Step 4.



RINSE the area thoroughly with clean water to ensure that any cleaning solution is completely removed.



Allow the floor to dry completely before allowing traffic. Use a snail fan if necessary.

Interim Cleaning

Cleaning performed as needed, depending on the application, type of traffic and hours of operation. The following processes should be followed when the routine cleaning is not removing the soil from the floor.



 Remove all surface debris by vacuuming using a dual motor upright vacuum with a rotating brush. The brush should be approximately 1/8" below the vacuum cleaner casing to ensure proper agitation. Make several passes with the vacuum cleaner to ensure that all loose dirt is removed. Vacuum action should be fast forward and slow backward.







2. Spot clean as necessary using the "Scrape, Scrub & Rinse" cleaning method.



- Use a self-contained extraction machine, preferably with counter-rotating brushes, to extract the floor using clean water only. Set the brushes to ensure maximum agitation and contact with the fibers.
- 4. Follow each wet pass with a minimum of two dry passes.



Allow the floor to dry completely before allowing traffic. Use a snail fan if necessary.



Caring for Forbo Coral®

Restoration Cleaning

Restoration cleaning is important to maintain Forbo Coral*. Periodically following the steps below will aid in the overall appearance of the floor. A good indication that restoration cleaning is required is when interim cleaning is not removing the soil from the floor.



 Remove all surface debris by vacuuming using a dual motor upright vacuum with a rotating brush. The brush should be approximately 1/8" below the vacuum cleaner casing to ensure proper agitation. Make several passes with the vacuum cleaner to ensure that all loose dirt is removed. Vacuum action should be fast forward and slow backward.







2. Spot clean as necessary using the "Scrape, Scrub & Rinse" cleaning method.



Make a cleaning solution by diluting a neutral pH cleaner in strict
accordance with the manufacturer's recommendations. The pH of the
cleaning solution must be between 6.0 – 8.0 pH.
 NOTE: If there are hard water or mineral deposits present, dilute a cleaning solution.

NOTE: If there are hard water or mineral deposits present, dilute a cleaning solution of hydrogen peroxide cleaner in strict accordance with the manufacturer's recommendations. The pH of the cleaning solution must be between 4.0-7.0~pH.





4. Apply the cleaning solution to the floor with a pump sprayer. Allow the solution to dwell on the floor for 5 – 10 minutes. Additional dwell time may be necessary for heavily soiled floors.

IMPORTANT!! THE ENTIRE FLOOR MUST BE COMPLETELY WET BEFORE MOVING TO THE NEXT STEP.

If the floor is not wet enough the friction between the nylon fibers of Flotex® and the brush can cause the machine to become uncontrollable.



5. Scrub the floor with a 175 RPM floor machine using a flagged bristled brush such as a Malish nylon carpet shampoo brush #812915 or equivalent.

NOTE: These types of brushes typically need to be broken in prior to use. Contact the brush manufacturer for recommendations.



- Use a self-contained portable extraction machine, preferably with counterrotating brushes to extract the floor using clean water only. Set the brushes to ensure maximum agitation and contact with the fibers.
- 7. Follow each wet pass with a minimum of two dry passes.



8. Allow the floor to dry completely before allowing traffic. Use a snail fan if necessary.

NOTE: Weather, traffic and geographical location will influence the required frequency of this procedure. For example, in areas where there are large amounts of snow and chemicals used in the winter months it will likely be necessary to perform this procedure more frequently. In dry climates, or where there is less dirt traffic, it may not be necessary to perform this procedure as frequently.

For additional information, visit www.forboflooringNA.com or contact Forbo's Product Support & Education Services at 1-800-842-7839.