



Forbo Flooring
Products 2017






# CONTENT

Forbo Flooring Systems	8
Our Milestones	10
Flooring Systems & The Environment	12
Forbo Found Everywhere	14
Committed To The Health Of One	16
The Floor Coverings Of Forbo Flooring Systems	18
	20
Take A Look Into The Facinating World Of Colour	
And Design	22
Sustainable & Durable	24
Topshield2, For Floor Performance In The Real World	25
LCA & Environmental Product Declarations	27
Content Linoleum	29
Marmoleum Marbled Real	30
Marmoleum Marbled Vivace	32
Marmoleum Marbled Fresco	33
Marmoleum Solid Cocoa	36
Marmoleum Solid Walton Uni	37
Marmoleum Solid Piano	38
Marmoleum Solid Concrete	40
Marmoleum Solid Slate	42
Marmoleum Patterned Graphic	44
Marmoleum Patterned Piano	45
Marmoleum Linear Striato Textura	46
Marmoleum Linear Striato Original	48
Marmalaum Linear Striata Colour	40





Marmoleum Acoustic	51
Marmoleum Ohmex	52
Technical Specifications Marmoleum	54
Marmoleum Modular	56
Marmoleum Modular Floorplans	58
Marmoleum Modular Lines	60
Marmoleum Modular Shade	62
Marmoleum Modular Colour	64
Marmoleum Modular Marble	66
Marmoleum Modular Textura	68
Technical specifications Marmoleum Modular	70
Marmoleum Click	72
Technical Specifications Marmoleum Click	76
Marmoleum Sport	78
Marmoleum Sport Move	81
Technical Specifications Marmoleum Sport	82
Linoleum for walls and furniture	84
Furniture Linoleum	86
Bulletin Board	88
Technical Specifications Furniture Linoleum	90
Technical Specifications Bulletin Board	91
PROJECT VINYL	92
Content Project Vinyl	95
Allura	96
Allura Flex	108
Allura Flex 0.55 Stone	114
Allura Flex 0.55 Wood	116
Allura Flex Decibel	118
Allura Click	120

Allura Click Decibel	126	Sarlon	180
Allura Safety	128	Sarlon Canyon	182
Allura Colour	130	Sarlon Wood	184
echnical Specifications Allura	132	Sarlon Cement	186
phera	134	Sarlon Typography	187
phera Element	136	Sarlon Abstract Wood	188
phera Energetic	140	Technical Specifications Sarlon	189
echnical Specifications Sphera	143	Colorex	190
ternal	144	Colorex SD/ED	194
ternal Wood	146	Colorex Plus	196
ternal Material	148	Technical Specifications Colorex	197
ternal Colour	150		
ternal Decibel	152	FLOTEX	198
echnical Specifications Eternal	153	Content Flotex	205
ternal Digitally Printed Vinyl	154	Flotex Colour	206
ternal Magnified Nature	156	Flotex Metro	208
urestep	158	Flotex Metro Neon	210
Surestep Original	162	Flotex Calgary	212
Surestep Star	164	Flotex Penang	214
Surestep Mineral	165	Flotex Linear	216
Surestep Texture	166	Flotex Complexity	218
Surestep Wood	168	Flotex Integrity2	219
Surestep Stone	169	Flotex Cirrus	220
Gurestep Aqua	170	Flotex Stratus	221
Surestep Laguna	171	Flotex Artline	222
Surestep R11	172	Flotex Vision	224
Surestep R12	173	Flotex Digital Library	226
Solidstep	174	Flotex Sottsass	228
echnical Specifications Safestep	175	Flotex Bacteria	230
Sarlon Acoustic Vinyl	176	Flotex Wool	231
Sarlon Dégrade	178	Flotex Terrazzo	232



4 Content 5

332

335 336

338

340

342

344

346

348

350

352 354

356

358 359

361

362

363

366

lotex Kasuri	233
echnical Specifications Flotex	234
lotex Seagrass	237
lotex Triad	238
lotex Box Cross	240
lotex Concrete	241
lotex Wood	242
lotex Lava	243
lotex Van Gogh	244
lotex Tibor Ziggurat	245
lotex Tibor Mosaic	246
lotex Tibor Quartz	247
lotex Tibor Tessello	248
lotex Tibor Onyx	249
lotex Tibor Tweedy	250
lotex Tibor Arbor	251
lotex Tibor Tweedy	252
echnical Specifications Flotex Tibor	253
CARPET TILES & NEEDLEFLET	254
Content Carpet tiles & Needleflet	259
essera	260
essera Atrium	262

Tessera Arran

Tessera Basis

Tessera Barcode

Tessera Format

Tessera Create Space 1
Tessera Create Space 2



flotex®		

263

264

265

266

267

268

Tessera Helix	269	<b>ENTRANCE FLOORING SYSTEMS</b>
Tessera Inline	270	Content Entrance Flooring Systems
Tessera Rippleweave2	271	Coral
Tessera Weave	272	Coral Luxe
Tessera Diffusion	273	Coral Welcome
Tessera Layout & Outline	274	Coral Brush
Tessera Circulate	276	Coral Classic
Tessera Mix	277	Coral Duo
Tessera Alignment	278	Coral Grip
Tessera Contour	279	Coral Logo
Tessera Create Space 3	280	Technical Specifications Coral
Tessera Ethos	281	Nuway
Tessera Acrobat	282	Nuway Tuftiguard
Technical Specifications Tessera	285	Nuway Tuftiguard HD
Tessera Planks	288	Nuway Grid
Technical Specifications Tessera Planks	289	Nuway Gable
Westbond	290	Nuway Connect
Westbond Naturals	292	Technical Specifications Nuway
Westbond Reds	293	Our Footprint
Westbond Greens	294	
Westbond Blues	295	
Westbond Flex	296	
Westbond Natural	298	
Needlefelt	300	
Showtime Nuance	302	
Showtime Experience Wonderlab	303	
Wonderlab 01	304	
Wonderlab 02	305	
Wonderlab 03	306	
Wonderlah 04	307	

Showtime Experience Metropolis

Showtime Experience Ecosystems

Showtime Experience Héritage

Metropolis 01

Metropolis 02

Metropolis 03 Metropolis 04

Ecosystems 01

Ecosystems 02

Ecosystems 03

Ecosystems 04

Héritage 01

Héritage 02

Héritage 03

Héritage 04

Forte Graphic Reef

Forte Graphic Rice

Markant Graphic City


Technical Specifications Needlefelt and Showtime

Forte

Markant


Akzent

		3	
cor	al®		



6 Content 7

# Assendelft, **Netherlands**


























# FORBO FLOORING MARKELLEADER

Forbo Flooring Systems is a global market player in Linoleum, project vinyl, carpet tiles, Flotex flocked flooring, Coral entrance systems and vinyl floor coverings. In addition to floor coverings, Forbo develops, manufactures and markets a full range of professional service products. All Forbo products combine high levels of functionality and durability. Forbo Flooring Systems is committed to environmentally responsible production and to far-reaching customer service. Forbo Flooring is part of the Swiss Forbo Group and owns twenty manufacturing plants and branches in 32 countries worldwide.



# OUR MILESTONES

### 1928

Three linoleum manufacturers – German, Swedish and Swiss - form the Continentale Linoleum Union.

### 1950 - 1973

Diversification into related products such as carpets and vinyl flooring.

### 1973 and 1974

Adhesives activities hived off from linoleum business to be developed independently.

Continentale Linoleum Union is renamed Forbo to reflect the wider portfolio of activities.

# 1975 - 1994

Forbo evolves into a worldwide group operating on five continents: acquisition of a flooring business in Britain; diversification into wall-coverings and highpressure laminates.

Acquisition of Siegling, specializing in process and conveyor belt systems.

# 1996 - 1998

Divestment of wall-coverings and laminates activities.

# 2000 and 2001

New strategy focusing on four divisions: Linoleum, Vinyl, Belting and Adhesives. Divestment of industrial activities, including extruded profiles, decorative products and coated textiles. Carpet business spun off in management buyout. A series of minor acquisitions to strengthen Adhesives business.

# 2000 - 2003

Adhesives gains world stature by acquiring Swift, operating worldwide from the USA, Europe and Asia. Belting business expands in Britain. Linoleum and Vinyl merged to create Forbo Flooring. Now three strategic businesses: Flooring, Adhesives and Belting.

# 2004 - 2006

Strategic focus on three core divisions reaffirmed. Restructuring and measures to raise profitability. Acquisition of Chinese adhesives manufacturer specialized in hot-melt and water-based adhesives.

New branding and growth strategy; three core divisions – flooring, adhesives and belting – renamed Flooring Systems, Bonding Systems and Movement Systems, operating under the Forbo brand with an integrated business strategy.

### 2008

Acquisition of Bonar Floors, a major European flooring manufacturer in the contract flooring sector. With this, Flooring Systems strengthens its leading position as a systems provider of resilient flooring solutions in the commercial market.

Forbo acquires the lightweight PVC conveyor belting business from Fenner Dunlop (Charlotte) Inc. North America as a further step to strengthen its Movement Systems division.

### 2012

Focus on leading market positions through the sale of the industrial adhesives activity, including synthetic polymers, which belonged to the Bonding Systems division.


### 2013

Forbo Eurocol Krommenie (NL), Erfurt (DE) and Stroitec (RU) Building & Contuction adhesives join the Forbo Flooring Systems organization.

Forbo Flooring Systems launches full Marmoleum modular program in plank and tile formats.

# 2016

Introduction of in-house manufactured homogeneous vinyl using the latest insights and technology from a state of the art zero waste greenfield factory in Coevorden, The Netherlands.



# **FLOORING SYSTEMS**& THE ENVIRONMENT

### Life Cycle Assesment

Forbo uses Life Cycle Assessment (LCA) as the independent methodology of measuring our impact on the environment. Standardized within ISO 14040, Life Cycle Assessment (LCA) is defined as a compilation and evaluation of the inputs and outputs and the potential environmental impacts of a product system throughout its life cycle, a cradle-to-grave-approach. Measurement against the specific impact categories focuses on efforts for reduction; it is the basis for Forbo's green development and our overall performance. The LCA is calculated for 1m2 installed floor covering from cradle to installation. We base our LCA calculation on the weighted mass of all the products we produce and also include the energy consumption of all our offices and warehouse worldwide.

# **Environmental Product Declarations (EPD's)**

Forbo Flooring Systems has published Environmental Product Declarations for all of its indivudual floor covering products. An EPD presents quantified environmental data for a product, based on information from a life cycle assessment (LCA). An EPD is a report verified by the European Resilient Flooring Manufacturers Institute (ERFMI) that summarises and explains the data generated from an LCA.

# Green design principles

We conscientiously apply green design principles to all our products and processes. In order to live up to our promise to reduce our environmental footprint by 25% in 2015, all our collections are engineered and designed to commit to this goal.

A project where we achieved a reduction of 23.1% and reduction of 23.1%. At the same time Forbo Flooring Systems' contribution to the global warming potential expressed in CO2 equivalents is reduced by 37,7%. The project continues globally on annually set targets.

### Reduce, Renewable, Reuse, Recycle

The key to our success in implementing our environmental policies lies in the application of our "4 R's": Reduce, Renewable, Reuse, Recycle.

A number of initiatives have been rolled out across the business, and it is our commitment to continuing and improving ourselves to achieve our environmental aims.

**Reduce:** energy, landfill, raw material consumption **Renewable:** electricity, natural & sustainable raw materials

**Reuse:** production waste across all sites **Recycle:** product and sampling take back schemes

# Forbo way to win

Forbo's internal awareness programme. In 2010 we rolled out our internal awareness programme - The Forbo Way to Win. We used this to introduce our sustainability policy and strengthen our employee's engagement by providing a platform for them to contribute to our efforts in reducing energy consumption, the use of raw materials and waste. We also asked them to look as ways of increasing recycling.

# Realized examples of Forbo Way To Win

The programme generated over 1700 ideas, resulting in 600 possible projects, some of which have already been successfully implemented.

- Rewinding yarn ends and reuse in producing Tessera carpet tiles.
- Reduce the need of water to produce steam the Flotex production.
- Use different pre-cut lengths of paper for the backing machine.
- Elimination of the cardboard cores in the jumbo rolls of Flotex.

# **FORBO** FOUND EVERYWHERE

Flooring Systems' floor coverings are to be found in a wide variety of buildings. In hospitals, schools, retail, offices, industry, in every space is another floor solution. For all these areas we have a suitable floor that meets all the requirements and conditions to create the right atmosphere, ambience and comfort. You can find us in ...



When it comes to refurbishing commercial properties, we know you need flooring. You probably are looking for a flooring design that will set your property apart or need a solution to cover the whole of your building. Our portfolio will make it easy to select the ideal floor covering to meet your needs.

# Healthcare

With millions of square metres of our floor coverings installed Creating the perfect environment in which your customers in healthcare establishments, we are is at the forefront when it comes to understanding the needs and concerns of the health.



From nurseries to universities, educational establishments demand attractive, hardwearing, low maintenance safe and sustainable flooring solutions. Durability and hygiene are important in areas used by children and young adults.

# Retail, leisure & hospitality

An experience in any retail, leisure & hospitality environment is about more than just the products you can buy or experience. feel relaxed and comfortable is key. From the first impression as they enter, to the ease of navigation, our portfolio of products makes it easy to select the perfect flooring to set the tone in your store, hotel or leisure environment.

### Industry

Forbo stands for guaranteed performance in all kinds of industrial environments, from electronic and pharmaceutical production areas to laboratories. We offer a complete range of products with antistatic, acoustic, conductive, water-resistant, slip-resistant, bacteriostatic and bactericidal properties.

Forbo offers a variety of floor covering solutions for the transport industry. All are fully certified and combine durability, excellent fire resistant properties and a wide variety of designs and colours.








# **Application possibilities for Forbo Flooring**

Application areas	Linoleum	Projectvinyl incl. LVT	Carpe	t tiles and Ne	eedlefelt	Flotex	Entrance flooring
			Tessera	Westbond	Needlefelt		
Hospital	•••	•••	•		•	•	•••
Private clinic	•••	•••	•		•	•	•••
Rehabilitation center	•••	•••	•		••	••	•••
Medical practice	•••	•••	•		•	••	•••
Elderly care	•••	•••	••	••	••	•••	•••
Education	•••	••	•		••	•••	•••
Day care	•••	••			••	•••	•••
Sports	•••						•••
Fitness center	••		•		•••	•••	•••
Offices	••	•••	•••	•••	•••	•••	•••
Bank	••	•••	•••	•••	•••	•••	•••
Hotel	••	•••	•••	•••	••	•••	•••
Restaurant	•••	•••	•		•	••	•••
Leisure & Hospitality	•••	•••	•••	••	•••	•••	•••
Retail	•••	•••	•	•	•••	•••	•••
Industry	•	•••					•••
Transport	•••	•••			•	••	•••

••• Recommended

• • Very suitable

• Suitable



# FORBO FLOORING SYSTEMS: COMMITED TO THE HEALTH OF ONE

In today's world more than half of the global population is living in urbanized areas. Here we consume more than two thirds of the world's energy and use more than 80% of all its resources. Cities create over 70% of all CO<sup>2</sup> emissions and create billions of tons of waste. As Forbo, we are part of the urbanized society and as we are spending more than 80 to 90% of our time indoors we feel it is our responsibility to contribute to a better indoor environment and on top of that a better world to live in.

We do this by focusing on creating products that make a positive contribution to everyone health, safety and well-being. We run our plants on green energy, we manufacture products that are made from renewable natural resources and we act responsible in using the latest techniques and insight in constructing our products. Earth Day mean, standing with both your feet on the ground and creating the best solutions going forward. At Forbo Flooring systems we are used to do this, that is why Flooring Systems from Forbo are tomorrows responsible choice



# THE FLOOR COVERINGS OF FORBO FLOORING SYSTEMS

# LINOLEUM

A Natural Winner! Our linoleum products with the Forbo Marmoleum brand are natural floors associated with sustainability, durability, high quality and innovative design. Our Linoleum range includes solutions for virtually any type of application. Discover the versatile world of Linoleum with over 300 colours and more than 12 different structures to choose from, available in sheet and modular tile formats.

# PROJECT VINYL

Forbo's project vinyl floors can be used wherever people work, learn, play or go about their daily business. Design, slip resistancy, acoustic comfort, easy maintenance and durability are a key consideration of our project vinyl floors. Our project vinyl offer is available in both sheet and tiles and contains a wide range of wood designs, all over designs, stone and metals. Suitable for professional environments in healthcare, schools, office and retail.

# FLOTEX FLOCKED FLOORING

Flotex combines the practicality of a resilient flooring with the slip resistant and acoustic properties usually associated with textiles. Flotex is strong and hygienic, and, being completely waterproof, Flotex is also the only truly washable textilefloor covering.

# CARPET TILES AND NEEDLEFELT

Carpet tiles are renowned for their aesthetic styling and outstanding performance in the most demanding heavy traffic environments. We offer a wide portfolio of carpet tile ranges, providing an extensive choice of design, colour, installation options and price points. The robust, hard-wearing properties of Needlefelt make it ideal for installations that meet high traffic or in those areas where chairs with castors are likely to be in use, such as in offices, administrative premises and retail establishments.

# ENTRANCE FLOORING

Entrance flooring is fundamental to modern building design: Preventing walk in grit, dirt, dust and moist, minimizing maintenance costs, protecting a building's flooring and environment from pollutants and dirt.

Forbo Flooring Systems offers solutions for every conceivable application.

Our high quality Linoleum-, Project Vinyl, Carpet tiles, Needlefelt, Flotex and Entrance Flooring systems combine functionality and design.

We offer a full range solution for each application available.

18





# TAKE A LOOK INTO THE FASCINATING WORLD OF COLOUR AND DESIGN

Marmoleum was created to complement and enhance the architecture interiors of tomorrow's buildings and construction.

Healthy flooring solutions inspired by nature that live up to their performance promise. Create a better environment. Choose a Marmoleum floor. Creating a new perspective.

Forbo Marmoleum stands for versatility, sustainability and durability. It combines ecological and economic values that help bring modern and contemporary architecture to life.

Marmoleum is a natural floor, created from all natural ingredients. It is the most sustainable floor in the resilient flooring category.

All Marmoleum floors include Topshield2, a double UV cured finish delivering floor performance in the real world, that result in the lowest cost of ownership over its life time.

The stereotype of traditional beige and grey marbled linoleum designs is in the past. Our collections offer a wide choice in colour and design with rich, warm, refined and contemporary looks. Marmoleum has been transformed for the modern office and retail environments.

Marmoleum is available in both sheet and tile with matching colours and designs for easy mix and match. Some designs have an additional texture to bring the floor alive and follow the trend of tactility. With our modular marmoleum tiles and planks you can play to create your own floor design.

# SUSTAINABLE & DURABLE

With its 'all-natural ingredients', Marmoleum floor covering is almost like creating a floor covering with nutrients. As a matter of fact, the process of making Marmoleum is not unlike to that of preparing an oven-baked apple pie.

What makes Marmoleum special is that it is created entirely from raw materials obtained from their natural habitat right where they grow and renew, often in just 12 months time.

Jute and flax are annual crops that can be harvested just like wheat or corn. Extracting rosin is a continuous process, while wood flour, a waste material from the timber industry, is derived from European production forests. Limestone is available in abundance.

With Marmoleum, the simple, natural ingredient combination that creates the product. Marmoleum has no other additives to make it look better, no supplements to enhance its green profile and no artificial ingredients to improve stability or flexibility. Marmoleum is what it is and nothing else.

All this makes Marmoleum a natural floor that, after a long 30-plus year life cycle, can start all over again. Marmoleum can be scrapped, since it's biodegrade. Alternatively, burning Marmoleum delivers a higher caloric value and creates thermal energy that outweighs the energy used during production. This demonstrates the full life cycle circle from which nature benefits.





# TOPSHIELD2, FOR FLOOR PERFORMANCE IN THE REAL WORLD

The reality of day-to-day life for a floor covering is that it encounters both use and abuse without being able to balance its performance with prescribed cleaning and maintenance regimes. That means cleaning and maintenance is not always carried out exactly 'on time' or in the way prescribed by the manufacturer. The real world requires foolproof solutions.

Forbo Marmoleum is known for its track record in heavy-traffic environments such as schools, health care, offices and public buildings. In these applications, everyday use is characterised by high demands on hygiene, resistance to wear and the need for easy cleaning and maintenance. Dirt and sand carried into the building, hand disinfectant spills and the reality of the pressure of the economy on cleaning and maintenance regimes mean that floors today have to endure and withstand use and abuse to an even higher degree than before.

Topshield2 has been designed to ensure that Marmoleum meets the demands of everyday use, is even more resistant to dirt pick-up and less prone to wear with improved resistance to

scratches and stains to create a floor that gives you lasting performance over time.

Topshield2 provides you with a floor covering that:

- Is naturally bacteriostatic
- Resistant to hand disinfectants
- Has excellent stain resistance
- Is efficient, easy to clean and quick drying
- Soils less and picks up less dirt
- Has improved scratch resistance
- Is easy to maintain
- Can be renovated



24 Sustainable & Durable Topshield 2 25

# **AUTHENTIC & VERSATILE**

### The lowest cost of ownership

Marmoleum has a long and proud heritage. Whether looking for a traditional or more modern design, in sheet or tile, Marmoleum is used in a variety of application areas ranging from hospitals and schools to airports and designer shops. No matter the application, Marmoleum is versatile and has the proven lowest cost of ownership.

# SUSTAINABLE & DURABLE


### The most sustainable resilient floor

Created from natural, renewable raw materials, one could say that as long as the sun shines and the rain falls we can continue to make Marmoleum. There are no phalates, plasticisers and no mineral oil in Marmoleum. It has in fact, 97% natural raw materials, 72% rapidly renewable and a 43% recycled content. Combine this with long cleaning and maintenance intervals, and there is no doubt that Marmoleum is the most sustainable resilient floor, bar none.

# **DESIGN & COLOUR**

# Designed to let you create the ultimate flooring

The breadth of our colour choice is vast. No other flooring collection offers you so many choices. Our marbled range includes exciting brights & bolds, while our solid range offers a wide range of neutral colourways. Our linear range makes a strong design statement while the patterned range includes both monochromatic tones and more outspoken colours for playful combinations. The modular range open the door to play with planks and tiles while the texture added to some ranges brings the floor to live.





# LIFE CYCLE ASSESSMENT & ENVIRONMENTAL PRODUCT DECLARATIONS

We believe an open, honest and transparent approach to demonstrating a sustainable attitude is the only way to show the credits we attribute to our products and processes. Life Cycle Assessment (LCA) is a methodology we use to determine and measure the impact on the environment of any product during its creation, use and what remains when a product reaches its end of life by measuring a set number of impact categories.

The Environmental Product Declaration (EPD) is the outcome of the LCA, which is published in a 3rd party, verified report on a particular product. The EPD for Marmoleum verifies our claims and gives transparent insights into our test results and measurements.

# **Environmental Stewardship**

Marmoleum is manufactured in a state-of-the-art environment where the traditional manufacturing process has been automated in efficient production lines that are run entirely on green energy. At Forbo, we actively steer our processes toward continuous improvement, maximising the use of recycled content in our Marmoleum and working with green design principles whenever new designs or structures are developed.

# Marmoleum installation waste take- back schemes

With Forbo's 'Back To The Floor' scheme, installation offcuts and waste are collected and returned to our factory for reprocessing into new Marmoleum products. On a smaller scale, in our sampling, we take the same approach. This way, we can do our best to assure full-circle recycling even at points where our product reaches customers.

# Labels and Certification, recognition that goes a long way

Marmoleum is among the most certified and environmentally sound floor covering. We value all our labels, whether it's the internationally recognised Swan label, the Blue Angel certification, the North American Sequoia Seal or more specific labels like Nature Plus or the Austrian environmental label. Next to labels and certification, Marmoleum brings real benefits when measured against BRE or LEED certifications. Here, using a Marmoleum floor helps you in the overall rating of your building.














5 Linoleum
Life Cycle Assessment & Environmental Product Declarations 27



# LINOLEUM

# 29 72 marmoleum® sport

For use in sports facilities Forbo specially developed Marmoleum Sport.

# 29 78 **furniture linoleum**

A linoleum surfacing material which has a multitude of applications providing a functional finish to walls, furniture, door panels and cupboards.

# 29 83 bulletin board

A linoleum surfacing material that is ideal for use on notice- and pin-boards.

# 30 marmoleum® marbled

The marbled collection is presented in a vast array of colours, combining stronger and subtler marbled patterns together.

# 34 marmoleum® solid

The secret spirit of this collection lies in colour nuances and subtleness. With reference to classic, heritage colours, a conceptual range of (almost) uni colours has been created.

# 44 marmoleum® patterned

This collection is a dialogue between the easily understood statement of the black, grey and white Graphics and the subtle, two-tone speckled pattern of Piano.

# 46 marmoleum® linear

Linearity is a modern and outspoken trend which we refined and brought up to the colour spectrum of the 21st century. Some colour references are offered with a textured top layer to enhance the tactility of the floor.

# 51 marmoleum® acoustic

Marmoleum Acoustic is a twin-layered Marmoleum designed to achieve 14dB impact sound reduction.

# 52 marmoleum® ohmex

Marmoleum Ohmex is a special type of Marmoleum with enhanced electrical properties.

# 56 marmoleum® modular

Our Marmoleum Modular tile collection takes linoleum out of its traditional environment. With a range of planks and tiles in different formats you can play endlessly to create the ultimate floor design.

### 72 marmoleum® click

Marmoleum Click presents a collection of easy to install Marmoleum panels made of HDF board with 2.5 mm Marmoleum on top and a sound absorbing cork backing.

# 78 marmoleum® sport

For use in sports facilities Forbo specially developed Marmoleum Sport.

# 84 furniture linoleum

A linoleum surfacing material which has a multitude of applications providing a functional finish to walls, furniture, door panels and cupboards.

# 89 bulletin board

A linoleum surfacing material that is ideal for use on notice- and pin-boards.




Around the world in 90 colours – Marmoleum marbled collection. Each design reference is developed from a mix of three to eight pure base colours, blended together to create unique marbled structures that give Marmoleum its natural authenticity. The colour palette is an all ecompassing spectrum of classic rich warm tones, cool neutral colours complemented by daring and vivid colourways to create a collection that is our most versatile offer yet.



\* also available in 3.2 mm \*\* also available in 3.2 mm and 4.0 mm Matching multi coloured and solid coloured welding rods are available in all collection colours. All colours available in 2.0 and 2.5 mm, unless otherwise indicated.








3413 | green melody











3421 oyster mountain









3874 | walnut


3870 | red copper

3884 | frost


Marmoleum Marbled 33 32 Marmoleum Marbled

# MAROLEUM SOLID PRESENTING THE PURE NATURE OF LINOLEUM











36 Marmoleum Cocoa 37

# marmoleum<sup>®</sup> solid









38 Marmoleum Piano Marmoleum Piano 39













40 Marmoleum Concrete 41





Our Marmoleum Graphic collection consists of a series of high-contrast blacks and whites as well as a range of complementary greys which makes Graphic a truly architectonic collection. Graphic is available in 8 colours that can be coordinated with the collection or with other items from the Marmoleum range.







3640 | Pacific blue

3643 | submarine

3642 | periwinkle

3634 | meadow

5314 | scenario



striato textura





The all natural Marmoleum Striato collection presents an exciting range of linear designs in contemporary neutrals where the floor act as a modern backdrop of a natural environment. The naturalness of Striato textura and Striato original answers the trend for tactility and residential feeling. In contrast, the Striato colour items emphatisises the brightness and colour that can be created with Marmoleum. Being the lively floor strongly present or the modest base where other elements can become the hero. In all cases Marmoleum flooring defines the space.

Please note digital and printed representations may vary from the actual product. Please order a sample to see the full effect.



e5232 | rocky ice














e5216 | Pacific beaches e5235 | North Sea coast e5217 | withered prairie e5236 | fox cub



48 Marmoleum Linear Striato Original 49




Decibel is 3.5 mm sheet floor covering with a 2.5 mm Marmoleum Real laminated onto a 1 mm thick layer of polyolefin foam. Marmoleum Decibel is available in 25 colours that are taken from the Marmoleum Real collection. Alternative Marmoleum designs in a Decibel variety are available on request.



387435 | walnut










323835 | laguna

324635 | shrike


327235 | volcanic ash





371135 | cloudy sand

304835 | graphite





370535 | meteorite

312535 | golden sunset





370635 | beton







33055 | fresco blue



marmoleum<sup>®</sup> acoustic








33032

50 Marmoleum Decibel Marmoleum Acoustic 51



# Technical specifications: **marmoleum**

Marmoleum meets the requirements of EN ISO 24011 Marmoleum Acoustic meets the requirements of EN 687 Marmoleum Decibel meets the requirements of EN 686

			Marmoleum Real/Fresco	Real/Fresco/ Vivace	Marmoleum Real	Marmoleum Real	Marmoleum Decibel	Marmoleum Acoustic
Ŷ	Total thickness	EN-ISO 24346	2.0 mm	2.5 mm	3.2 mm	4.0 mm	3.5 mm	4.0 mm
	Domestic: heavy	EN-ISO 10874	Class 23	Class 23	Class 23	Class 23	Class 23	Class 23
	Commercial: general/heavy/ very heavy	EN-ISO 10874	Class 32	Class 34	Class 34	Class 34	Class 33	Class 33
	Light industrial: moderate/general/ heavy	EN-ISO 10874	Class 41	Class 43	Class 43	Class 43	Class 41	Class 41
ŷŷ	Roll width	EN-ISO 24341	2.00 m	2.00 m	2.00 m	2.00 m	2.00 m	2.00 m
$\exists$	Roll length	EN-ISO 24341	≤ 32 m	≤ 32 m	≤ 32 m	≤ 32 m	≤ 32 m	≤ 32 m
	Indentation residual	EN-ISO 24343-1	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.20 mm	≤ 0.30 mm	≤ 0.40 mm
7	Castor chair continuous use	EN 425	Suitable for office chairs	with castors.				
₹	Light fastness	EN-ISO 105-B02	Method 3: blue scale mi	nimum 6.				
52	Flexibility	EN-ISO 24344	ø 30 mm	ø 40 mm	ø 50 mm	ø 60 mm	ø 40 mm	ø 60 mm
${}^{\!$	Resistance to chemicals	EN-ISO 26987	Resistant to diluted acid	ls, oils, fats and to conven	itional solvents. Not resi	stant to prolonged expo	sure to alkalis.	
<b>.</b>	Bacteriostatic properties		Marmoleum has natura	bacteriostatic properties	s, which are confirmed b	y independent laborator	ries, even against the bac	cteria MRSA.
	Cigarette resistance	EN 1399	Marks left on linoleum a	s a result of stubbed-out	cigarettes can be remo	ved.		
88	Slip resistance	DIN 51130	R9	R9	R9	R9	R9	R9
٩	Acoustical impact noise reduction	EN ISO 717-2	≤ 4 dB	≤ 5 dB	≤ 6 dB	≤ 7 dB	17 dB	14 dB
	Electrical resistance Marmoleum Ohmex	EN 1081	-	$1-10^6$ <r1 <="" <math="">1-10^8 Ω static dissipative</r1>	-	-	-	-
LCA	Life Cycle Assessment		LCA is the foundation	for securing the lowest e	environmental impact.			
	Marmoleum meets the	e requirements of	EN 14041					EN 140
(N	Reaction to fire	EN 13501-1	Cfl-s1					
88	Slip resistance	EN 13893	DS: ≥ 0.30	<u> </u>	·		<u> </u>	<u> </u>
13	Body voltage	EN 1815	< 2 kV					
ш	Thermal conductivity	EN 12524	0.17 W/m·K					

# Technical specifications: **marmoleum**

Marmoleum meets the requirements of EN ISO 24011 Marmoleum Acoustic meets the requirements of EN 687 Marmoleum Decibel meets the requirements of EN 686

		Marmoleum Concrete	Marmoleum Walton	Marmoleum Striato	Marmoleum Graphic	Marmoleum Piano			
Total thickness	EN-ISO 24346	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm			
Domestic: heavy	EN-ISO 10874	Class 23	Class 23	Class 23	Class 23	Class 23			
Commercial: general/heavy/ very heavy	EN-ISO 10874	Class 34	Class 34	Class 34	Class 34	Class 34			
Light industrial: moderate/general/heavy	EN-ISO 10874	Class 43	Class 43	Class 43	Class 43	Class 43			
Roll width	EN-ISO 24341	2.00 m	2.00 m	2.00 m	2.00 m	2.00 m			
Roll length	EN-ISO 24341	≤ 32 m	≤ 32 m	≤ 32 m	≤ 32 m	≤ 32 m			
Indentation residual	EN-ISO 24343-1	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm			
Castor chair continuous use	EN 425	Suitable for office chairs with castors.							
Light fastness	EN-ISO 105-B02	105-B02 Method 3: blue scale minimum 6.							
Flexibility	EN-ISO 24344	ø 40 mm	ø 40 mm	ø 40 mm	ø 40 mm	ø 40 mm			
Resistance to chemicals	EN-ISO 26987	Resistant to diluted acids, oils, fats and to conventional solvents. Not resistant to prolonged exposure to alkalis.							
Bacteriostatic properties		Marmoleum has natural bacteriostatic properties, which are confirmed by independent laboratories, even against the bacteria MRSA.							
Cigarette resistance	istance EN 1399 Marks left on linoleum as a result of stubbed-out cigarettes can be removed.								
Slip resistance	DIN 51130	R9	R9	R9	R9	R9			
Acoustical impact noise reduction	EN ISO 717-2	≤ 5 dB	≤ 5 dB	≤ 5 dB	≤ 5 dB	≤ 5 dB			
Electrical resistance Marmoleum Ohmex	EN 1081	-	-	-	-	-			
Life Cycle Assessmen	t								
Marmoleum meets th	ne requirements of	EN 14041				EN			
Reaction to fire	EN 13501-1								
Slip resistance	EN 13893								
Body voltage	EN 1815								
Thermal conductivity	EN 12524								

Technical Specifications Marmoleum 55

# PLAY WITH MARMOLEUM MODULAR NATURAL DESIGN TILES

Our Marmoleum Modular tile collection takes linoleum out of its traditional environment. It offers a playful experiment with colour & design, like no other floor covering has done before.

**Lines:** a contemporary collection of abstract linear designs. The random calandered pattern of the striato planks create a unique natural design that reflects both modern and traditional wood and parquet floors.

**Shade:** a collection of a subtle concrete look in cool and warm grey tones as well as black and white.


The XL tile (75 x 50 cm) allows you to emphasize the material connection of slate and stone.

**Colour:** This is the heart of the collection and the one for which linoleum is most well-known: colour. Colours can be used as highlight or accent or combined in a unique mosaic floor to create an expressive environment.


**Marble:** classic and contemporary marbled colours that have been created to mix and match to give a special dimension to your floor plan.

**Textura:** in this range we have added two types of embossing to some of our linear patterns. This way we are adding tactility to the floor which gives a wonderful opportunity to play with shadows of floodlight.





These floorplans serve as inspiration for the wide variety of designs, moods and colour varieties that can be created with Marmoleum Modular. For a full overview and an opportunity to create your own floor plans please visit our floor planner on forbo-flooring.xx/xxxx





PL-11 | 100 x 25 cm

PL-22 | 100 x 25 cm, 100 x 15 cm







PL-31 | 50 x 50 cm

58 Marmoleum Modular floorplans 59




The collection is created in natural lighter-, yellow, middle-, brown and darker- grey colours. The plank dimension are  $100 \times 25$  cm and  $100 \times 15$  cm. In addition there is a  $50 \times 50$  cm tile and an interesting  $25 \times 50$  cm tile with a cross-grained line in the yellow tones creating a bamboo-like effect.



60 Marmoleum Modular Lines 61




4 cool concrete greys and 4 warm sand tones, complemented with classic 'Black and White' tiles. Available tile formats are: 75 x 50 cm, 50 x 25 cm, 50 x 50 cm, 25 x 25 cm. The subtle colour tones in the concrete ranges mixed together create subtle nuances that make your floor come to life when the light captures your floor design.





62 Marmoleum Modular Shade 63



PC-31 (t3238 - t3884 - t3887)

The colour collection contains four contemporary grey tones that are mixed with a single contrast colour, 4 matching pastel tints and a set of 12 fashionable bright and rich colours that make playful and exciting combinations and that liven up the environment.



64 Marmoleum Modular Colour 65



PM-24 (t3048 - t3139 - t3407)

A collection of 16 classic and contemporary marbled structures, presented in a colour range that has been created to mix and match to give a special dimension to your floor design.



66 Marmoleum Modular Marble 67



Adding tactility by using embossing bears a wonderful opportunity to play with the subtle shadows of floodlight. By working with tiles you not only can play with direction of light, but you can also make the embossing structure come to life. It enhances the comfortable and familiar feel to natural surroundings.


















te5225 | compressed time

te3573 | trace of nature


te5231 | Cliffs of Moher

68 Marmoleum Modular Textura

# Technical specifications: **marmoleum**® modular

# Marmoleum Modular meets the requirements of EN-ISO 24011

			Modular	Modular Textura
* ×	Total thickness	EN-ISO 24346	2.5 mm	2.5 mm
Ůμ̈́	Domestic: heavy	EN-ISO 10874	Class 23	Class 23
iii.	Commercial: very heavy	EN-ISO 10874	Class 34	Class 34
ΔÜ	Light Industrial: heavy	EN-ISO 10874	Class 43	Class 43
	Dimensions (length x width)	EN-ISO 24342	25 x 25 cm 25x50 cm 50 x 25 cm 50 x 50 cm 75 x 50 cm 100 x 15 cm 100 x 25 cm	100 x 25 cm
K Z	Squareness and straightness	EN-ISO 24342	≤ 0.35 mm	≤ 0.35 mm
	Residual indentation Typical value	EN-ISO 24343-1	≤ 0.15 mm ~0.05	≤ 0.15 mm ~0.05
	Castor chair continuous use	EN 425	Suitable for office	ce chairs with castors
R	Light fastness	EN-ISO 105-B02	Method 3: blue scale minimum 6	
	Resistance to chemicals	EN-ISO 26987	Resistant to diluted acids, oils, fats and to conventional solvents. Not resistant to prolonged exposure to alkalis.	
<b>e</b> 7	Bacteriostatic properties			operties, which are confirmed by independent gainst the bacteria MRSA.
	Cigarette resistance	EN 1399		f the surface by cigarettes. stubbed-out cigarettes can be removed.
78	Slip resistance	DIN 51130	R9	R9
١	Acoustical impact sound reduction	EN ISO 717-2	≤ 5 dB	≤ 5 dB
LCA	Life Cycle Assessment		LCA is the foundation for securing	ng the lowest environmental impact.
	Marmoleum meets the requirements	s of EN 14041		EN 14041 C <b>E</b> 0100203-DoP-306
C <sub>II</sub> -s1	Reaction to fire	EN 13501-1	C <sub>n</sub> -s1	C <sub>n</sub> -s1
9 E	Slip resistance	EN 13893	DS: ≥ 0.30	DS: ≥ 0.30
Ź	Body voltage	EN 1815	< 2 kV	< 2 kV
111	Thermal conductivity	EN 12524	0.17 W/m·K	0.17 W/m·K




70 Technical specifications Marmoleum Modular 71

# MARMOLEUM CLICK FUN TO DESIGN, EASY TO INSTALL

Marmoleum Click is a high quality, easy to install floor panel system made with a high density fibre board (HDF) core, a cork backing and Forbo Marmoleum on top and is available in a wide range of colours. It is ideal for kitchens, living rooms, hallways, bedrooms, playrooms and studies. (Marmoleum Click is not recommended for rooms that regularly get very wet, such as bathrooms and saunas). Marmoleum Click is available in 90 cm x 30 cm panels and 30 cm x 30 cm squares and features a patented click system, which guarantees easy, problem-free installation. With Marmoleum Click, it really is easy to turn your wildest dreams into a beautiful reality.

# Marmoleum Click is a snap to install


Marmoleum Click also improves life for people with asthmatic allergies and similar disorders. Not only it is anti-static (which is why it's so easy to keep dust-free), but its lab-proven bacteriostatic properties inhibit microorganisms as well. And because Marmoleum is a natural product, it reaches room temperature quickly, ensuring your house is snug and warm. It can even be used with under-floor heating.




Marmoleum Click is a snap to install. Slot it together with the simple locking system and literally click the panels into place. Because Marmoleum Click panels are wide and leave no seams when connected, it's easy to get a nice smooth finish in no time. And there's no need to mess around with glue or waiting for it dry. Lay it, walk on it. Of course, your Marmoleum Click retailer can also fit your floor, if you prefer. Marmoleum Click can be installed over every type of surface. The only time extra preparation is needed is if the floor or underlay is very uneven (differences of 2 mm or more). We also offer a range of matching skirting finishes to give your room that extra touch.







Marmoleum Click lets you create endless design effects.
Quiet shades for a neutral background. Cheerful colours to brighten up your home. Fresh colours that soothe.
Light ones to make a room look bigger. Warm colours to make difficult spaces cosy. Marmoleum Click's colours are inspired by nature, but its beauty is more than skin deep.




74 Marmoleum Click 75


# Technical specifications: **marmoleum**

# Marmoleum Click meets the requirements of EN 14085

	Marmoleum Click			
Total thickness	EN-ISO 24346	9.8 mm		
Nominal thickness Marmoleum	EN-ISO 24346	2.5 mm		
Locking system		5G		
Domestic: heavy	EN-ISO 10874	Class 23		
Commercial: heavy	EN-ISO 10874	Class 33		
Tile/panel size	EN ISO 24341	30 x 30 cm 60 x 30 cm 90 x 30 cm		
Packaging per carton 30 x 30 cm Packaging per carton 60 x 30 cm Packaging per carton 90 x 30 cm		0.63 m² (7 squares) 1.26 m² (7 panels) 1.89 m² (7 panels)		
Residual indentation typical value	EN-ISO 24343-1	≤ 0.15 mm ~0.08		
Castor chair resistance	EN 425	Suitable for office chairs with castors.		
Light fastness	EN-ISO 105-B02	Method 3: blue scale minimum 6.		
Resistance to chemicals	EN-ISO 26987	Resistant to diluted acids, oils, fats and to conventional solvents. Not resistant to prolonged exposure to alkalis.		
Bacteriostatic properties		Marmoleum has natural bacteriostatic properties, which are confirmed by independent laboratories, even against the bacteria MRSA.		
Cigarette resistance	EN 1399	Marks left on linoleum as a result of stubbed-out cigarettes can be removed.		
Slip resistance	DIN 51130	R9		
Acoustical impact sound reduction	EN ISO 717-2	> 17 dB ≥ 21 dB (installed on Forbo foam)		
Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact.		
Marmoleum Click meets the requirements of El	N 14041	EN 140 C 0 0101601_D		
Reaction to fire	EN 13501-1	C <sub>n</sub> -s1		
Formaldehyde emission	EN ISO 717-1	E1		
Slip resistance	EN 13893	D5: ≥ 0.30		
Body voltage	EN 1815	< 2 kV		
Thermal conductivity	EN 12524	0.15 W/m·K		



# **MARMOLEUM SPORT** THE INNOVATIVE IN-DOOR SPORTS FLOORING





83120 3.2/4,0 mm 83878 3.2/4,0 mm 83212 3.2/4,0 mm 83208 3.2/4,0 mm 83215 3.2 mm

3,2 / 4,0 mm

3,2 / 4,0 mm 83210



Marmoleum sport is a natural linoleum that is supplied without any surface treatment to facilitatie the application of sports-striping to indicate the variety of indoor sports that can be played in the venue, after which a suitable surface finish is applied.

83711 + 83707

80 Marmoleum Sport Move 81

3,2 / 4,0 mm

# Technical specifications: **marmoleum** sport

Marmoleum Sport meets the requirements of EN-ISO 24011, EN 14904 and DIN V 18032-2

· v	Total Thickness	EN-ISO 24346	3.2 mm	4.0 mm
	Roll Width	EN-ISO 24341	2.00 m	2.00 m
	Roll Length	EN-ISO 24341	≤ 28m	≤ 28m
	Total Weight	EN-ISO 23997	3.7 kg/m <sup>2</sup>	4.6 kg/m²
52	Flexibility	EN-ISO 24344	50 mm	60 mm
	Light reflection	DIN 5036-3	≥ 0.20 (except colour 83210, 83215, 83707)	≥ 0.20 (except colour 83210, 83215, 83707)
<b>7</b>	Light Fastness	EN-ISO 105-B02	Method 3: blue s	cale minimum 6.
٩	Acoustical impact noise reduction	EN-ISO 717-2	6dB	7dB
	Castor Chair continous use	EN 425	No effect	No effect
	Residual Indentation	EN-ISO 24343-1	≤ 0,15 mm	≤ 0,20 mm
<b>9</b>	Bacteriostatic properties		yes	yes
	Cigarette resistance	EN 1399	There is no melting of the surface b as a result of stubbed-out o	
38	Slip Resistance	EN 13893	DS ≥ 0.30	DS ≥ 0.30
Ĝ	Body voltage	EN 1815	< 2 kV	< 2 kV
	Thermal conductivity	EN 12524	0.17 W/m-K	0.17 W/m-K
LCA	Life Cycle Assesment		yes	yes
				EN 14904
	Marmoleum Sport meets the requirements of EN 14904			0100208_DoP-309
B <sub>n</sub> -s1	Reaction to fire	EN 13501-1	C <sub>n</sub> , S1	C <sub>nr</sub> S1
	Friction	EN 13036-4	80-110	80-110
	Resistance to rolling load	EN 1569	Pass	Pass
	Resistance to wear	EN-ISO 5470-1	≤ 1000mg	≤ 1000mg

Marmoleum Sport meets the emission requirements and is AgBB by DIBt building approval: approval no. Z-156604-627]

Certification from sports associations, e.g. Fiba or IHF, is only provided on the surface layer in combination with the subfloor. There are examples in the market available of complete floor systems which use Marmoleum Sport that received certificates from either Fiba, IHF or other sport associations.



# FOR WALL AND FURNITURE SURFACE APPLICATIONS

The Furiture and Bulletin Board are linoleum products which have amultitude of surface application possibilities. Its properties make it ideally suited for use on notice boards, and it provides a functional finish to walls, furniture, door panels and cupboards. Both collections are produced from renewable raw materials.

## Furniture linoleum

Forbo Furniture Linoleum is the finishing touch for everyone who wants to create breathtaking beautifully designed and functional furniture that will stand out from the crowd while also standing the test of time. A high-quality material with a proven pedigree, Furniture Linoleum is renowned for its elegance and durability and is suitable for countless stunning decorative surfacing applications. The unique aesthetic and tactile properties of Furniture Linoleum ensure that every object develops its own character. The combination of matt surface and a warm, soft texture are your guarantee for interior furniture with a truly distinctive, genuinely individual look and feel that really is unlike any other surface material available.


# **Bulletin Board**

Bulletin Board is a linoleum surfacing material with exceptional durability that is ideal for use on noticeboards and pinboards. Bulletin Board is applicable wherever people communicate with one another. The strong, durable, resilient properties of Bulletin Board prevent crumbling and loss of grip often associated with traditional materials such as cork or soft board. Bulletin Board is hygienic due to the fact that it does not attract dust and is bacteriostatic.

Bulletin Board can be applied to flat concrete walls, walls with a cement-stabilised plaster finish, gypsum walls, dividing walls and sheet materials such as hardboard, fibreboard, plywood, MDF and HDF. It can be applied to the wall in a vertical or horizontal direction.



Linoleum for walls and furniture



- 3. Water-based, cross-linked finish
- 2. Linoleum
- 1. Paper

Forbo's Furniture Linoleum, Desktop, is a natural surfacing material that delivers the finishing touch for all high end 3D furniture designs such as desks, chairs, stools, cabinets, doors and displays. The material is flexible and can be applied as a surface on all kinds of constructions. Furniture Linoleum is renowned for its elegance and

durability, radiating high quality and finesse.







bulletin board®

Pinboard linoleum, or Bulletin Board, offers a practical, simple solution to collect and exchange thoughts and ideas whenever people plan, create and meet. Simply share your thoughts by pinning your idea onto the wall. Bulletin Board is an all natural material that can be applied in framed pin boards or directly onto the wall. Its surface is tactile and colourful, creating a decorative element in your space, in addition to being a practical aid in your day to day activity.

\* also available in 183 cm



# Technical specifications: **furniture linoleum**

# Desktop meets the requirements of EN 688


		aesktop
Total Thickness	EN 428	2.0 mm
Collection size		20
Roll width	EN 426	1.83 m
Roll length	EN 426	≤ 30 m
Total weight	EN 430	2.1 kg/m²
Indentation-residual	EN 433	< 0.20 mm
Light fastness	ISO 105-B02	Method 3: blue scale minimum 6.
Gloss level	ISO 2813	<5
Flexibility	EN 435	ø 50 mm
Resistance to chemicals	EN 423	Resistant to diluted acids, oils, fats and to the conventional solvent. Not resistant to prolonged exposure to alkalis.
Heat resistance	EN 433	70°C.
A Life Cycle Assesment		LCA is the foundation for securing the lowest environmental impact
Body voltage	EN 1815	< 2 kV


<sup>\*</sup> Typical value

The above information is subject to modifications for the benefit of further improvements.

# Technical specifications: **bulletin board**

×	Total Thickness	EN-ISO 24346	6.0 mm ± 0.25 mm
Ŷ	Roll Width	EN-ISO 24341	1.22 m (3 colours in 1.83 m)
- <u>\$</u> }	Roll Length	EN-ISO 24341	≤ 28 m
٩	Total Weight	EN-ISO 23997	$4.7 \text{ kg/m}^2 \pm 10\%$
9	Flexibility	EN-ISO 24344	Ø 50 mm, according to method A
))))	Sound absorption coefficient	EN-ISO 354	a <sub>w</sub> 0.1 (typical)
<b>=</b>	Thermal conductivity	EN 12524	0.10 W/m-K
	Self-healing properties	LH000420	yes
	Force on pins - Perpendicular to pin direct	LH000421	25 N (typical)
	Force on pins - Perpendicular to pin at 7 mm	LH000421	10 N (typical)
	Force on pins - Parallel to pin (pulling the pin out)	LH000421	15 N (typical)
Ţ	Bacteriostatic properties	EN-ISO 22196	yes
Ö	Chemical resistance	EN-ISO 26987	Resistant to diluted acids, oils and most conventional solvents such as alcohol, white spirit, etc. Not resistant to prolonged exposure to alkalis.
K 7)	Dimension stability		Due to the natural jute back, providing a strong durable foundation, the product is dimensionally stable in all directions when properly installed. It resists cracking, drying and peeling.
	Anti-static		yes
	Gloss		Only available in matt colours, so that reflection caused by sunlight or artificial light is reduced.
	Natural materials (e.g. cork, linseed oil, jute)		91%
	Recycled content		43%
	PVC, PET, plasticizers content		0%





# **PROJECTVINYL**

# **Luxury Vinyl Tiles**

## 96 allura

Allura LVT floors present the ultimate finesse in realistic wood and stone designs that have been made with high end European based production techniques to create today's most realistic and natural look & feel in luxury vinyl tiles.

# 108 allura flex

Allura Flex loose lay tiles and planks are the ultimate LVT. High quality, dimensionally stable, heterogeneous vinyl tiles that have been specifically designed for loose lay installation.

# 114 allura flex 0.55

Allura Flex 0.55 loose lay tiles bring a new design concept to loose lay installation. This multi-layer dimensionally stable high tech vinyl tile is designed to reflect the latest flooring trends and offers unique designs and endless combination opportunities.

### 118 allura flex decibel

Allura Flex Decibel is looking stunning with an impact sound reduction of 19dB. It offers similar speedy installation properties and dimensional stability as regular allura flex products.

# 120 allura click

18 elegant designs in woods and stones which can be quick and easily installed thanks to the unique and patented click system. Realistic plank sizes, natural embossing and true tone colours make every item unique.

# **Homogeneous Vinyl**

# 130 allura colour

The Allura Colour tiles are unique high density pressed flooring tiles with a homogeneous composition ensuring an outstanding performance under high traffic conditions.

# 134 sphera

Sphera is Forbo's new premium, homogeneous vinyl collection. Styled by our European design team and using the latest production technology in an advanced purpose-built manufacturing plant, Sphera comprises three distinct ranges, Element, Energetic and Evolution. Each range offers differentiated aesthetics to ensure that Sphera adds interest and style to floor designs across a broad range of applications.

# **Hetrogeneous Vinyl**

# 144 eternal

Eternal vinyl floors present an advanced range of natural wood, stone, textile and colour designs along with some exclusive digitally printed visuals. Eternal is a high tech heterogeneous compact sheet vinyl that fits all general purpose needs in various segments.

# 154 digitally printed vinyl

Our advanced digital printing technology has provided our design team with the tools to develop striking visuals that cannot be achieved with conventional print techniques but also has the option to design your own floor.

# 158 **step**

Step safety vinyl floors have guaranteed life time slip resistant performance and also offer unique solutions for wetroom applications, providing the best 'bare foot', as well as 'bare foot / footwear' non slip solutions. The collection comprises various subranges each with it's own properties, offering a solution for any area that requires a safety floor.

# 176 sarlon acoustic vinyl

Takes sound reduction to the next level. Acoustic floors have an important contribution when it comes to reducing noise in buildings. Forbo Flooring is a specialist in acoustic floors with more than 30 years of experience. In our Sarlon acoustic vinyl range we offer floors with an impact sound reduction of up to 19dB in a wide variety of colours and designs.

# **ESD Floor Covering**

# 190 **colorex**

The Colorex collection offers a premium brand of conductive and static dissapative high density dimentional stable tiles. Colorex is an advanced technical flooring system specifically designed to control static discharge in sensitive areas such a cleanrooms, operating theatres and the electronics industry.



Allura is Forbo's brand of Luxury Vinyl Tile (LVT) and over the past decade, it's established itself as one of the most popular brands in our extensive product portfolio. There is no other LVT in the market today that can match Allura in terms of design, technology and sustainability. Designed and produced in Europe, Allura uses advanced production technology to ensure maximum dimensional stability so that the appearance of the floor remains as seamless as the day it was installed. Protected by our exclusive lacquering system it will stand the test of time.

The Allura design signature is inspiring, offering over 100 different designs in a wide variety of different sizing. This including our widest collection of wood designs. The range of stone and abstract designs ranges from classic marbles and concretes to eye catching galaxy and space designs. Allura is the Luxury Vinyl Tile of choice, take a look and see for yourself what Allura has to offer you and get inspired by the endless possibilities.

For increased flexibility, a selection of 34 designs are available in both fully adhered, click and loose lay (tackified) formats.

# DESIGN WINNOVATION

- Beautiful wood, stone, metal and abstract designs offered in many different sizes of planks and tiles
- Each wood and stone design reflects true life
- 14 embossing structures make Allura come to life, choosing the right structure for every design
- Striking new LVT designs such as Hungarian point and XXL planks



# DURABILITY \*\* PERFORMANCE

- Embossed lacquering systems ensure lasting appearance retention
- Scratch and stain proof by hard, yet flexible top layer
- 100% dimensionally stable avoiding gaps between tiles appearing over time

# SUSTAINABLE FASY



- · Manufactured with green electricity and 100% phthalate free
- Over 20% recycled content in the backing
- Easy to clean and maintain through specially embossed top-layer



The phthalate free Allura collection is REACH\* compliant and produced in Europe with low emission levels.

The excellent dimensional stability ensures safe and hygienic floors as dirt isn't trapped in the seams. Available in natural stress reducing designs and high LRV's, choosing Allura means you are choosing to create better indoor & outdoor environments.

\* Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) address the production and use of chemical substances and their potential impacts on both human health and the environment.



# allura®












mist texture










# allura® a63453



Format strips: 100 x 0,5 cm

allura® strips overview

space galaxy

white

certain designs, such as grout lines or accentate the

w60063 | f60074

PROJECT VINYL

106 Allura Allura 107

f60074 | black rustic oak

f63624 | silver metal brush



Allura Flex is a collection of high quality, dimensionally stable, heterogeneous loose lay vinyl tiles and planks which are adhered with tackifier that allows post use removal. The design concept of Allura Flex consists of the most realistic wood designs in the market, but also essential concretes and interesting textile and colour effects. The 43 designs offer a large design freedom; also in larger sizes and the specific Hungarian Point format and are easy to combine. The collection offers something for all commercial floors, also in use alongside carpet tiles because of the 5 mm gauge. Allura Flex has a 1 mm transparent wear layer and proven PUR finish.

The Forbo exclusive combination of functional layers, including a strong glass fleece carrier, makes Allura Flex unprecedented in dimensional stability, strength, performance and quality. Beautiful designs in wood, stone and brights that are easy to install, resulting in stunning and reliable floors.

> For increased flexibility, a selection of 34 designs are available in not only loose lay but also fully adhered and click formats.

# DESIGN WINNOVATION

- Beautiful wood, stone and bright designs offered across 43 plank and tile formats
- Realistic embossing structures bring every Allura Flex design to life
- · Available in a variety of sizes, including XL tile and plank formats

# DURABILITY PERFORMANCE



- Scratch and stain proof by hard, yet flexible top layer with best appearance retention
- Best dimensionally stable avoiding seam gaps appearing over time
- Only functional layers that enhance the performance of the product

# SUSTAINABLE WEASY



- Manufactured with green electricity and 100% phthalate free
- Over 50% recycled content in the backing layer
- Easy to clean and maintain through specially embossed top-layer




The phthalate free Allura collection is REACH\* compliant and produced in Europe with low emission levels.

The excellent dimensional stability ensures safe and hygienic floors as dirt isn't trapped in the seams. Available in natural stress reducing designs and high LRV's, choosing Allura means you are choosing to create better indoor & outdoor environments.

\* Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) address the production and use of chemical substances and their potential impacts on both human health and the environment.



108 Allura Flex Allura Flex 109








110 Allura Flex

\* designed with natural colour variation 🕹 2 sided bevelled 🕹 4 sided bevelled 🕀 in register embossing 📗 hungarian point size





blanco marble

blanco marble

sky marble

oyster marble

oyster marble

oyster marble

anatural concrete

malachite hybrid

114 Allura Flex 0.55 115



The inviting realistic Wood designs complement office, retail, leisure and hospitality spaces. Allura Flex 0.55 Wood planks are available in 3 plank sizes:  $20 \times 100$ ,  $20 \times 120$  and  $28 \times 150$  cm.





116 Allura Flex 0.55 117



With 18 energetic colours Allura Flex Decibel is looking stunning with an impact sound reduction of 19dB. Although it is a much lighter product than conventional loose lay tiles, the innovative double glass fleece construction offers similar speedy installation properties and dimensional stability. Flex Decibel offers a quick installation solution in, for example, busy offices, housing projects and communal and retail spaces.



Allura Flex Decibel Allura Flex Decibel



and easily installed thanks to our proven and patented click system. Protected by our exclusive lacquering system it will stand the test of time.

Allura Click is produced in Europe and includes Forbo's unique glass fleece construction for dimensional stability. The click system can be angled down, creating a perfect floor installation. Forbo always emphasizes a proper subfloor preparation as a guarantee that the product can be installed without any requirement for flooring adhesives, resulting in a beautifully finished and functioning floor solution.



# DESIGN WINNOVATION

- Exclusive wood and stone designs offered in different sizes
- Realistic embossing structures bring every Allura Click design to life
- Bevelled wood planks for enhanced realism



# DURABILITY PERFORMANCE

- Embossed lacquering systems ensure lasting appearance retention
- Scratch and stain proof by hard, yet flexible top layer
- Best dimensionally stable avoiding seam gaps appearing over time
- Patented locking systems ensure a strong and lasting connection

# SUSTAINABLE FASY



- Manufactured with green electricity and 100% phthalate free
- Recyclable and easy to repair
- Time optimal, quick and easy installation also suitable for mid-size installations
- Easy to clean and maintain through specially embossed top-layer




The phthalate free Allura collection is REACH\* compliant and produced in Europe with low emission levels. The excellent dimensional stability ensures safe and hygienic floors as dirt isn't trapped in the seams. Available in natural tranquil and pleasing designs and high LRV's. A choice for Allura means a choice for creating a better quality indoor environment.

\* Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) address the production and use of chemical substances and their potential impacts on both human health and the environment.




120 Allura Click Allura Click 121








122 Allura Click \* designed with natural colour variation → 4 sided bevelled → 4 sided bevelled ↓ in reginal to the first of the first





Allura Click Decibel is an innovative combination of our regular Allura Luxury Vinyl Tile on top of a stable, noise reducing combination of HDF and Forbo PU underlay.

- LVT that brings acoustical impact noise reduction of 19 dB
- Time saving of 20% thanks to the integrated sub floor
- An economical solution to cover old soils, including asbestos (according to current regulations)
- Ideal thickness in combination with tiles or carpet tiles





grigio concrete natural concrete


Magic things happen when our Allura luxury vinyl tiles meet our Step slip-resistant floors. Combining Step Crystals with our most appropriate Allura LVT designs, Allura Safety is the first flooring to combine the looks and performance of LVT with the safety properties of our Step floors.























128 Allura Safety Allura Safety 129



Whether you are looking for a bright colourful floor, or where you would like to have a natural stone like appearance, Allura colour has the solution. The designs are available in 24 colours, each with a matching chipmix of coloured and transparent particles. Allura colour floors are vibrant and hardwearing, an ideal combination for tough environments that still want to show a difference.



Allura Colour 131

# Technical specifications: **allura**

			Allura 0.70	Allura 0.55	Flex	Flex 0.55	Click
° v	Total thickness	EN-ISO 24346	2.5 mm	2.5 mm	5 mm	4 mm	5 mm
$\stackrel{\leftarrow}{\boxtimes}$	Wearlayer thickness	EN-ISO 24340	0.70 mm	0.55 mm	1 mm	0.55 mm	0.55 mm
	Collection size		112	112	43	43	38
<u></u>	Domestic use	EN-ISO 10874	23	23	23	23	23
	Commercial/light industrial use	EN-ISO 10874	34/43	33/42	34/42	33/42	33
	Tile size	EN-ISO 24342	50 x 50 cm / 75 x 25 cm / 75 x 50 cm / 75 x 75 cm / 100 x 100 cm	50 x 50 cm / 75 x 25 cm / 75 x 50 cm / 75 x 75 cm / 100 x 100 cm	50 x 50 cm / 100 x 100 cm	50 x 50 cm / 100 x 100 cm	60 x 31.7 cm
	Plank size	EN-ISO 24342	50 x 15 cm / 100 x 15 cm / 120 x 20 cm / 150 x 28 cm / 180 x 32 cm / HP 90 x 15 cm	50 x 15 cm/ 100 x 15 cm/ 120 x 20 cm/ 150 x 28 cm/ 180 x 32 cm/ HP 90 x 15 cm	100 x 20 cm / 120 x 20 cm / 150 x 28 cm / HP 120 x 20 cm	100 x 20 cm / 120 x 20 cm / 150 x 28 cm / HP 120 x 20 cm	121.2 x 18.7 cm / 150.5 x 23.7 cm
	Packaging per carton tiles		3 m <sup>2</sup> (12 pcs) / 4.5 m <sup>2</sup> (24 pcs) / 3.75 m <sup>2</sup> (10 pcs) / 0.56 m <sup>2</sup> (1 pce) / 1 m <sup>2</sup> (1 pce)	3 m <sup>2</sup> (12 pcs) / 4.5 m <sup>2</sup> (24 pcs) / 3.75 m <sup>2</sup> (10 pcs) / 0.56 m <sup>2</sup> (1 pce) / 1 m <sup>2</sup> (1 pce)	2.5 m <sup>2</sup> (10 pcs) / 1 m <sup>2</sup> (1 pce)	2.5 m <sup>2</sup> (10 pcs) / 1 m <sup>2</sup> (1 pce)	1.90 m <sup>2</sup> (10 pcs)
	Packaging per carton planks		3 m² (40 pcs) / 3 m² (20 pcs) / 2.88 m² (12 pcs) / 4.2 m² (10 pcs) / 4.6 m² (8 pcs) / 4.5 m² (40 pcs)	3 m² (40 pcs) / 3 m² (20 pcs) / 2.88 m² (12 pcs) / 4.2 m² (10 pcs) / 4.6 m² (8 pcs) / 4.5 m² (40 pcs)	2 m <sup>2</sup> (10 pcs) / 2.4 m <sup>2</sup> (10 pcs) / 2.52 m <sup>2</sup> (6 pcs) / 2.4 m <sup>2</sup> (12 pcs)	2 m <sup>2</sup> (10 pcs) / 2.4 m <sup>2</sup> (10 pcs) / 2.52 m <sup>2</sup> (6 pcs) / 2.4 m <sup>2</sup> (12 pcs)	1.81 m² (8 pcs) / 2.14 m² (6 pcs)
	Squareness and straightness	EN-ISO 24342	< 400 mm < 0.25 mm > 400 mm < 0.35 mm	< 400 mm < 0.25 mm > 400 mm < 0.35 mm	< 400 mm < 0.25 mm > 400 mm < 0.35 mm	< 400 mm < 0.25 mm > 400 mm < 0.35 mm	< 400 mm < 0.25 mr > 400 mm < 0.35 mr
	Total weight	ISO 23997	ca 3600 g/m²	ca 3400 g/m²	ca 6550 g/m²	ca 5200 g/m²	8300 gr/m <sup>2</sup>
	Wearlayer binder content	EN-ISO 10582	Type 1	Type 1	Class T	Class T	Type 1
38	Slip resistance	DIN 51130	R10	R10	R10	R10	R10
١	Acoustical impact noise reduction	EN ISO 717-2	6 dB	6 dB	14 dB	14 dB	7 dB / 15 dB in combination with Forbo underlay
	Castor chair continuous use	ISO 4918	Superior	Very good	Superior	Very good	Good with and without Forbo underlay
	Residual indentation Typical value	ISO 24343-1	≤ 0.10 mm ~ 0.04 mm	≤ 0.10 mm ~ 0.04 mm	≤ 0.20 mm ~ 0.11 mm	≤ 0.10 mm ~ 0.04 mm	≤ 0.10 mm ~ 0.05 mm
<b>P</b>	Light fastness	ISO 105-B02	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6
	VOC emissions	ISO 16000-9	≤ 100 µg/m³	≤ 100 µg/m³	≤ 110 µg/m³	≤ 110 µg/m³	≤ 160 µg/m³
<b>\$</b>	Resistance to chemicals	EN-ISO 26987	Very good	Very good	Very good	Very good	Very good
K 7	Dimension stability (after exp. to heat)	EN-ISO 23999	≤ 0.05%	≤ 0.05%	≤ 0.05%	≤ 0.05%	≤ 0.05%
	Allura meets the requirements o	f EN 14041	EN 14041 <b>C É</b> 0200130-DoP-306	EN 14041 C E	EN 14041 <b>C €</b> 0200131-DoP-507	EN 14041 C <b>E</b>	EN 14041 <b>C €</b> 0200132_DoP_701
B <sub>m</sub> s1	Reaction to fire	EN 13501	B <sub>ff</sub> -s1	0200130-DoP-306 B <sub>fl</sub> -s1	B <sub>A</sub> -s1	0200131-DoP-507 B <sub>n</sub> -s1	B <sub>n</sub> -s1 with and without For underlay
**************************************	Slip resistance	EN 13893	DS - μ > 0.30	DS - μ > 0.30	DS - µ > 0.30	DS - μ > 0.30	DS - μ > 0.30
	Thermal conductivity	EN 12524	0.25 W/mK	0.25 W/mK	0.25 W/mK	0.25 W/mK	0.25 W/mK
<u></u>	Body voltage	EN 1815	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV

# Technical specifications: **allura**

			Allura Click Decibel	Allura Flex Decibel	Allura Safety	Allura Colour
· ×	Total thickness	EN-ISO 24346	10 mm	3.45 mm	2.5 mm	2 mm
* ×	Wearlayer thickness	EN-ISO 24340	0.55 mm	0.65 mm	0.7 mm	1 mm
	Collection size		9	18	16	24
	Residential use	EN-ISO 10874	23	-	-	-
	Commercial use	EN-ISO 10874	33	33	34	34
	Light industrial use	EN-ISO 10874	-	42	43	43
	Tile size	EN-ISO 24342	60 x 31.7 cm	50 x 50 cm	48 x 48 cm	61 x 61 cm
	Plank size	EN-ISO 24342	121.2 x 18.7 cm / 150.5 x 23.7 cm	20 x 100 cm	-	-
اگ	Total weight	ISO 23779	ca 9800 g/m²	ca 2800 g/m²	ca 3600 g/m²	ca 3100 g/m²
38	Slip resistance	DIN 51130	R10	R9	R10	R9
	Acoustical impact noise reduction	EN ISO 717-2	19 dB	19 dB	6 dB	14 dB
	Castor chair continuous use	ISO 4918	Very good	Very good	Superior	Very good
	Residual indentation	ISO 24343-1	≤ 0.05 mm	≤ 0.12 mm	≤ 0.04 mm	≤ 0.04 mm
<b>3</b>	Light fastness	ISO 105-B02	≥ 6	≥ 6	≥ 6	≥ 6
	Resistance to chemicals	EN-ISO 26987	Very good	Very good	Very good	Excellent
[K 7]	Dimensional stability	EN-ISO 23999	≤ 0.05%	≤ 0.10%	≤ 0.05%	≤ 0.05%
	Allura meets the require	ments of EN 14041	EN 14041 <b>C E</b> 0200140-DoP-503	EN 14041 <b>C E</b> 0200935-DoP-410	EN 14041 <b>C E</b> 0200102_DOP_411	EN 14041 <b>C €</b> 0200130_DOP_306
	Reaction to fire	EN 13501	B <sub>n</sub> -s1	C <sub>n</sub> -s1	B <sub>f</sub> -s1	B <sub>n</sub> -s1
* % §	Slip resistance	EN 13893	DS - μ > 0.30	DS - µ > 0.30	DS - μ > 0.30	DS - µ > 0.50
	Thermal conductivity	EN 12524	-	0.25 W/mK	0.25 W/mK	0.25 W/mK
	Body voltage	EN 1815	-	< 2 kV	< 2 kV	< 2 kV

132 Technical Specifications Allura 133

# SPHERA HOMOGENEOUS VINYL

Forbo Sphera is setting new standards in homogeneous vinyl flooring. It is produced in our brand new manufacturing plant where all the latest insights and technology have been used to create smart and innovative solutions. The result: a premium homogeneous vinyl floor covering!

Our Sphera flooring adds character and style to floors across numerous applications. Whether in demanding, hygienic healthcare environments, in flexible, multi-purpose modern public buildings or in education facilities and offices where durability and colour are key.

# Design & colour

Low emitting and 100% phthalate free

- A new technology delivers bright and saturated hues, resulting in striking colourtones, many with high light reflection values (LRV)
- Sphera offers a balanced palette of 62 colours that coordinates well with other Forbo floor coverings like Marmoleum and textile flooring.

# Technology & sustainability

- State of the art steel-belt press and thermofix technology provide consistent quality
- Green energy and zero waste technology ensure efficient and sustainable manufacturing
- Sphera can contribute to a healthy indoor environment by phtalate free manufacturing & low emissions

# Performance & durability

Produced in a zero waste environment

- A unique embossing process following lacquer application delivers durable performance
- In-line coating and subsequent embossing process provides superior appearance
- The evenly distributed top-layer provides superior all over protection
- The SMART-top surface finish ensures that Sphera has a high resistance to chemicals, scratches and stains
- Sphera achieves the highest abrasion wear rating group T tested to EN660-2



134 Sphera



Forbo Sphera is setting new standards in homogeneous vinyl flooring because of its design, technology and performance. Sphera Element offers a 62 fresh, light and contemporary colour palette which adds a sophistication to floor design. The collection includes warm and cool neutrals which complement interior finishes such as wood and stone along with pastels and bright accent colours for areas requiring way-finding or zoning.




136 Sphera Element 137






138 Sphera Element 139




Sphera homogeneous vinyl floor coverings add character and style to floors across numerous applications. Sphera Energetic has the thrilling sensation of crossing design boundaries, making homogeneous vinyl look different. Energetic offers an intricate pallet of semi plain and larger particle-mix colours. Transparent granules provide for depth and dirt hiding properties. Sphera Energetic is playful and designed to combine with corresponding visuals with vivid highlights. The palette contains 41 solid colours and 11 matching colours with vivid accent chips.





Sphera Energetic 141



# Technical specifications: **sphera**

# Sphera element and energetic meets the requirements of EN-ISO 10582

			element	energetic
	Binder content	EN-ISO 10581	type 1	type 1
,	Total thickness	EN-ISO 24346	2.0 mm	2.0 mm
	Surface finish		SMART top	SMART top
	Collection size		62	52
iji.	Commercial use	EN-ISO 10874	34 very heavy	34 very heavy
iii)	Industrial use	EN-ISO 10874	43 heavy	43 heavy
	Roll width	EN-ISO 24341	2 m	2 m
	Roll length	EN-ISO 24341	± 25 m	± 25 m
ß	Total weight	EN-ISO 23997	2.9 kg/m²	2.9 kg/m <sup>2</sup>
K Z	Dimensional stability	EN-ISO 23999	< 0.2 %	< 0.2 %
	Residual indentation	EN-ISO 24343-1	≤ 0.10 mm, typical value ~ 0.03	≤ 0.10 mm, typical value ~ 0.03
	Abrasion resistance	EN 660-2	group T	groupT
	Castor chair continuous use	ISO 4918 / EN 425	pass	pass
R	Light fastness	ISO 105-B02	≥ 6	≥7
5	Flexibility	EN-ISO 24344	ø 10 mm	ø 10 mm
	Resistance to chemicals	EN-ISO 26987	very good	very good
38	Slip resistance	DIN 51130	R10	R9
	Wetroom application		yes	yes
	Application on underfloor heating		yes	yes
	TVOC after 28 days	ISO 16000-6	≤ 10 µg/m³	≤ 10 µg/m³
			EN 14041	EN 14041
	Sphera element and energetic m	neets the requirements of EN 14041	0200103-DoP-605	0200103-DoP-605
°∭ B <sub>m</sub> s1	Reaction to fire	EN 13501-1	B <sub>n</sub> -s1	B <sub>n</sub> -s1
9 9 10	Slip resistance	EN 13893	DS - µ ≥ 0.30	DS - µ ≥ 0.30
73	Body voltage	EN 1815	≤ 2 kV	≤ 2 kV
<u> </u>	Thermal conductivity	EN 12524	0.25 W/m⋅K	0.25 W/m·K

Technical Specifications Sphera 143

## ETERNAL DESIGN VINYL SHEET

The Eternal collection presents an advanced range of natural wood, stone, textile and colour designs along with some exclusive digitally printed visuals. Eternal is a high tech heterogeneous compact sheet vinyl that fits all general purpose needs in various segments. It is produced with the latest technology containing up to 50% recycled content and is phthalate free.

#### **Product construction**

Eternal is created around a nonwoven, fully impregnated, glass fleece core which provides dimensional stability and allows a lean-development approach, resulting in a sustainable compact, high tech base. Adding to stability and determining the high quality standard of Eternal project vinyl is the optimized calandered backing; a firm yet flexible layer to allow easy installation, even when coving is required or in wetroom applications. The unique and innovative embossed wear layer ensures maximum wear resistance and provides optimal appearance retention. The backing layer of the construction, contains up to 50% re-used content.

#### Authenticity

All of the Eternal designs are true originals, created by an in-house team of expert designers who translate the latest trends in classic, contemporary as well as modern and advanced flooring designs that cannot be distinguished from their original material expressions, like wooden and concrete floors.

### **PUR Pearl and PUR Wood Pearl**

For the majority of our designs Forbo uses it's proven PUR Pearl lacquering protection technique. The application technique for the lacquering layer assures an even amount of lacquering both on top and in the deeper areas of the embossing. It prevents the surface collecting dirt and is the best guarantee for quality and gloss consistency that ensures low maintenance costs.

New in this collection are 8 items that are introduced with a specific PUR Wood embossing, offering the best possible performance on an allover wood grain design with integrated Pearl effect. The mat embossed lacquer layer ensures the highest level of both chemical- and scuff resistance.

#### Phthalate free

All Eternal collections are created with the highest environmental stands in mind using the best qualified virgin materials as well as controlled recycled content creating a closed loop production. In addition all items in the Eternal range are phthalate free.







146 Eternal Wood 147





12932 | grey woven



12942 | indigo woven









148 Eternal Material 149





44752 | rainbow

150 Eternal Colour 151



## Technical specifications: **eternal**®


## Eternal meets the requirements of EN-ISO 10582

e ×	Total thickness	EN-ISO 24346	2.0 mm	
×	Wear layer thickness	EN-ISO 24340	0.7 mm	
	Collection size		96	
	Commercial use	EN-ISO 10874	34 very heavy	
	Industrial use	EN-ISO 10874	43 heavy	
<del>^</del>	Roll width	EN-ISO 24341	2 m	
	Roll length	EN-ISO 24341	± 25 m	
2	Total weight	EN-ISO 23997	2.8 kg/m²	
K 7	Dimensional stability	EN-ISO 23999	< 0.1 %	
	Residual indentation	EN-ISO 24343-1	≤0.05, typical value 0.03	
	Abrasion resistance	EN 660-2	group T	
	Castor chair continuous use	ISO 4918 / EN 425	no effect	
泵	Light fastness	ISO 105-B02	≥ 6	
5	Flexibility	EN-ISO 24344	ø 10 mm	
	Resistance to chemicals	EN-ISO 26987	very good	
38	Slip resistance	DIN 51130	R10	
5/2 510 <sup>5</sup> Ω	Electrical resistance	EN 1081	R1 > 1·10° Ω	
<b>7</b>	Water tight installation	EN 13553	Yes	

## All Eternal products meet the requirements of EN 14041

All Eternal products meet th	e requirements of EN 14041		EN 14041 <b>C E</b> 0200105-DoP-306
Reaction to fire	EN 13501-1	B <sub>ff</sub> -s1	
Slip resistance	EN 13893	DS - µ ≥ 0.30	
Body voltage	EN 1815	≤ 2 kV	
Thermal conductivity	EN 12524	0.25 W/m·K	

152 Eternal Decibel Technical Specifications Eternal 153



Digitally printed vinyl

Our design vinyl sheet collection contains a series of digitally printed flooring designs which offer a new dimension in colour and design whilst retaining the full performance specification of the Eternal core collection. This includes a 0.7mm wear layer that ensures maximum wear resistance and excellent appearance retention.

Our advanced digital printing technology has provided our design team with the tools to develop striking visuals that cannot be achieved with conventional print techniques: subtle colour gradients that run along the full length of a roll, a rainbow cascade of colours with no pattern repeat over a 10 metre length, or spectacular geodes of polished gemstones that are available in a custom scaling. In addition to the digital print designs in the core Eternal collection, we also offer bespoke, tailored flooring designs from as little as 12m². So whether you are designing a meeting room, retail interior or creating a spectacular atrium in a school or public building.

## **RAINBOW**

The Eternal Rainbow design reveals a spectrum of colour gradients over a 10 metre length enabling a rolling cascade of rainbow hues as the first colour follows the last without any break in the pattern. This scale of pattern repeat is only achievable through digital printing technology. Eternal Rainbow is available in 1.95 metre wide rolls and the width can easily be extended to suit wider areas.




44752 | 43002

## **eternal**<sup>®</sup> magnified nature



From Geodes that offer giant 'gemstones' to a 'Petrified Bark' effect that will form a centerpiece in any interior space, this collection brings nature to the floor in a scale not seen before. As each design can be scaled in size, Magnified Nature is ideal for those looking to create an eye catching feature on the floor. The Eternal Magnified Nature designs are supplied as an inset piece which can be inserted into any of the Eternal colourways in the collection. For bespoke flooring projects, the Magnified Nature designs can also be rescaled to fit the required floor.

## Suggested floors to combine with:




























43132 | tender sparkle

40322 | smoke palette



43812 | taupe sparkle

43212 | mouse sparkle




43002 | fog sparkle

40542 | earth palette













43432 | espresso sparkle 43992 | violet sparkle

156 Eternal Magnified Nature Eternal Magnified Nature 157

# STEP SAFETY FLOORING





## BY CHOOSING A FORBO SAFETY FLOOR THE NUMBER OF ACCIDENTS CAUSED BY SLIPPING CAN BE REDUCED SIGNIFICANTLY.

Forbo's Step safety vinyl floors have guaranteed life time slip resistant performance and also offer unique solutions for wetroom applications, providing the best 'bare foot', as well as 'bare foot / footwear' non slip solutions. The collection comprises various subranges each with it's own properties, offering a solution for any area that requires a safety floor.

New & unique in the Step range are the slip resistant "Step Crystals", that provide security and contribute to a clean and fresh design, with proven easier cleaning. Step offers the widest range in design in safety flooring, without compromising performance.

### Safety. Design. Confidence.

Our Step safety vinyl collection is unique in many ways. It's a durable floor covering combining outstanding slip resistance (up to R12) with a wide range of design possibilities. The PUR Pearl surface provides superior, long-lasting appearance and performance.

## The collection is divided in 3 ranges:

Surestep (R10), Safestep (R11, R12) and Wetroom floors

#### Surestep

All Surestep floors provide R10 slip resistance, are non-slip particle enhanced and can be applied in all types of general walking areas where an increased slip


risk may occur. Typical areas are high traffic areas like corridors, ramps, coffee corners, washrooms, toilet, crafts class rooms and public rooms.

## Safestep

Safestep floors are applicable in areas where a higher slip risk is identified when incidental, accidental or continuous active contamination of the floor occurs. In these areas it is simply not possible to prevent spillage, due to the type of work environment. Typical areas are: professional kitchens, light industrial food production, flourist shops, garden centres.

**Wetroom** (Surestep Laguna, Safestep Aqua) Wetroom floor coverings are developed for use in continuously wet areas, where water flows frequently and barefoot traffic is the standard, or a combination of barefoot and footwear traffic occurs. Typical areas are; shower rooms, spa/pool surroundings, changing rooms, locker rooms.

## **ANTISLIPVALUES**




**All Step floors** 


**Surestep Laguna** Safestep Aqua

**Surestep Laguna** Safestep Aqua


Alle Surestep R10 Safestep R11 + R12 Safestep Aqua




All Surestep floors provide R10 slip resistance, are non-slip particle enhanced and can be applied in all types of general walking areas where an increased slip risk may occur. Typical areas are high traffic areas like corridors, ramps, coffee corners, washrooms, toilet, crafts class rooms and public rooms.



102 Suitstep Original







8902 | cotton






8901 | leather



166 Surestep Texture Surestep Texture





18932 | rustic oak

18362 | chestnut





18562 | grey seagrass



18662 | pear





18572 | black seagrass



17142 | warm concrete



17072 | anthracite




17162 | grey concrete





18792 | dark oak

168 Surestep Wood Surestep Stone 169



This modern, organic design with a new and unique embossing shape is designed for barefoot (and soft soled shoes) areas. Safestep Aqua is a flexible floor, that can easily be installed to the specifc requirements of these wetroom areas. And most importantly: it will perform on the highest barefoot class. The clean and modern collection fits the hygienic and sensitive requirements of the application areas, like bathrooms and swimming pool areas.

Specifications: Class B, R10, ESf + ESb, TRRL≥36, Rz≥20.

Surestep Laguna safety flooring combines barefoot and footwear slip resistance, for areas where both are likely and frequently will take place. Complying to the relevant norms for both needs, Surestep Laguna can cover all transition areas, like changing rooms and circulation areas. The subtle, soil hiding particle is integrated in the visual, offering a clean and fresh looking floor.



170 Surestep Aqua





174642 | cloudy







174562 | pepper






















175992 | charcoal

The Safestep R12 range offers soil hiding colourways and can also be colour matched with products in the Surestep collection and with Safestep R11. A high slip resistant R12 rated floor ensures slip resistance under even the most extreme conditions.

172 Surestep R11 Safestep R11 173



Forbo's Solidstep safety flooring is the fresh looking

179672 | jungle

## 

179392 | red

179902 | stateblue

179532 | sun

## Technical specifications: **safestep**

## Step meets the requirements of EN - ISO 10582 & EN 13845

			Surestep Original	Surestep Wood Surestep Stone Surestep Mineral					
			Surestep Star	Surestep Texture	Safestep Aqua	Surestep Laguna	Safestep R11	Safestep R12	Solidstep
· ×	Total Thickness	EN - ISO 24346	2.0 mm	2.0 mm	2.0 mm	2.0 mm	2.0 mm	2.0 mm	2.0 mm
* ×	Thickness wear layer	EN - ISO 24340	0.7 mm	0.7 mm	0.7 mm	0.7 mm	0.7 mm	0.7 mm	0.35 mm
<b>##</b>	Commercial very heavy	EN - ISO 10874	Class 34	Class 34	Class 34	Class 34	Class 34	Class 34	Class 34
Tm 333	Light industrial	EN - ISO 10874	Class 43	Class 43	Class 43	Class 43	Class 43	Class 43	Class 43
	Collection size		24 - 13	12-8-5-5	12	12	8	4	13
	Roll Width	EN - ISO 24341	2.00 m	2.00 m	2.00 m	2.00 m	2.00 m	2.00 m	2.00 m
	Roll Length	EN - ISO 24341	20 - 27 m	20 - 27 m	20 - 27 m	20 - 27 m	20 - 27 m	20 - 27 m	20 - 27 m
	Total Weight	EN - ISO 23997	2.75 kg/m <sup>2</sup>	2.75 kg/m²	2.75 kg/m <sup>2</sup>	2.75 kg/m <sup>2</sup>	2.75 kg/m <sup>2</sup>	2.75 kg/m²	2.75 kg/m²
K N K N	Dimension Stability	EN - ISO 23999	< 0.1%	< 0.1%	< 0.1%	< 0.1%	< 0.1%	< 0.1%	< 0.1%
	Residual Indentation	EN - ISO 24343-1	≤ 0.05 mm	≤ 0.05 mm	≤ 0.05 mm	≤ 0.05 mm	≤ 0.05 mm	≤ 0.05 mm	≤ 0.05 mm
	Castor Chair	EN 425	No effect	No effect	No effect	No effect	No effect	No effect	No effect
	Use in Wet areas	EN 13533	Yes	No	Yes	Yes	Yes	Yes	Yes
<b>3</b> 70	Light fastness	EN - ISO 105 B-02	≥6	≥6	≥6	≥6	≥6	≥6	≥6
5	Flexibility	EN - ISO 24344	ø 10mm	ø 10mm	ø 10mm	ø 10mm	ø 10mm	ø 10mm	ø 10mm
		EN 13845 Annex C	ESf	ESf	ESb	ESb / ESf	ESf	ESf	ESf
**************************************	Slip resistance	EN 13845 Annex D 50.000 revolutions <10% loss	Class 34/43	Class 34/43	Class 34/43	Class 34/43	Class 34/43	Class 34/43	Class 34/43
		DIN 51130	R10	R10	R10	R10	R11	R12	R10
		Din 51097			Class C	Class B			
	Chemical resistance	EN-ISO 26987	Very Good	Very Good	Very Good	Very Good	Very Good	Very Good	Very Good
* <u>//</u>	Electrical resistance	EN 1081 (R1)	> 1.10 <sup>9</sup> Ω	> 1.10 <sup>9</sup> Ω	> 1.10° Ω	> 1.10° Ω	> 1.10 <sup>9</sup> Ω	> 1.10 <sup>9</sup> Ω	> 1.10 <sup>9</sup> Ω
	Step meets the requirem	nents of EN 14041							EN 14041 CE 0200101-DoP-306
Bir-s1	Reaction to fire	EN 13501-1	B <sub>n</sub> -s1	B <sub>f</sub> -s1	B <sub>fl</sub> -s1	B <sub>ff</sub> -s1	B <sub>fl</sub> -s1	B <sub>fl</sub> -s1	B <sub>fl</sub> -s1
B	Body Voltage	EN 1815	< 2kV	< 2kV	< 2kV	< 2kV	< 2kV	< 2kV	< 2kV
	Thermal Conductivity	EN 12524	0.25 W/m.K	0.25 W/m·K	0.25 W/m·K	0.25 W/m·K	0.25 W/m·K	0.25 W/m·K	0.25 W/m·K
198	Slip resistance	EN 13893	DS: ≧0.30	DS: ≧0.30	DS: ≧0.30	DS: ≧0.30	DS: ≧0.30	DS: ≧0.30	DS: ≧0.30


Technical Specifications Safestep 175

## **SARLON** TAKES SOUND REDUCTION TO THE NEXT LEVEL

Reducing noise pollution to a minimum can prevent adverse effects on the human body, such as sleeping disorders, stress, headaches, memory loss, aggressiveness and learning difficulties.


Reducing noise pollution to a minimum can prevent adverse effects on the human body, such as sleeping disorders, stress, headaches, memory loss, aggressiveness and learning difficulties. That's why acoustic performance is essential when designing a building. Acoustic floors are key when it comes to reducing noise in buildings. The floor coverings in the Sarlon acoustic vinyl range have been developed and

tested to maximize impact sound reduction while meeting the needs of heavy traffic commercial areas. To suit all types of applications, our Sarlon acoustic vinyl range offers 2 levels of impact sound reduction: 15dB and 19dB. Sound reduction versus residual indentation Each one of our floor coverings takes 2 key criteria into account: Impact sound reduction & residual indentation.






Sarlon dégradé is the inspiring in colour and design. The fluent colouration from in combination with the design pattern is an unique flooring in the Sarlon range With the 6 different dessins (all in 19 dB) this is truly a unique match. The lighter side of each Dégradé design is perfectly matching and can be combined with a Uni color.




178 Sarlon Dégrade Sarlon Dégrade



15db 423208 | 19dB 433208 15db 420819 | 19dB 430819 These ranges will gives you the option to create floors that will comes to life. With a range of bright colours, any space will become more vibrant and special. Dessins made for movement and colour are in some designs the key elements. Although the pattern can easily be combined with other ranges.




180 Sarlon 181



These clean design designs are the more earth, mineral based colours that would turn any room in a natural and modern look.





The wood is represented with a more classic and a modern oak, giving enough choice for anyone in need of acoustic woods. Linea is a more graphic design of vibrant Zebrano. They come in modern and relevant colours.

Sarlon wood XL modern 15 & 19dB

Sarlon ask 15 & 19dB

Sarlon ask 15 & 19dB


Sarlon ask 15 & 19dB

Sarlon modern 15 & 19dB

Sarlon wood XL modern 15 & 19dB


Sarlon zebrano 15

184 Sarlon Wood Modern XL | Oak | Linea | Zebrano 185



The design in our acoustic range is the right balance between a movement and uniformity; which makes it easy to use. Especially in these 6 modern colours.








186 Sarlon Cement Sarlon Cement

## **sarlon**® abstract wood 19 dB







This graphic wood is unique and our own interpretation with a more black and white approach. This design will give any area a modern natural feeling.


## Technische specificaties: **Sarlon**

	Sarlon 15 dB and 19 dB meet the re-	quirements of EN 14041 and EN 6	51 sarlon 15 dB	sarlon 19 dB	
Ž	Total thickness	EN-ISO 24346	2.6 mm	3.4 mm	
×	Wear layer thickness	EN-ISO 24340	0.70 mm	0.67 mm	
R	Total weight	EN-ISO 23997	2,700 g/m²	2,900 g/m <sup>2</sup>	
١	Impact sound reduction	EN-ISO 717-2	$\Delta L_{\rm w} = 15~{\rm dB}$	$\Delta L_{_{W}} = 19 \text{ dB}$	
	In-room impact noise	NF S 31-074	L <sub>n,e,w</sub> < 65 dB, Class A	L <sub>n,e,w</sub> < 65 dB, Class A	
	Sound absorption	EN-ISO 354 EN-ISO 11654	$\alpha_{_W}=\pm~0,05$	$\alpha_{_{\mathrm{w}}} = \pm 0.05$	
	Residual indentation (Typical value) Requirement	EN-ISO 24343-1	~0.05 mm ≤ 0,20 mm	~0.08 mm ≤ 0,20 mm	
	Slip resistance	DIN 51130	R9	R9	
	Abrasion resistance	EN 660-2	T	T	
	Specifications		EN 651	EN 651	
	Commercial use	EN-ISO 10874	34	34	
îm Å	Light industrial use	EN-ISO 10874	42	42	
	Packaging		Rolls	Rolls	
	Roll length	EN-ISO 24341	25 m	25 m	
	Roll width	EN-ISO 24341	2 m	2 m	
	Castor chair resistance	EN 425 (ISO 4918)	Yes	Yes	
	Furniture leg resistance	EN 424 (ISO 16581)	compliant	compliant	
K 2J,	Dimensional stability Requirement	EN-ISO 23999	< 0.10 % ≤ <i>0.40</i> %	< 0.10 % ≤ 0.40 %	
	Colour fastness to light Requirement	EN ISO 105-B02 - method 3	7 ≥6	7 ≥6	
	Stain resistance	EN-ISO 26987	Good	Good	
	Surface treatment		PUR	PUR	
	Emissions into air : TVOC* at 28 days	EN-ISO 16000-9	< 100 μg/m³	< 20 μg/m³	
			EN 14041 <b>C €</b> 0201819_DOP_306	EN 14041 <b>C E</b> 0200825_DOP_306	
	Compliance EN 14041		Yes	Yes	
Caral	Reaction to fire	EN 13501-1	Bfl - s1 <sup>(2)</sup>	Cfl - s1 (1)	
(25) 20	Slip resistance	EN 13893	Class DS (µ ≥ 0,30)	Class DS (µ ≥ 0,30)	
Ħ	Body voltage	EN 1815	E ≤ 2 kV , Antistatic	E ≤ 2 kV , Antistatic	
	Thermal conductivity	EN 12524 (EN-ISO 10456)	0,25 W/(m.K), suitable for heating floors	0,25 W/(m.K), suitable for heating floors	

 $<sup>^{(1)}</sup>$  Valid on every substrate: wood, non combustible A2 $_{\rm ff}$ -s1 oo A1 $_{\rm ff}$  or on free laying (with SARLIBASETE underlayer)  $^{(2)}$  Valid on non combustible substrate: A2 $_{\rm ff}$ -s1 or A1 $_{\rm ff}$  \* TVOC: total volatile organic compounds

188 Sarlon Abstract Wood 19 dB Technical Specifications Sarlon 189

# COLOREX ESD FLOOR COVERING IS SAFE STAYS SAFE



## **colorex**<sup>®</sup> ESD & cleanroomfloors


Protecting your technology Colorex is an advanced technical flooring system specifically designed to control static discharge in sensitive areas such as cleanrooms, operating theatres and the electronics industry. Not only does Colorex provide an advanced technical solution, it is also aesthetically pleasing, enhancing any commercial interior from industrial to educational establishments.

Providing peace of mind Forbo Flooring Systems is an international market leader with a wealth of experience in providing ESD and clean room flooring with probably the best known brand in the market place - Colorex. You can have peace of mind that Colorex complies to every standard and norm that is required today and likely to be required tomorrow. Environmental credentials We constantly strive to produce sustainable flooring systems that create better environments everywhere. At the same time we help take care of the natural environment through our commitment to sustainable development, responsible raw material procurement and manufacturing processes. For example our Colorex collection contains 15% post industrial recycled content, is manufactured using green electricity and is REACH compliant.

## The 8 benefits of Colorex

Colorex is the ideal flooring system for sectors such as electronics, pharmaceuticals, health, data centres and server rooms.

- Colorex offers peace of mind as it fully complies with all ESD and clean room standards, including the Fraunhofer institute.
- Colorex offers a life time conductivity warranty guaranteeing optimal performance throughout the life of the product
- The dense construction of Colorex provides a porefree surface ensuring the highest hygiene properties
- The low plasticiser content in Colorex tile creates a unique dimensional stability and prevents shrinkage
- The low plasticiser content also ensures extremely low emissions and outgassing making Colorex the right choice for clean rooms
- The surface of Colorex can be fully repaired extending the useful life of the product
- The dense construction of Colorex provides excellent resistance to to heavy loads making it an ideal solution for commercial and industrial environments
- Colorex is available in tile format, a prerequisite for raised access floors found in many commercial environments such as data centres and server rooms.




**ESD-floors** 



Healthcare-flooring



Cleanroom-flooring




Industrial-flooring

## **colorex**® EC plus, basic plus, R11 plus

Colorex Basic Plus is a loose lay floor system with Colorex on top without conductive properties. This ensures all the benefits of Colorex like high density, easy repair and stain resistance. But also combines the benefits of a heavy duty loose lay tile.

## colorex EC plus Highperform



Renovating an industrial floor can be a very costly and labour intensive endeavour. The downtime needed to move or disassemble heavy production equipment and the cost of a complex subfloor renovation can begin to add up before work on installing the new floor has even started. Colorex EC plus is a high performance floor covering system that consists of loose lay tiles. Suitable for applications where expensive preparatory measures and downtimes are not acceptable, it can be installed without any interruptions and is immediately accessible. There's no need for special subfloor treatments or preparations. The tiles connect to each other using a unique dovetailing system that remains hidden. As the tiles have a genuine Colorex surface you can still take advantage of its proven features and benefits.

Functionality: Permantly conductive

**Description:** Permanently conductive floor, connection between

tiles through dovetails and connected to earth with copper strip. Compliant to IEC 61340-4-5 with

appropriate ESD shoes.

**Application areas:** Renovation of ESD facilities, cleanrooms,

pharmaceutical laboratories and production sites. Suitable when down time, damp floors or poor sub

floors are an issue.

## colorex basic plus



Colorex Basic plus is a loose lay floor system with a Colorex surface and limited conductive properties. This range provides all the benefits of Colorex, such as a high density, repairable and chemical resistant surface with the flexibility of a heavy duty loose lay tile.

**Functionality:** Resistant / repairable


**Description:** Excellent chemical resistance. Floor can be repaired

in case of heavy damages.

Application: areas Shops, stores, warehouses. Suitable when down

time, damp floors or poor sub floors are an issue

## colorex R11 plus



The product has enhanced slip resistance, catergorised as, R11 due to its strong surface embossed structure. Only available in colourway 601060.


**Functionality:** Slip resistant to R11

**Description:** Dirt hiding, slip resistant floor.


**Application areas:** Industrial areas, garages, warehouses. Suitable when

down time, damp floors or poor sub floors are an issue

192 Colorex 193



The Colorex collections offers a premium brand of conductive and static dissapative high density dimentional stable tiles. Colorex SD enables safe electrostatic discharge through the entire surface and mass of the tile. The conductive carbon black forms a dense network of tiny black veins. Colorex SD is \*\*permanently static dissipative.



194 Colorex SD/ED Colorex SD/ED 195



## Colorex Basic Plus is a loose lay floor system with Colorex on top without conductive properties. This ensures all the benefits of Colorex like high density, easy repair and stain resistance. But also combines the benefits of a heavy duty loose lay tile.

## Technical specifications: **colorex**®

_	Colorex meets the requirements of EN 649		Colorex SD	Colorex EC	Colorex EC Plus	Colorex Basic Plus	R11 Plus
E CE n	marking	EN 14041	Compliant	Compliant	Compliant	Compliant	Complian
AST	M**	Compliant	Compliant				
Tota	al thickness	ISO 24346 / EN 428	2.0 mm / 3.0 mm*	2.0 mm / 3.0 mm*	10.5 mm	10.5 mm	10.5 mm
Tile	size	EN 427 / ISO 24342	615x615 mm 615x1230 mm*	615x615 mm 615x1230 mm*	608x608 mm	608x608 mm	608x608 m
Com	nmercial very heavy	ISO 10874 / EN 685	34	34	34	34	34
Indu	ustrial heavy	ISO 10874 / EN 685	43	43	43	43	43
Elec	trical resistance	IEC 61340-4-1 EN 1081 (100V) ANSI/ESD 7.1	$10^6 \le R \le 10^8 \Omega$	$5 \times 10^4 \le R \le 10^6 \Omega$	2.5 x 10 <sup>4</sup> ≤ R ≤ 106	n.a.	n.a.
in co	trical resistance ombination with Shoes	IEC 61340-4-5 ESD STM 97.1	n.a.	$R < 3.5 \times 10^7 \Omega$	$R < 3.5 \times 10^7 \Omega$	n.a.	n.a.
Out	gassing	IDEMA M11-99	total < 1 μg/cm²	total < 1 μg/cm²	total < 2 μg/cm²	total < 2 μg/cm²	n.a.
Tota	al TVOC 28 days	AgBB guidelines	25 μg/cm³	25 μg/cm <sup>3</sup>	25 μg/cm³	25 μg/cm³	n.a.
Bact	teriostatic	SNV 195 920	Pass	Pass	Pass	Pass	n.a.
Che	mical resistance	ISO 26787 / EN 423	Excellent	Excellent	Excellent	Excellent	Excellen
Slip	resistance	DIN 51130	R9	R9	R9	R9	R11
Tota	al weight	ISO 23997 / EN 430	3.2 kg/m <sup>2</sup>	3.2 kg/m²	12.4 kg/m <sup>2</sup>	12.4 kg/m²	11.4 kg/n
Dim	nensional stability	ISO 23999 / EN 434	0.05%	0.05%	n.a.	n.a.	n.a.
The	rmal dilatation coef- ent		n.a.	n.a.	0.11 mm/m°C	0.11 mm/m°C	0.11 mm/n
Resi	idual indentation	ISO 24343-1 / EN 433	0.035 mm	0.035 mm	n.a.	n.a.	n.a.
(per	istence to load formance may vary, ject to local conditions)		Powered pallet truck and forklifts: total weight up to 2.5 t withhard wheels and up to 5 t with air tyres. Static loads: 50 kg/cm² - dynamic loads: 90 kg/cm²				
Abra	asion resistance	EN 660-2	Group M	Group M	Group M	Group M	n.a.
Cast	tor chair continuous use	ISO 4918 / EN 425	no effect	no effect	no effect	no effect	n.a.
Ligh	nt fastness	EN ISO 105 B02	≥ 6	≥6	≥6	≥ 6	n.a.
Imp	act sound reduction	EN ISO 140-8	2 dB	2 dB	12 dB	12 dB	12 dB
All C	All Colorex products meet the requirements of EN 14041						E
	ly voltage generation, n appropriate ESD shoes	IEC 61340-4-5 ESD STM97.2 EN 1815	40 V	20 V	20 V	< 2 kV	< 2 kV
Read	ction to fire	EN 13501-1	B <sub>ff</sub> -s1	B <sub>ff</sub> -s1	B <sub>ff</sub> -s1	B <sub>n</sub> -s1	B <sub>ff</sub> -s1
Slip	resistance	EN 13893	DS ≥ μ 0,30	DS ≥ µ 0,30	DS ≥ µ 0,30	DS ≥ μ 0,30	DS ≥ μ 0,5
<u> </u>	rmal conductivity	ISO 10456/EN 12524	0.25 W/(m·K)	0.25 W/(m·K)	0.25 W/(m⋅K)	0.25 W/(m·K)	0.25 W/(m

196 Colorex Plus Technical Specifications Colorex 197

<sup>\*</sup> Available on request \*\* Product also tested to ASTM. Results available on request





# FLOTEX, A UNIQUE FLOOR COVERING

Flotex is neither a true textile, nor is it an resilient and its unique construction succeed in combining the best of both worlds, suitable for use in commercial environments however demanding the conditions.

Approximately 80 million minute nylon 6.6. fibres (flock) are as strong as a bamboo construction, yet creating the comfort of a moss surface. Precision printing technologies used to manufacture Flotex mimic the rich colour pallet that can be found in nature to the smallest detail. Slip resistant in wet and dry conditions (R13), imitating the functions of the Gecko's feet. Like a honey bee collects and distributes pollen on the stems by hovering between flowers, the Flotex surface captures fine dust and allergens from the air and releases this completely during a simple basic cleaning action.

As such Flotex is the high tech textile that offers bionic performance, available in both sheet and tile.

## Fresh air:

- · the nylon fibres capture allergens and fine dust from the air
- · as easy to clean as any resilient floorcovering
- the anti microbial Sanitized® treatment ensures consistent protection against bacteria



# FLOTEX, THE HIGH TECH TEXTILE

Flotex Flocked Flooring is a completely unique textile flooring that combines the hard wearing and durable characteristics of a resilient floor with the quality, warmth and comfort of a carpet.

### **Durable and comfortable**

Discover the toughness and durability of Flotex which comes as a result of the 80 million nylon 6.6. fibres per square metre, while experiencing the quietness and comfort normally only associated with a carpet as a result of the impervious cushioned backing.

## **Quiet yet Hygienic**

The nylon fibres not only perform in sound absorption and comfort, they also capture allergens and fine dust from the air, all of which they effortlessly release in any cleaning action in both dry and wet conditions. Through its construction Flotex is protected against mould and odour's whilst keeping up its appearance, as the floor restores to mint condition after every cleaning action.

## Warm while washable


Simple every day vacuuming removes any dirt or dust trapped in the dense nylon surface. However also steam cleaning or deeper mechanical cleaning can be used after heavy soiling, requiring a minimum of traditional detergents. Simple cleaning action already restores Flotex to its original appearance. The wide array of colours and designs in which Flotex is offered, remain as vibrant and livery as the day the floor was installed.


#### Safe but sound absorbing

Flotex provides both low in-room impact noise performance (class A) as well as good impact sound reduction (>20dB), meaning a quiet room and a quiet building. Flotex also meets the HSE wet and dry slip resistance classifications for use of flat surfaces and ramps.

## Flotex, a choice, not a compromise

Flotex is a high tech textile which brings together the world of resilients and textiles connecting key performance indicators into one single product, that delivers all you can expect from an innovative flooring solution.





## **FLOTEX**

#### 206 flotex colour

Showing three individual designs in a rhapsody of colour that offers you the choice for selection of the detail and nuance that you are looking for.

### 216 flotex° linear

Represents a comprehensive choice of 5 linear designs in various colour ways that suit office environments, but also deliver playful effects for leisure, hospitality or retail spaces.

## 224 flotex\* vision

An overwhelming choice of over 600 digitally printed designs to suit every taste or requirement, right down to a colour on demand option.

#### 228 flotex sottsass

A collection of 4 exquisite designs, created exclusively for Forbo by Italian design studio Sottsass Associati.

### 236 flotex\* planks


Flotex is neither a true textile, nor is it a resilient flooring. Its unique dense fiber construction succeeds in combining the best of both worlds: comfort & resilience. Flotex offers a flooring solution for areas where safety, hygiene and well-being are in high demand.


# IT'S NOT A RESILLIENT BUT PERFORMS LIKE ONE

## flotex<sup>®</sup> colour


Flotex Colour is a collection with 3 designs which together form a rhapsody of colour across a broad spectrum. Ideal for education, health - and age care environments, leisure, retail and other commercial spaces.

Flotex Colour is a comprehensive collection of textile designs that are presented in 3 different allover styles and subtle print nuances: Metro, Calgary and Penang. The Metro Neons add a special twist to this collection. All items are available in sheet or tile.







FLOTEX













































































208 Flotex Metro Flotex Metro 209



Opening up a whole new dimension of design possibilities, the Flotex Metro Neon range offers 8 vibrant colours cleverly designed to work on their own or in conjunction with the standard Metro range. You can use them to create striking breakout areas, cut-outs and borders or delineate walkways and individual zones in open plan spaces.




210 Flotex Metro Neon 211





212 Flotex Calgary 213



Flotex Penang offers a stunning look for any modern environment. Its hint of the wooden planks design provides a quiet neutral floor design.




214 Flotex Penang 215


# **flotex**® linear

Flotex Linear represents a comprehensive choice of 5 linear designs designed to work together or on their own: Integrity<sup>2</sup>, Complexity, Stratus, Cirrus and Pinstripe.

Across the 5 ranges there are sheet and tile options, most of which can be laid in a variety of fitting styles. For everyday installations, Flotex tiles can also be installed using tackifier.










216 Flotex Pinstripe 217



Flotex Complexity is only available in tile format.















Flotex Integrity<sup>2</sup> is only available in tile format.




























Flotex Integrity2 219 218 Flotex Complexity





With Flotex Artline you are able to make borders, creative features and delineators between colour ways or even different designs. Artline is available in 11cm and 22cm widths and matches the base shades of the various Flotex designs.



222 Flotex Artline 223

# THE DIGITAL WORLD OF FLOTEX VISION



# The **flotex** digital library

Like any library the Flotex Digital library gives you an opportunity to browse and wonder about the many opportunities that Flotex digitally printed floor coverings offer to you. We also would like to give you some guidance and offer you a logic design path to the items of your taste or choice.

We have created 6 initial entries to the library, each of them representing a design direction that might suit your taste. In addition to the items in the library there also are additional options for some designs where you can choose your own colour combination. Also there is an opportunity for bespoke, unique designs, they are not part of the library but can discussed with your Forbo sales representative.

The designs in the library will be updated and new items will be added on a regular basis. At this moment the library contains 600 different designs and colour ways.

#### The entries to the library are as follows:



#### Floral

A selection of 8 different floral designs, ranging from abstract, graphic flower motives to romantic images of roses and butterflies or flower designs that fit very well into children's daycare centres. Each of the 8 design types comes in a variety of colour ways.



#### Shape

A collection of organic shapes and motives that result in beautiful all over patterns ranging from contemporary to traditional designs.



#### Linear

8 line or stripe designs with their own characteristics, ranging from plain and simple to very complex and multi-colour.



#### Pattern

The intricate play of networks and patterns that provides textured floors with a clear and non-directional visual. Each design can be chosen in a number of colour ways.



#### lmage


This section of the library contains a wide variety of photographic images that are transferred into interesting theme floors. Grass, sand, water drops, buttons or street maps are amongst the interesting options.



#### Naturals


Floor images that represent materials like wood, stone, ceramics or cork floors. The design technology creates real and life like floors, with a twist for example wood planks that are acoustic and comfortable to walk on.

#### Go online and discover over 600 designs for your floor




# Find your design in 4 easy steps:

- 1. Access www.flotexvision.com
- 2. Choose your main design entry in the library (1 out of 6 entry options)
- 3. Choose the collection you like
- 4. Choose the colour you like... and order your sample online



# View rooms in hundreds of floor designs

Explore online how you can customise your floor designs. Some designs can even be fully matched with your taste or branding colours.



#### Recolour designs

Some designs in the library you can colour as you wish.
The colour bank offered can be used for the background and the pattern.

226 Flotex Digital Library 227


# **flotex**<sup>®</sup> sottsass


At the crossroads of art, design and architecture, the work of Ettore Sottsass represents the birth of non-conformist Italian design, somewhere between the industrial and the experimental. A prominent figure in Italian design since the 1950's, this ingenious free thinker sought to explore every creative avenue with a non-conformist attitude that was both assuming and audacious.


Whether designer, architect, sculptor, artist or photographer, Ettore Sottsass has left his mark and his commitment in his global view of the environment and space, through his sculptures, jewellery, artwork, furniture, and industrial objects. Today, many designers and architects emulate his spiritual heritage, radical in its stance against functionalism.


The exclusive design collaboration with Flotex was borne out of the desire to work with an innovative flooring technology and its precision HD printing brings to life the avant guard designs that clearly carry the Sottsass signature.

There are four designs: Terrazzo, Wool, Bacteria and Kasuri. These designs have features in common: irregular, apparently random and organic forms, and the "optical" features that play with scale. Thanks to the ease of printing, almost every design is possible. The collection is available in a wide range of different colourways and include hot fashion colours in strongly contrasting combinations.











flotex<sup>®</sup> wool




The Wool design implies
the texture and stranded
feel of this natural material,
whilst presenting a strongly
impressionistic effect. Irregular
coloured strands form linear
(and roving) patterning,
reminiscent of Bridget
Riley op-art. When viewed
from a distance this design
dramatically shifts perspective
and redefines the interior space.

FLOTEX

230 Flotex Bacteria Flotex Wool 231

# **flotex**® terrazzo 990701











990806

























Terrazzo is a witty "twist" on the concept of traditional Italian Terrazzo (a poured concrete flooring containing chips of stone, marble or glass with distinctive and irregular pattern when dry and polished); on closer inspection, the "chips" in Terrazzo are revealed as pieces of torn paper – each holds its own story.

Flotex Kasuri 233 232 Flotex Terrazzo

# Technical specifications: **flotex** colour and linear

	Flotex sheet and tile meet the requirem	nents of EN 1307	tile			
	Total thickness	ISO 1765	4.3 mm	5.3 mm		
	Commercial use	EN 685	Class 33 heavy	Class 33 heavy		
	Roll width		2.0 m	-		
	Roll length		30 m	-		
	Tile size	-	50 x 50 cm			
	Quantity of tiles per box	-	12 (3m²)			
	Total weight	ISO 8543	1.8 kg/m²	4.5 kg/m <sup>2</sup>		
K Z	Dimensional stability	ISO 2551 / EN 986	< 0.2%	< 0.2%		
	Abrasion resistance	EN 1307 annex F	> 1000 cycles	> 1000 cycles		
	Castor chair continuous use	EN 985	r = ≥2.4 continuous use	r = ≥2.4 continuous use		
7	Light fastness	EN ISO 105-B02	≥ 6	≥ 6		
98	Slip resistance	UK SRG pendulum	Dry – very low slip risk Wet – low slip risk	Dry – very low slip risk Wet – low slip risk		
	Acoustical	EN-ISO 717-2	Impact sound $\Delta L_{_{\rm W}} = 20~{\rm dB}$	Impact sound $\Delta L_w = 19 \text{ dB}$		
(m)	Acoustical	ISO 354	Sound absorption = 0.10	Sound absorption = 0.10		
	Water tightness	EN 1307 annex G	Pass	Pass		
	Creating better environments					
Ť	Renewable electricity	Flotex is manufactured using	100% electricity made from renewable sources			
3	Recycled content		mately 22% recycled content by weight stely 67% recycled content by weight			
	Back to the Floor	Installation off cuts can be col	lected and recycled via Back to the Floor			
	Ska	Flotex meets the Ska Rating cr	riteria for M12 soft floor coverings in both office and retail	schemes		
LCA	LCA	LCA is a foundation for securir	ng the lowest environmental impact			
	Flotex meets the requirements of EN 1-	4041				
Barst	Reaction to fire	EN 13501	B <sub>ff</sub> - s1	B <sub>ff</sub> - s1		
188°	Slip resistance	EN 13893	DS: ≥ 0.30	DS: ≥ 0.30		
F	Body voltage	ISO 6356	< 2 kV	< 2 kV		
	Thermal conductivity	ISO 8302	0.048 m2 K/W	0.040 m2 K/W		

# Technical specifications: **flotex** vision and sottsass

#### Flotex Naturals, Vision and Sottsass sheet meet the requirements of EN 1307


° ×	Total thickness	ISO 1765	4.3 mm			
	Commercial use	EN 685	Class 33 heavy			
ĵ\$	Roll width	2.0 m				
-\$)	Roll length	30 m				
옥	Total weight	ISO 8543	1.8 kg/m²			
7 Z	Dimensional stability	ISO 2551 / EN 986	< 0.2%			
	Abrasion resistance	EN 1307 annex F	> 1000 cycles			
	Castor chair continuous use	EN 985	r = ≥2.4 continuous use			
7	Light fastness	EN ISO 105-B02	≥6			
S.	Slip resistance	UK SRG pendulum	Dry – very low slip risk Wet – low slip risk			
<u></u>	Acoustical	EN-ISO 717-2	Impact sound $\Delta Lw = 20 \text{ dB}$			
$\langle \langle \langle \langle \langle \rangle \rangle \rangle \rangle$	Acoustical	ISO 354	Sound absorption = 0.10			
R	Water tightness	EN 1307 annex G	Pass			
<b>À</b>	Creating better environments					
$\checkmark$	Renewable electricity	Flotex is manufactured using 100% electricity m	nade from renewable sources			
3	Recycled content	Flotex sheet contains approximately 22% recycled content by weight				
	Back to the Floor	Installation off cuts can be collected and recycle	ed via Back to the Floor			
	Ska	Flotex meets the Ska Rating criteria for M12 soft floor coverings in both office and retail schemes				
.CA	LCA	LCA is a foundation for securing the lowest envi	ironmental impact			
	Flotex meets the requirements of EN 14041					
(N)	Reaction to fire	EN 13501	B <sub>n</sub> - s1			
Ş	Slip resistance	EN 13893	D5: ≥ 0.30			
<b>1</b>	Body voltage	ISO 6356	< 2 kV			
<u>=</u>	Thermal conductivity	ISO 8302	0.048 m² K/W			
_						


234 Technical Specifications Flotex 235

# **flotex**<sup>®</sup> planks

#### Flotex planks: sophistication & style

Flotex is neither a true textile, nor is it a resilient flooring. Its unique dense fiber construction succeeds in combining the best of both worlds: comfort & resilience. Flotex offers a flooring solution for areas where safety, hygiene and wellbeing are in high demand.






Flotex Seagrass planks combine lasting performance with sophistication & style. Because of its natural and warm feel, the Seagrass design goes down well in homely environments like housing for the aged or care facilities. You can create stunning floor designs with Flotex Seagrass, whether it is laid as herringbone, brick or basketweave. Sophisticated in 1 colour, or stylish with 2 or more.




236 Flotex Planks Flotex Planks



Flotex Triad planks have an exciting graphical design and offer you the creative freedom to mix and match, combining colours and installation methods easily to customize your floor. It looks great laid brick, herringbone or basket weave and has a range of exciting colourways with highlight options and a unique embossed version to add more texture and tactility to your floor.



238 Flotex Triad 239



**flotex**® box cross


With Flotex Box Cross planks you can transform a space. With Box Cross every plank is unique. It contains a pattern





240 Flotex Box Cross

145002 | 145005 | 145007 | 145009 | 145010 | 145014



A wood pattern on a textile floor? You will be amazed on how it looks, feels and performs. A nice warm underfoot, no noise of ticking shoes and no wear. The ideal floor covering in offices, hotel rooms and elderly care locations. It is a mindset change. Get the looks of a real wooden floor with the advantages of comfortable textile flooring. All installation patterns are possible for Flotex Wood, use your imagination!




creative design combinations in every way possible. Flotex Lava offers you a large flooring choice with 18 colourways ranging from subtle shades to vibrant brights. Madeira Pinatubo

Flotex Lava planks are all about texture and colour. They give you the opportunity to define spaces, highlight areas and explore

242 Flotex Wood
Flotex Lava 243

flotex<sup>®</sup> lava




Our designers have created 6 floor designs inspired by famous Van Gogh paintings. A tribute to Van Gogh, made possible by the unique characteristics of Flotex flocked flooring.


Thanks to the high density of the fibres, Flotex is ideal to print digitally and this allows for picturesque floors. Flotex is strong and durable, so despite intensive use the prints will remain beautiful over time.














980212 | grey

Through focusing on texture and line, Tibor's detailed photograph of straw inspired this famous pattern from the Fotexur range. The photograph was taken in the spring sunshine to give the image greater definition and the design deliberately highlights the tonal contrast between light and dark. Co-ordinating broad stripes available in two colourways.


Flotex Tibor Ziggurat 245 244 Flotex Van Gogh





Tibor often incorporated richlytextured 'fancy yarns' into his weaves to create tactile effects. For this pattern Tibor photographed a sheer fabric made from slub yarn. The uniformity of the grid contrasts pleasingly with the randomness of the loops. Co-ordinating stripes available in two colourways.



980408 | stone








980412 | raspberry stripe





The natural world provided a great source of inspiration for Tibor and he photographed it extensively. This pattern depicts the granular composition of rocks and pebbles.

246 Flotex Tibor Mosaic Flotex Tibor Mosaic




This ingenious Tibor pattern has two distinct layers: a fine mesh in the background, overlaid with a fragmented larger scale-grid. Structured yet informal, its subtle textures create a highly effective low-key flooring design.










980712 | clay





Although this pattern resembles marble, it was actually inspired by a photograph of cracked mud in the riverbed next to Tibor's Clifford Mill. One of his most famous Fotexur designs, it was originally used for a woven carpet called Padua, so it is particularly apt that it is now being used for decorative flooring once again. The majority of colourways work in pairs as positive and negative variations.

248 Flotex Tibor Tessello Flotex Tibor Onyx 249



and woven fabrics. This pattern was inspired by a photograph of one of his celebrated Deep Texture weaves, in which irregular slubby yarns were used to create tactile fabrics with textural variety and depth.







980610 | cornflower



980609 | stone



980605 | grey

980601 | pewter

Like all Tibor's Fotexur patterns, the starting point for this design was a crisp black and white photograph taken by the designer himself. The image, recording the rough striated bark of an oak tree, is ruggedly textural, providing the perfect foil for varied coloured overlays.


250 Flotex Tibor Tweedy Flotex Tibor Arbor 251

253



This design, derived from a photograph of an atomic structure, symbolises the period known as the Atomic Age. Part of the Colatomic range, launched in 1960, it reflects Tibor's dual interests in colour and texture. It also reflects the impact of Abstract Expressionism, which was very popular in the art world at the time.

252 Flotex Tibor Atomic





980802 | saffron

# Technical specifications: **flotex** tibor

#### Flotex Tibor sheet meet the requirements of EN 1307

• ×	Total thickness	ISO 1765	4.3 mm			
- min	Commercial use	EN 685	Class 33 heavy			
÷	Roll width	2.0 m				
$\stackrel{\circ}{\Longleftrightarrow}$	Roll length	30 m				
ري	Total weight	ISO 8543	1.8 kg/m²			
(K 2)	Dimensional stability	ISO 2551 / EN 986	< 0.2%			
	Abrasion resistance	EN 1307 annex F	> 1000 cycles			
	Castor chair continuous use	EN 985	r = ≥2.4 continuous use			
R	Light fastness	EN ISO 105-B02	≥6			
36	Slip resistance	UK SRG pendulum	Dry – very low slip risk Wet – low slip risk			
١	Acoustical	EN-ISO 717-2	Impact sound $\Delta Lw = 20 \text{ dB}$			
(m)	Acoustical	ISO 354	Sound absorption = 0.10			
	Water tightness	EN 1307 annex G	Pass			
	Creating better environments					
1	Renewable electricity	Flotex is manufactured using 100% electricity m	ade from renewable sources			
3	Recycled content	Flotex sheet contains approximately 22% recycle	ed content by weight			
	Back to the Floor	Installation off cuts can be collected and recycle	d via Back to the Floor			
	Ska	Flotex meets the Ska Rating criteria for M12 soft	floor coverings in both office and retail schemes			
LCA	LCA	LCA is a foundation for securing the lowest envir	ronmental impact			
	Flotex meets the requirements of EN 14041					
Birst	Reaction to fire	EN 13501	B <sub>n</sub> - s1			
93	Slip resistance	EN 13893	DS: ≥ 0.30			
7	Body voltage	ISO 6356	< 2 kV			
	Thermal conductivity	ISO 8302 0.048 m² K/W				
_						





# **UNIQUE COLLECTIONS WITH** SPECIFIC PROPERTIES

#### **Carpet tiles**

Today's office environments frequently accommodate layout changes, which is why carpet tiles, with their ability to quickly adapt to new requirements, can reduce the cost of reorganisation. Where carpet tiles are installed, telephone, network, electrical and other underfloor systems remain easily accessible for these changes to be made.

#### The carpet tile constructions

Our collections consist of different constructions, each with its own specific characteristics. The variety of tufting - the making of loops of yarn on a ground cloth - creates different constructions.



Carpet tiles with a loop pile construction are designed to maintain their good looks in the most demanding heavy traffic areas of buildings such as corridors and reception areas. There are various styles of loop pile products in the Tessera range covering level loop and multi-height loop pile constructions.



#### Cut and loop

Cut and loop pile tiles feature a clever hybrid construction that offers all the robustness of a conventional loop pile product but with the superior aesthetics and more luxurious feel of a cut pile carpet tile.



Fusion bonding is a sophisticated method of carpet tile manufacture where individual yarn pile is bonded onto the backing material to make an extremely dense and luxurious product. A high proportion of the yarn is in the wear surface providing a beautiful, rich velour carpet tile which gives an excellent broadloom appearance.

#### Westbond

The Westbond product range is synonymous with total flexibility and sophistication. Blending yarns to order and manufacturing premium quality fusion bonded tiles in an almost infinite number of colourways, with no minimum order quantity, Westbond allows customers to take control of the process of designing luxurious, bespoke carpet tiles with exceptionally heavy pile weights for the most prestigious installations.

The robust, hard-wearing properties of Needlefelt make it ideal for installations that meet high traffic or in those areas where chairs with castors are likely to be in use, such as in offices, administrative premises and retail establishments.



#### **CARPET TILES & NEEDLEFELT**

#### 260 tessera

Tessera offers stylish, sustainable and hardwearing tufted carpettiles in various pile constructions and textures, delivering specific performance and aesthetic benefits.

#### 262 tessera loop pile

Carpet tiles with a loop pile construction are designed to maintain their good looks in the most demanding heavy traffic areas of buildings, even in corridors and reception areas. There are various styles of loop pile floors in the Tessera range, covering level loop and designer loop constructions

#### 276 tessera random lay. batchless

A random lay tile is cleverly designed so that it may be laid in any direction to produce a totally individual installation. Different production consignments of 'batchless' tiles can be used together without the usual risk of visible batch variation.

#### 278 tessera cut & loop pile

Cut & loop pile carpet tiles feature a clever hybrid construction that offers all the robustness of a conventional loop pile floor covering but with the superior aesthetics and more luxurious feel of a cut pile carpet tile. Tessera offers cut & loop pile tiles in various aesthetic styles, for all types of environments.

#### 282 tessera cut pile

Softer and more luxurious than loop pile, cut pile carpet tiles are ideal for boardrooms and meeting rooms in addition to general office environments. Tessera offers one tufted cut pile tile range to meet different aesthetic requirements.

#### 290 westbond

Westbond fusion bonded carpet tiles offer infinite colour possibilities and exceptional quality and luxury from as little as 1m<sup>2</sup>.

#### **NEEDLEFELT**

#### 302 showtime

This fine fibre needlefelt collection offers a large choice of uni colours which coordinate perfectly with the printed designs allowing the demarcation of individual spaces and the creation of different moods.

#### 324 forte

Forte is the premium product in our needlefelt range, offering the maximum feeling of comfort that comes with a fibre weight of approximately 750 g/m². Forte is an impressive premium product.

#### 328 markant

Markant is a high-quality, coarse-texture covering made of 100% polyamide fibres, equipped with all the characteristics required for hard-wearing performance in frequently used places. Markant comes with a fibre weight of approximately 600 g/m².

# **TESSERA** ENORMOUS DESIGN **POSSIBILITIES**

#### **TESSERA & WESTBOND CARPET TILES**

Forbo carpet tiles are renowned for their aesthetic styling and outstanding performance in the most demanding heavy traffic environments. Side by side these three long established reputable brands offer specifiers and their clients an unrivalled carpet tile offer to meet every possible design brief.

#### **Carpet tiles**

Carpet tiles are renowned for their aesthetic styling and outstanding performance in the most demanding heavy traffic environments. Forbo Flooring offers a wide portfolio of carpet tile ranges, providing an extensive choice of design, colour, installation options and price points.

#### Tessera carpet tiles

- Colour co-ordinated for maximum design flexibility
- Quicker to install than broadloom carpet
- Installation wastage is reduced
- Damaged or soiled tiles can be replaced
- Wear rotation to extend flooring lifespan
- Renovation with minimal disruption - Compatibility with entrance systems

#### Materials used:



Basis, Format and Apex 640 are manufactured from 100% Aquafil solution-dyed nylon yarn, renowned for its low dust and dirt penetration and superior colour fastness. Accordingly, Apex 640



Inline is produced with 100% Universal polyamide. The use of high lustre Antron® 'metallic' yarn in Helix gives a restrained reflective quality to this distinctive multi-height loop pile tile



Designed for heavy contract installations and constructed using regenerated solution dyed ECONYL® polyamide, Create Space 1 carpet tiles are not only tough and durable but also respond to globally increasing environmental concerns. Up to 100% of the yarn (average 86% across the colour range) is regenerated from post-consumer and post-industrial waste streams including old carpets and discarded fishing nets.

#### Installationmethodes









1500



Atrium is a heavy contract carpet tile at a very affordable price, providing an excellent choice for any office environment. A structured loop pile tile manufactured from 100% polyamide, this great all rounder offers outstanding wear performance and appearance retention, keeping its good looks year after year. Atrium comes with a broad palette of 24 bold colourways, providing an excellent choice for any office environment.



Arran's natural, almost 'artisan' appearance belies the complexity of its multi-height textured loop pile design and the state of the art manufacturing technology behind it. Using CMC Infinity machinery Forbo's designers have developed a carpet tile with unashamedly irregular peaks and furrows which broadlooms beautifully to deliver an alluringly tactile linear design offering real warmth.

tessera® arran

loop pile



262 Tessera Atrium Tessera Atrium



Barcode challenges the uniformity and rigidity of conventional linear low level loop pile tiles and, with its confident bands of contrasting colours in varying widths, delivers a more eclectic and exuberant look that is right on trend for today's commercial environments.


Suitable for every type of commercial installation, Tessera Basis fits throughout the building, wherever an attractive and hardwearing modular floorcovering is required. Available in 18 semi-plain colourways, Basis offers an exceptionally diverse palette with classic and contemporary shades which fit beautifully with any office interior.
















































264 Tessera Barcode Tessera Basis 265




With a distinctive textured construction and a broad colour palette of 18 contemporary and commercially attractive tonal shades, Format has taken low loop pile tiles into a new dimension. This hardwearing heavy contract carpet tile, manufactured using new high tech tufting machines combines rich texture with densely packed low loops for superior aesthetic appeal and real added value. A universally attractive carpet tile suitable for heavy traffic environments in all types of commercial premises, Format boasts a high castor chair rating, making it an ideal and cost-effective solution for busy offices large and small.






An exceptionally flexible range of 18 commercial colourways, Create Space 1 is suitable for any commercial spaces, large or small. Styled for today's interiors, Create Space 1 lends itself to single colourway installations, feature area designs and bespoke creative schemes.




266 Tessera Format Tessera Format





Featuring a versatile geometric stripe design and a contemporary palette of 15 colourways, Create Space 2 adds stylish and creative interest to any size of flooring scheme.

Create Space 2 carpet tiles are designed to provide the maximum flexibility in any installation as they can be fitted in a variety of styles including broadloom, nondirectional (reduces installation waste to less than 2%), tessellated or half drop. Each creates a very modern and individual aesthetic.









2811 | quartz







2809 | cinnabar



tessera® helix

loop pile



803 | clay

804 | taupe




















268 Tessera Create Space 2 Tessera Helix 269

# tessera<sup>®</sup> inline

loop pile





of linear design. Featuring rich, differential texture. Inline provides a strong directional pattern, randomly interspersed with patches of tonal relief. This 'broken linearity' and combination of high and low level loops, delivers a visually interesting backdrop for any commercial interior design scheme. The forgiving design masks tile edges resulting in a broadloom appearance when laid in monolithic fashion.






























The rich undulating texture of this luxurious carpet tile designed for high end commercial interiors and hospitality environments is perfectly captured by the name Rippleweave2. Taking state-of-the-art Infinity CMC tufting technology into previously uncharted waters, Tessera has created a sophisticated textured loop pile carpet tile that flows across the floor delivering an unmistakable look of opulence and a superior level of underfoot comfort.





270 Tessera Inline Tessera Rippleweave2 271


One of a new generation of cleverly textured loop pile tiles from Tessera, Inline adds a completely new twist to the concept








1714 | crater







19 tonal colourways and is suitable for broadloom, tessellated or quarter turn installation. Weave is made from 100% Econyl solution dyed nylon 6 ensuring that the product retains its appearance throughout the lifespan of the floor.

**ECONYL**®

2008 | forrest trail 2012 | flight transfer

2000 | space quest

2004 | pivotal movement









in nature. Inspired by crystalline structures, the fractal shapes fade in and out creating appealing contemporary floor spaces.



2013 | ocean cruise




2014 | skyfall





2015 | arctic voyage

272 Tessera Weave Tessera Diffusion 273



Featuring a contemporary palette of 32 colours with 8 co-ordinated stripes, our Tessera Layout and Outline carpet tiles offer numerous possibilities for creative inspiration in any flooring scheme.


The dynamic colour palette of **Layout** is hugely versatile featuring a comprehensive choice of modern neutrals in combination with diverse and directional brighter shades.

Colours can be used independently or in combination to achieve a myriad of interior styles.

**Outline** is a subtly textured striped loop pile carpet tile with each colourway perfectly matched to 2 Layout colours. Combinations of Outline and Layout allow complete freedom of expression creating connections, highlights and transitions enhancing any style of scheme.



274 Tessera Layout & Outline 275



952 | bone

963 | obsidian

955 | grit

life and excitement to interior floor spaces of any scale, from the narrowest corridors to the most expansive open plan environments. The random nature of the design in modular form creates contemporary floorspace environments which are modern and distinctive yet commercially attractive and highly accessible. Circulate is offered in a range of eight fresh colourways, with options available to suit all types of commercial interiors. The collection is complemented by the addition of 16 Westbond N9000 co-ordinates which offer the opportunity to enhance meeting, break-out or feature areas further.



1600

1600 | turbine




1605 | centrifuge















954 | woodash 953 | canyon 965 | ruby

















276 Tessera Circulate Tessera Mix 277



Alignment is a sophisticated and cleverly textured cut and loop carpet tile designed to complement the most contemporary commercial interiors. Multi-height loops give this distinctive floor covering a bold directional theme which is tempered by the introduction of intersecting random blocks of rich cut pile.

The result is a highly effective broadloom appearance and a unique linear style, equally suited to open plan interiors and more modest enclosed spaces alike.




204 | horizon

203 | cyclone




















1903 | white spruce

tonal progression of diffused shades ranging from pale to very dark.

tessera® contour

cut & loop pile





1906 | rising ash

The controlled geometric background of Tessera Contour is heavily influenced by repeated shapes in

architecture and urban settings. The structure is relieved and broken by a more softly striated cut pile

overlay to reflect the diverse human and natural elements found in these landscapes. The palette is a




1902 | neutral buff






208 | nucleus 214 | nocturn







278 Tessera Alignment Tessera Contour 279



280 Tessera Create Space 3



Acrobat combines the sheer convenience, practicality and hardwearing features of a heavy contract carpet tile with the stunning appearance and tactile benefits of a traditional cut pile carpet.

Constructed from Invista Antron polyamide 6.6 yarn, with its generous pile weight and cut pile tufted construction, Acrobat offers superior underfoot comfort and a touch of



282 Tessera Acrobat 283



# Technical specifications: **tessera**®

Tessera meets the requirements of EN-ISO 1307

			Atrium	Tessera Arran	Tessera Barcode	Tessera Basis	Tessera Format	Tessera Create Space 1			
	Description		Tufted loop pile carpet tile	Tufted multi-height loop pile carpet tile	Tufted low level loop pile carpet tile	Tufted level loop pile carpet tile	Tufted multi-height loop pile carpet tile	Tufted low level loop pi carpet tile			
$\bigoplus$	Dimensions		50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm			
× ^	Total thickness		6.9mm ± 10%	7.0mm ± 10%	6.0mm ± 10%	5.7mm ± 10%	5.8mm ± 10%	5.5mm ± 10%			
	Pile height		3.5mm ± 0.5mm	4.0mm ± 0.5mm	3.0mm ± 0.5mm	2.8mm ± 0.5mm	3.1mm ± 0.5mm	2.7mm ± 0.5mm			
	Collection size		24 colourways   5m² per box	18 colourways   4m² per box	17 colourways   4m² per box	44 colourways   5m² per box	13 colourways   5m² per box	17 colourways   5m² per box			
	Application	EN 1307	-	Class	33, Suitable for any type	of heavy contract applic	ation				
	Pile composition		100% Aquafil 'Alto' polyamide	100% Invista Antron® Lumena poly- amide 6.6	100% Aquafill polyamide 6	100% Aquafil polyamide 6	100% Aquafil polyamide 6	100% Aquafil ECONYL Alto Chroma regenera ted polyamide 6			
	Dye method		100% piece dyed	100% solution dyed	100% solution dyed	100% space dyed	80% solution dyed, 20% space dyed	100% solution dyed			
	Stitch density		104,000 per m <sup>2</sup> ± 10%	202,960 per m <sup>2</sup> ± 10%	169,420 per m <sup>2</sup> ± 10%	200,940 per m <sup>2</sup> ± 10%	252,520 per m <sup>2</sup> ± 10%	245,440 per m² ± 10%			
	Pile weight			950 gsm ± 10%	580 gsm ± 10%	520 gsm ± 10%	525 gsm ± 10%	570 gsm ± 10%			
R	Total weight			4,465 gsm ± 10%	3,895 gsm ± 10%	3,835 gsm ± 10%	4,040 gsm ± 10%	4,085 gsm ± 10%			
	Primary backing	mary backing Polyester/Nylon									
	Secondary backing	ing Modified bitumen and polyester fleece. Also available in SOFTbac® secondary backing									
	Castor chair use	BS EN 985:2001	Minimum R value: ≥2.4								
$\overline{\gamma}$	Light fastness	BS EN ISO 105 B02	≥5		≥5	≥5	≥5	≥5			
K Z	Dimensional stability	BS EN 986			≤0.2	2%					
<u></u>	Impact sound reduction	ISO 10140-3 (ΔL <sub>w</sub> )			22dB	22dB	22dB	21dB			
	Creating Better Enviro	nments									
<b>a</b>	Renewable Electricity All Tessera carpet tiles are manufactured using 100% electricity made from renewable sources										
$\tilde{\prec}$	Recycled Content				Contains over 50% recyc	cled content by weight					
1` ?}	Indoor Air Quality	Tessera meets 01350 Indoor Air Quality standard									
	Ska	Tessera meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes									
٦	Guarantee	Tessera carpet tiles are guaranteed for 10 years under heavy contract conditions (15 years guaranteed with SOFTbac®) provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force									
	Installation method		Broadloom (monolithic), quarter turn or tessellated	Monolithic, quarter turn or tessellated	Brick, quarter turn, tessellated or quarter-brick	Monolithic, quarte	er turn or tessellated	Monolithic, quarter turn or tessellated			
	Tessera carpet tiles meet the requirements of EN 14041										
	Reaction to fire	EN 13501-1			B <sub>fi</sub> -	s1					
			D5: ≥0.30								
	Slip resistance	EN 13893			DS: ≥	0.30					

Shades may vary from batch to batch and should be checked before installation. Except for Tessera Mix, batches should not be mixed in the same location.

# CARPET TILES & NEEDLEFELT

# Technical specifications: **tessera**®

#### Tessera meets the requirements of EN-ISO 1307


			Tessera Create Space 2	Tessera Helix	Tessera Inline	Tessera Rippleweave	Tessera Weave	Tessera Diffusion	Tessera Layout	Tessera Outline	
Descript	ion			Tufted multi-height loop pile carpet tile	Tufted textured loop pile carpet tile	Tufted multi-height loop pile carpet tile	Tufted mul-pile height loop carpet tile	Tufted multi-height loop pile carpet tile	Tufted low loop pile carpet tile	Tufted low loop pile carpet tile	
Dimensi	ons		50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	
Total thic	ckness		5.7mm ± 10%	6.9mm ± 10%	6.5mm ± 10%	7.5mm ± 10%	7.0mm ± 10%	6.5mm ± 10%	5.8mm ± 10%	5.8mm ± 10%	
Pile heig	ht		3.1mm ± 0.5mm	3.9mm ± 0.5mm	3.9mm ± 0.5mm	4.3mm ± 0.5mm	3.5mm ± 0.5mm	3.7mm ± 0.5mm	2.9mm ± 0.5mm	2.9mm ± 0.5mm	
Collection	on size		10 colourways   5m² per box	11 colourways   4m² per box	7 colourways   4m² per box	7 colourways   4m² per box	19 colourways   4m² per box	15 colourways   4m² per box	30 colourways   5m² per box	8 colourways   5m² per box	
Applicati	ion	EN 1307			Class 33,	Suitable for any type	of heavy contract ap	pplication			
Pile com	position		100% Aquafil ECONYL®/Alto Chroma regenerated polyamide 6	100% Invista Antron® Lumena polyamide 6.6	100% polyamide 6	100% Invista Antron® Lumena polyamide 6.6	100% ECONYL® regenerated poly- amide 6	100% Universal Fibers™ Refresh™ polyamide 6.6	100% polyamide 6	100% polyamide 6	
Dye met	hod		100% solution dyed	100% solution dyed	100% solution dyed	100% solution dyed	100% solution dyed	100% solution dyed	100% solution dyed	100% solution dyed	
Stitch de	ensity		245,440 per m <sup>2</sup> ± 10%	219,480 per m² ± 10%	198,374 per m <sup>2</sup> ± 10%	160,480 per m <sup>2</sup> ± 10%	179,664 per m <sup>2</sup> ± 10%	217,120 per m <sup>2</sup> ± 10%	193,060 per m² ± 10%	193,060 per m <sup>2</sup> ± 10%	
Pile weig	jht		570 gsm ± 10%	740 gsm ± 10%	605 gsm ± 10%	950 gsm ± 10%	660 gsm ± 10%	570 gsm ± 10%	580 gsm ± 10%	580 gsm ± 10%	
Total we	ight		4,085 gsm ± 10%	4,255 gsm ± 10%	4,120 gsm ± 10%	4,465 gsm ± 10%	4,155 gsm ± 10%	4,085 gsm ± 10%	3,895 gsm ± 10%	3,895 gsm ± 10%	
Primary	backing					Polyeste	er/Nylon				
Seconda	ry backing	Modified bitumen and polyester fleece. Also available in SOFTbac® secondary backing									
Castor ch	nair use	BS EN 985:2001	Minimum R value: ≥2.4								
Light fas	tness	BS EN ISO 105 B02	≥5	≥5	≥5	≥5	≥5	≥5	≥6	≥6	
Dimension stability	onal	BS EN 986				≤0.	2%				
Impact s reductio		ISO 10140-3 (ΔL <sub>w</sub> )	23dB	21dB	25dB	27dB		22dB	27dB	27dB	
Creating	Better Envi	ronments									
Renewal				All Te	ssera carpet tiles are	manufactured using	100% electricity mad	de from renewable so	ources		
Recycled	Content				Cc	ontains over 50% recy	cled content by wei	ght			
Indoor A	ndoor Air Quality Tessera meets 01350 Indoor Air Quality standard										
Ska			Tessera meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes								
Guarante	ee		Tessera carpet tiles are guaranteed for 10 years under heavy contract conditions (15 years guaranteed with SOFTbac*) provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force								
Installati	on method		Monolithic, quarter turn, tessellated, half drop or non- directional	Quarter turn or tessellated		Brick, quarter turn or		Monolithic guarter	Manalithic brick	Brick, tessellated, quarter turn & quarter brick	
Tessera	carpet tiles	s meet the requ	irements of EN 1404	1						EN 14041	
Reaction	to fire	EN 13501-1				B <sub>n</sub>	-s1				
Slip resis	tance	EN 13893				DS: ≥	≥0.30				
Electrica	l resistance	BS ISO 10965 & EN1815	<1 x	10° Ω: Static dissipati	ve. Body voltage: Pas	ss (< 2kV). Lifetime pro	otection through the	use of permanent ar	nti-static yarn and bac	king	

# Technical specifications: **tessera**®

#### Tessera meets the requirements of EN-ISO 1307

			Tessera Circulate	Tessera Mix	Tessera Align- ment	Tessera Contour	Tessera Create Space 3	Tessera Ethos	Tessera Acrobat
D	escription		Tufted multi-height loop pile carpet tile, Random lay. batchless	Tufted multi-height loop pile carpet tile, Random lay. batchless	Tufted multi-height cut and loop pile carpet tile	Tufted multi-height cut and loop pile carpet tile	Tufted multi-pile height cut and loop pile carpet tile	Tufted cut and loop pile carpet tile	Tufted cut pile carpe tile
<b>⊕</b> D	imensions		50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm	50cm x 50cm
To	otal thickness		6.5mm ± 10%	5.9mm ± 10%	6.2mm ± 10%	6.6mm ± 10%	5.7mm ± 10%	6.4mm ± 10%	8.0mm ± 10%
Pi	ile height		3.7mm ± 0.5mm	3.1mm ± 0.5mm	3.5mm ± 0.5mm	3.5mm ± 0.5mm	3.1mm ± 0.5mm	3.3mm ± 0.5mm	5.0mm ± 0.5mm
	ollection size		8 colourways   4m² per box	15 colourways   5m <sup>2</sup> per box	23 colourways   4m² per box	10 colourways   4m² per box	10 colourways   4m² per box	12 colourways   4m² per box	31 colourways   5m per box
A A	pplication	EN 1307		Class 3	3, Suitable for any type	of heavy contract app	lication	·	Class 32. Suitable fo any type of general contract application
Pi	ile composition		100% Universal Fibers <sup>sM</sup> Refresh <sup>™</sup> polyamide 6.6	100% Invista Antron® Lumena polyamide 6.6	100% Invista Antron® Lumena polyamide 6.6	100% Universal Fibers™ Refresh™ polyamide 6.6	100% Aquafil ECONYL®/Alto Chroma regenerated polyamide 6	100% Aquafil Alto Chroma polyamide 6	100% Antron® poly- amide 6.6
D	ye method		100% solution dyed	100% solution dyed	100% solution dyed	100% solution dyed	100% solution dyed	100% solution dyed	100% piece dyed
St	titch density		254,880 per m <sup>2</sup> ± 10%	200,600 per m² ± 10%	217,488 per m² ± 10%	255,053 per m <sup>2</sup> ± 10%	236,000 per m <sup>2</sup> ± 10%	202,960 per m <sup>2</sup> ± 10%	181,102 per m² ± 109
Pi	ile weight		520 gsm ± 10%	650 gsm ± 10%	700 gsm ± 10%	580 gsm ± 10%	595 gsm ± 10%	755 gsm ± 10%	1,050 gsm ± 10%
To	otal weight		4,035 gsm ± 10%	4,165 gsm ± 10%	4,195 gsm ± 10%	4,095 gsm ± 10%	4,110 gsm ± 10%	4,270 gsm ± 10%	4,650 gsm ± 10%
Pr	rimary backing					Polyester/Nylon			
Se	econdary backing			Modified bitumen a	nd polyester fleece. Als	o available in SOFTbac	secondary backing		Modified bitumen an polyester fleece.
G C	astor chair use	BS EN 985:2001			Minimum R value: ≥2.4	ļ			
∏ ∏Li	ight fastness	BS EN ISO 105 B02	≥5	≥5	≥5	≥5	≥5	≥6	≥5
Z N D	imensional stability	BS EN 986				≤0.2%			
	mpact sound eduction	ISO 10140-3 (ΔL_)	22dB	24dB	23dB	23dB	23dB	23dB	n/a
- - - - -	reating Better Envir	onments							
Re	enewable Electricity	,	A	ll Tessera carpet tiles a	re manufactured using	100% electricity made	from renewable source	es	Contains 10% recycle
Re	ecycled Content			(	Contains over 50% recy	cled content by weigh	t		n/a
n In	Indoor Air Quality Tessera meets 01350 Indoor Air Quality standard						n/a		
SI	Ska Tessera meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes						es	7 years under genera contract conditions	
G	Guarantee  Tessera carpet tiles are guaranteed for 10 years under heavy contract conditions (15 years guaranteed with SOFTbac*) provided that sionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements curren								
In	nstallation method		Random	Random	Monolithic, quarter turn or tessellated	Monolithic, quarter turn, tessellated, half drop or non- directional	Monolithic, quarter turn, tessellated, half drop or non- directional	Monolithic, quarter turn or tessellated	Monolithic, quarter turn or tessellated
Te	essera carpet tiles	meet the require	ements of EN 14041						EN 140
Re	eaction to fire	EN 13501-1				B <sub>ff</sub> -s1			
SI	lip resistance	EN 13893				DS: ≥0.30			
<u></u> _	lectrical resistance	BS ISO 10965 & EN1815	<1 x 10° Ω:	Static dissipative, Bod	y voltage: Pass (< 2kV).	Lifetime protection th	rough the use of perma	anent anti-static varn a	nd backing

Technical Specifications Tessera 287



Following on from the success of our Tessera Layout & Outline  $50 \times 50$  carpet tiles, we've extended the range with  $100 \times 25$  cm planks to create even more possibilities for stunning floor designs. The collection consists of 14 sophisticated uni colours and 4 linear designs that offer endless possibilities to mix & match.



288 Tessera Planks 289

# WESTBOND SOPHISTICATED FLEXIBILITY

### Let the world inspire your creativity.

Realise it with Westbond.

Westbond carpet tiles are synonymous with total flexibility and sophistication.

Blending yarns to order and manufacturing premium quality fusion bonded tiles in an almost infinite number of colourways, with no minimum order quantity. Westbond allows customers to take control of the process of designing luxurious, bespoke carpet tiles with exceptionally heavy pile weights for the most prestigious installations.



Fusion bonding is a sophisticated method of carpet tile manufacture where individual yarn pile is bonded onto the backing material to make an extremely dense and luxurious product.

Each tuft is individual and a high proportion of the yarn is in the wear surface providing a beautiful, rich velour carpet tile which gives an excellent broadloom appearance.

### westbond ibond

The Westbond Ibond Naturals colour range is available in a variety of qualities including polyamide or wool, and pile weights up to 2400 g/m2.

### westbond flex

Westbond Flex carpet tiles are the ideal solution for those seeking a truly individual look to the floor. Simply create your own Westbond Flex carpet tile by selecting up to 4 colours from the Westbond Ibond colour palette, or a colour you've created, and within

2 working days we'll send you a 'pom' that offers a realistic impression of the finished carpet tile. To create your own Flex combination, you can use our online Westbond Flex Creator WESTBOND FLEX CREATOR To stimulate your imagination, we have made a core collection of 30 Flex combinations, which are shown below.

### westbond natural

Westbond Natural is a unique collection of commercial carpet tiles containing pure & natural undyed British wool. The range is the perfect answer to today's ecological concerns. The carpet tile backing minimises environmental impact through its use of up to 74% recycled materials and wool is a sustainable, natural and renewable resource.

290 Westbond 291

# westbond® naturals



# westbond<sup>®</sup> reds



9389 putty

292 Westbond Naturals Westbond Reds 293

9842 creme caramel



# westbond<sup>®</sup> greens




# westbond® blues




9418 pearlblue

294 Westbond Greens
Westbond Greens


9327 capriblue







Westbond Flex carpet tiles are the ideal solution for those seeking a truly individual look to the floor. Simply create your own Westbond Flex carpet tile by selecting up to 4 colours from the Westbond Ibond colour palette, or a colour you've created, and within 2 working days we'll send you a 'pom' that offers a realistic impression of the finished carpet tile. To create your own Flex combination, you can use our online Westbond Flex Creator WESTBOND FLEX CREATOR To stimulate your imagination, we have made a core collection of 30 Flex combinations, which are shown below.








NF92078 | goldcup



Westbond Flex 297 296 Westbond Flex




Westbond Natural is a unique collection of commercial carpet tiles containing pure & natural undyed British wool. The range is the perfect answer to today's ecological concerns. The carpet tile backing minimises environmental impact through its use of up to 74% recycled materials and wool is a sustainable, natural and renewable resource.



W12921U | tussock







## Technical specifications: **westbond**®

Westbond meets the requirements of EN-ISO 1307

			EN 14041
	Installation method		Monolithic, tessellated or quarter turn
	Guarantee		Provided that they have been professionally fitted by a recognised contractor and regularly maintain in accordance with the Forbo requirements currently in force
	Ska		Meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes  10 years under heavy contract conditions
٦			
₩ W	Indoor Air Quality		Westbond meets 01350 Indoor Air Quality standard
ا ک	Recycled Content		Contains 43% recycled content by weight
$\tilde{\langle}$	Creating Better Environments  Renewable Electricity		All Tessera and Westbond carpet tiles are manufactured using 100% electricity made from renewable so
	Impact sound reduction	ISO 10140-3 (ΔL <sub>w</sub> )	27dB
0	Dimensional stability	BS EN 986	≤0.2%
(A)	Light fastness	BS EN ISO 105 B02	≥5
<u>a</u>	Castor chair use	BS EN 985:2001	Minimum R value: ≥2.4
	Secondary backing		PVC incorporating at least 70% pre-consumer recycled content
_	Primary backing		n/a
ال	Total weight		4,000 gsm ± 10%
શ્	Pile weight		950 gsm ± 10%
	Stitch density		272,000 per m² ± 10%
	Dye method		Hank dyed
	Pile composition		100% polyamide 6.6
M.	Application	EN 1307	Class 33, Suitable for any type of heavy contract application
	Collection size		Any colour from 1 m²   4,5 m² per box
	Pile height		5.0mm ± 0mm/-0.5mm
^	Total thickness		8.1mm ± 10%
$\Rightarrow$	Dimensions		50cm x 50cm
	Description		Fusion bonded cut pile carpet tile

 $Shades \ may \ vary \ from \ batch \ to \ batch \ and \ should \ be \ checked \ before \ installation. \ Except \ for \ Tessera \ Circulate, \ batches \ should \ not \ be \ mixed \ in \ the \ same \ location.$ 

W12789U | manx W12795U | dorset Technical Spcifications Westbond 299 298 Westbond Natural

# ROBUST AND INADVERTENTLY NEEDLEFELT

### Needlefelt

The robust, hard-wearing properties of Needlefelt make it ideal for installations that meet high traffic or in those areas where chairs with castors are likely to be in use, such as in offices, administrative premises and retail establishments.

The textile look and typical range of colouring blend harmoniously and inadvertently into any interior-design scheme. Needlefelt carpet often provides a cost-efficient alternative to conventional broadloom carpeting in heavily-used areas that require a practical and durable textiletype floor covering. Forbo uses high quality polyamide fibres and a full latex impregnation for all its needlefelt carpets.

### showtime®

This fine fibre needlefelt collection offers a large choice of uni colours which coordinate perfectly with the printed designs allowing the demarcation of individual spaces and the creation of different moods.

### forte

Forte is the premium product in our needlefelt range, offering the maximum feeling of comfort that comes with a fibre weight of approximately 750 g/m². Forte is an impressive premium product. It is available in a range of 24 attractive colours. A very dense texture, with more than three million needle punches per square metre, guarantees a combination of attractive looks and hard-wearing performance for use in highly-frequented areas.

### markant

Markant is a high-quality, coarse-texture covering made of 100% polyamide fibres, equipped with all the characteristics required for hard-wearing performance in frequently used places. Markant comes with a fibre weight of approximately 600 g/m2.

### akzent

Akzent is the value-for-money alternative and the only collection in the range that is made of a combination of 80% polyamide and 20% polypropylene fibres (fibre weight of 500 g/m2), which is nevertheless no lightweight when it comes to hard-wearing performance.

CARPET

# showtime nuance 900202


This fine fibre needlefelt collection offers a large choice of uni colours which coordinate perfectly with the printed designs allowing the demarcation of individual spaces and the creation of different moods.



Olive | 900208



Perle | 900200
















Anthracite | 900212






Rose indien | 900206








Rouge | 900216

Violet | 900227

# **showtime** experience wonderlab

Showtime experience Wonderlab consists out of a range of four individual graphic geometric designs that offer elegance to the room with a classic textile look and feel.




302 Showtime Nuance Showtime Experience Wonderlab 303

wonderlab<sub>02</sub>




wonderlab 01

304 Wonderlab 01



wonderlab 03




wonderlab<sub>04</sub>

Wonderlab 04 307

# CARPET TILES & NEEDLEFELT

# **showtime** experience metropolis

Showtime Experience Metropolis consists out of a range of four individual graphic modern rythmic designs that refer to the city landscape experience. Showtime Experience Metropolis print designs are available in a large range of colours.



# metropolis<sub>01</sub>

918216




308 Showtime Experience Metropolis 01 309

Metropolis 03 311

# metropolis 02

# metropolis 03












310 Metropolis 02



# **showtime** experience ecosystems


Showtime Experience Ecosystems consists out of a range of four individual graphic nature designs that hint to the great outdoors with a playful twist. The four Ecosystems prints are available in a wide choice of colours






Showtime Experience Ecosystems 313

# ecosystems 01






Ecosystems 02 315

# ecosystems 03

# ecosystems 04








316 Ecosystems 03 Ecosystems 04 317


# CARPET TILES & NEEDLEFELT

# **showtime** experience héritage

Showtime Experience Heritage consists out of a range of four individual graphic classic textile designs that refer to the classic textile experience. Showtime Experience Heritage print designs are available in a wide range of colours.









318 Showtime Experience Héritage 01 319


# héritage 02




# héritage 03



Héritage 03 321




Héritage 04





Forte is the premium product in our needlefelt range, offering the maximum feeling of comfort that comes with a fibre weight of approximately 750 g/m². Forte is an impressive premium product. It is available in a range of 24 attractive colours. A very dense texture, with more than three million needle punches per square metre, guarantees a combination of attractive looks and hard-wearing performance for use in highly-frequented areas.

324 Forte 325




Forte Grafic Reef provides the basis for this newly-developed print design, with colour contrasts that nevertheless work together in total harmony. The range of attractive colour shades shares the common element of varying grey background mottling.





The fine print design of this member of the Forte range accents the delicate texture of its textile-like finish.
Forte Graphic Rice is available in 8 attractive colour shades.

326 Forte Graphic Reef
Forte Graphic Reef





This modern print design, of Markant Graphic Rice as the basis, helps accentuate an interior designer's pure lines. The classical "box" pattern makes it especially suitable for use on large floor-areas.

328 Markant Markant Graphic City 329




Akzent is the value-for-money alternative and the only collection in the range that is made of a combination of 80% polyamide and 20% polypropylene fibres (fibre weight of 500 g/m²), which is nevertheless no lightweight when it comes to hard-wearing performance.


















# Technical specifications: needlefelt and showtime

			Forte / Forte Graphic	Markant / Markant Graphic	Akzent	Showtime nuance	Showtime experience
÷ ×	Total thickness	ISO 1765	ca. 6.5 mm	ca. 5.5 mm	ca. 5.0 mm	3.8 mm	3.8 mm
	Thickness of wear layer					1.3 mm	1.3 mm
	Residential application					Class 23	Class 23
<i></i>	Commercial application	EN 1470	class 33	class 33	class 33	Class 32	Class 32
	Roll length		ca. 30 m	ca. 30 m	ca. 30 m	40 m	40 m
	Roll width		200 cm	200 cm	200 cm	200 cm	200 cm
	Installation method	NF 262				Rolls laid in same direction	Design dependent, refer to brochure
	Fibre composition of the wear layer		100% PA	100% PA	80% PA / 20% PP	100% polyamide	100% polyamide
	Backing		100% recycled PES	100% recycled PES	100% recycled PES	100% recycled polyester	100% recycled polyester
	Construction		fully impregnated	fully impregnated	fully impregnated	Fully impregnated	Fully impregnated
R	Fibre weight of the wear layer		ca. 750 g/m²	ca. 600 g/m <sup>2</sup>	ca. 500 g/m²		
	Total weight	ISO 8543	ca. 1,5 Kg/m²	ca. 1,2 Kg/m²	ca. 1,0 Kg/m²	750 g/m²	750 g/m²
	Antistatic properties ISO 10965		≤ 10 <sup>7</sup> Ω	≤ 10 <sup>7</sup> Ω	≤ 10 <sup>7</sup> Ω		
٩	Impact sound reduction	ISO 140-8	22 dB	21 dB	20 dB	$\Delta Lw = 19 dB$	$\Delta Lw = 19 dB$
(A)	Sound absorption	EN ISO 354	$\alpha w = 0,20 (H)$	$\alpha w = 0.20 (H)$	$\alpha w = 0.20 (H)$	aw = 0,15 (H)	$\alpha w = 0.15 (H)$
	Suitability for castor chairs	EN 985	Yes	Yes	Yes	Yes	Yes
	Indoor air emissions : TVOC* at 28 days	EN ISO 16000				< 100 μg/m³	< 100 μg/m³
	Requirement for class A+	(ISO 10580)				$< 1000 \ \mu g/m^3$	$< 1000  \mu g/m^3$
	GuT label					Application underway	Application underway
	REACH - European regulation	1907/2006/CE				compliant (1)	compliant (1)
	(Regulation, Evaluation, Authorisation & Restriction of CHemicals)	3-					
	Light fastness	ISO 105/B02	> 6	> 6	> 6		
	Water fastness	ISO 105/E01	> 3-4	> 3-4	> 3-4		
	Rubbing fastness wet	ISO 105-X12	>3	> 3	> 3		
	Rubbing fastness dry	ISO 105-X12	> 3-4	> 3-4	> 3-4		
	-						

All Needlefelt products meet th	All Needlefelt products meet the requirements of EN 14041										
Reaction to fire	EN 13501-1	B <sub>n</sub> -s1	B <sub>n</sub> -s1	B <sub>f</sub> -s1	C <sub>fl</sub> - s1 (2)	C <sub>ff</sub> - s1 <sup>(2)</sup>					
Slip resistance	EN 13893	DS ≥ 0.30	DS ≥ 0.30	DS ≥ 0.30	DS (µ ≥ 0,30)	DS (µ ≥ 0,30)					
Personal charging	ISO 6356	≤ 2 kV	≤ 2 kV	≤ 2 kV	$E \le 2 \text{ kV}$ , Antistatic	$E \le 2 \text{ kV}$ , Antistatic					
Heat transmission resistance	ISO 8302	0,07 m <sup>2</sup> K/W	0,06 m <sup>2</sup> K/W	0,05 m <sup>2</sup> K/W	0,06 W/(m.K), suitable for use with underfloor heating	0,06 W/(m.K), suitable for use with underfloor heating					

<sup>(1)</sup> Showtime products do not contain substances from the candidate list (substances of very high concern) published by the ECHA within the REACH regulation framework (2) When laid on a wood substrate. Achieves A1fl or A2fl when laid on concrete \*TVOC: Total volatile organic compounds: quantity emitted to indoor air

330 Akzent Technical Specifications Needlefelt and Showtime 331





### **ENTRANCE FLOORING SYSTEMS**


Ever thought about slowing down or stop to wipe your feet when you walk into a store, an office, hospital clinic or school, or other public space? Chances are you don't. Most of us just stride on in, which is why it's important to install an entrance flooring product to keep the world outside, outside.

### 350 **nuway**

No entrance area is too big, too small or too awkwardly shaped for a Nuway rigid matting system. No level of traffic is too heavy and no level of soiling is too high. Whatever type of rigid engineered system you have in mind, Nuway's experienced sales and technical teams can guide you to a solution tailored perfectly to your needs.

# CORAL ENTRANCE FLOORING SYSTEMS THE FIRST STEPS IN PROTECTING YOUR BUILDING

# ENTRANCE FLOORING STARTS OUTSIDE AND BRINGS YOU INSIDE



If you really want to keep your building clean and safe, it's not enough to just put down an entrance mat in front of the door. Creating a good entrance flooring system means thinking about footfall - the number of people walking in and out in a given period - and walking routes

(the directions they take once inside) and applying that information in the design of the entrance area. One of the best ways to plan an entrance flooring system is to think in terms of applications. The table opposite is designed to help you select which Coral entrance product best meets your needs.

# Application 1: Outside use that information in the design of ance area. One of the best ways to entrance flooring system is to think Application 1: Outside use Any matting placed outside the building entrance creates the first line of defense against feet-borne soil by scraping the

entrance creates the first line of defense against feet-borne soil by scraping the coarsest dirt from the soles of shoes before they cross the threshold.

### Application 2: Inside use


Moving inside, the next line of defense, is used to remove moisture and finer dirt particles from all feet entering the building.

### Application 3: Other circulation areas

Other areas in the building also suffer from soil and moisture; reception areas, corridors, walkways to other parts of the building, elevators, staircase exits, etc. All these areas are prone to residual soiling and will benefit highly from a purposely designed Coral entrance floor to absorb this soiling.

Aŗ	plication	moisture removal	dirt removal	ECO	
coral <sup>®</sup> grip MD	1 + 2	●000	••••	●000	х
coral <sup>®</sup> grip HD	1 + 2	•000	••••	●000	х
coral®duo	2	••••	••••	●●00	Х
coral®brush	2+3	••••	•••0	•••0	Х
<b>coral</b> ®welcome	2+3	••••	•••0	••••	Х
coral <sup>®</sup> classic	2+3	••••	••00	••00	Х
coral <sup>®</sup> luxe	2+3	••••	••00	●000	-
coral®logo	2+3	•••0	••00	●000	-

336 Coral Coral 337




6 metres of Coral can stop up to 95% of dirt and moisture entering a building.

Coral Luxe is particularly designed to enhance the aesthetic appeal of entrance lobbies, corridors and reception areas. Because of its luxurious look and feel, this deceptive soil and moisture barrier blends particularly well with other carpeted areas of the building.

- Rich and elegant appearance
- Comfortable and soft feel
- Offers effective moisture and soil absorption
- Dries quickly for maximum functionality
- $\bullet$  Complies with the highest fire class standard:  $B_{\rm f}$ -s1
- Suitable for light industrial use and private applications
- Ideal for circulation areas
- Produced with phthalate free technology




Coral Luxe 339







With its contemporary linear design and rich, deep pile, Coral Welcome packs the style and aesthetic appeal of a luxury carpet. But Coral Welcome is more than just a fabulous looking floor covering – it's an environmentally advanced one as well. The secret lies in its use of Econyl® yarn, which is made from regenerated industrial and postconsumer waste. In the creation of Econyl® products our supplier is waste positive, which means the amount of waste removed from the earth is greater than the amount of waste resulting from production. On top of that, the production has a low environmental impact because we limit the consumption of natural resources and energy to a minimum.


- Made with Econyl® 100% regenerated yarns
- Primary backing made from recycled PET bottles
- Produced with phthalate free technology
- Keeps out moisture and dirt
- $\cdot$  Complies with the highest fire class standard:  $\mathrm{B_{f}}$ -s1
- Suitable for the toughest commercial use
- Ideal for inside entrance and circulation areas











340 Coral Welcome







Many Coral ranges are available with an FR version for fire sensitive areas.

Coral Brush is suitable for all types of entrance areas, absorbing moisture and removing dry soiling as the weather demands. Created around simple, solid colours, this collection works well with any interior design, serving as eye-catcher or self-effacing support for the rest of the floor design.

- Good all-rounder that keeps out moisture and dirt
- Made with Econyl® 100%-regenerated yarns
- Appealing colours complement every floor
- $\cdot$  Complies with the highest fire class standard:  $\mathrm{B_{fl}}$ -s1
- ${\:\raisebox{3.5pt}{\text{\circle*{1.5}}}}$  Suitable for the toughest commercial use
- Ideal for inside entrance and circulation areas
- Produced with phthalate free technology





Coral Brush 343











Research shows that taking just two steps on Coral Classic's moisture absorbing yarns is enough to absorb half of the foot-borne moisture that would otherwise be carried inside on the soles of people's shoes. A few steps more and your feet are as dry as possible. This has clear benefits. First, the floor coverings further inside stay cleaner, longer. Second, resilient floors like vinyl, linoleum, wood and concrete are less likely to become slippery and dangerous.

- Maximum moisture absorption and scrapes off dirt
- Choice of attractive contemporary colours
- Maximum colour fastness
- Complies with the highest fire class standard: B<sub>n</sub>-s1
- Suitable for the heaviest commercial and light industrial use
- Ideal for inside entrance and circulation areas
- Produced with phthalate free technology






4759 | old rose












4764 | taupe

4750 | warm black

4753 | bright red


344 Coral Classic Coral Classic 345





Coral Duo is the go-to solution when you need maximum dirt removal, unrivalled dirt retention and exceptional moisture absorption all in the short distance of just a couple of paces. Research has shown that Coral Duo retains 10% more dirt in the first few metres than any other textile entrance flooring solution on the market.

- Excellent solution for every entrance
- Made for 75% with Econyl® 100% regenerated yarns
- Produced with phthalate free technology
- Unbeatable performance on both moisture and dirt
- $\bullet$  Complies with the highest fire class standard:  $B_{\rm ff}$ -s1
- Suitable for the toughest commercial use
- Ideal for inside entrances with limited entrance floor space










9725 | cafe bahia





9724 | cafe supreme





9714 | Sicilian sand

9727 | Volga blue

346 Coral Duo Coral Duo 347



6145

Don't start your entrance floor protection inside, start outside – by scraping off the largest soil particles before your visitors even cross the threshold. Coral Grip is a versatile, non-woven clean off barrier mat for outdoor and indoor use that comes in medium duty (MD) and heavy duty (HD) formats.

Standard Coral Grip has an open, non-backed, pervious structure, though it can also be manufactured with an Everfort vinyl backing to make it impervious.

• Contains granulates for maximum non-slip performance


6943 6923 wine

- Cleans off the worst dirt before it can get inside
- Helps protect an inviting interior design street-side
- Suitable for the heaviest commercial use
- Ideal for outside and inside entrance





Coral Grip 349



# 22 37 16 23 25 33 45 29 28

Forbo has the capability to offer a bespoke print or cut-out design service that can be tailored to your precise design specification, offering individuality and a unique point of difference. Our Coral Logo collection offers a wide range of bright attractive colours. Depending on the colours and design of your corporate identity, you can choose between a printed mat or one with a cut inset logo. The Coral Logo collection is designed to the same standards as all other Coral products, which means it will retain its looks whilst keeping out dirt and moist for years to come.

# Technical specifications **COral**® logo

			Coral Logo	o (43xx)*		
Ŷ	Total thickness	ISO 1765	Approx.	8 mm		
Å	Wear classification	EN 1307	31, comme	rcial light		
	Available sizes		Standard mat sizes (sizes with edges)	Special sizes (sizes without edges)		
٥٧	(all sizes are approx.) Roll sizes with 2.5 cm edge each side		55 x 90 cm	any width, any length		
	euge each side		105 x 155 cm, 105 x 300 cm			
	Mat sizes with 2.5 cm edge all sides		155 x 197 cm, 155 x 300 cm			
	euge all sides		197 x 197 cm, 197 x 300 cm	up to 192 cm wide		
	Colour fastness ratings:					
R	Light	EN ISO 105/B02	>5			
	Rubbing	EN ISO 105/X12	4-5	;		
	Water	EN ISO 105/E01	4-5	;		
	Manufacturing method/type		Tufted, 1/8	d, 1/8" cut-pile		
	Designs		Hi-definition c	ustom print		
	Pile material		100% High Twist N	lylon polyamide		
	Tuft base		Non-woven	polyester		
	Backing phthalate free vinyl		EVERFOR	T vinyl		
3	Total weight	ISO 8543	Approx. 3350	0 gram/m²		
	Pile installation weight	ISO 8543	Approx. 680	gram/m²		
Š	Pile thickness	ISO 1766	Approx.	5 mm		
	Pile density	ISO 8543	0.113 gra	m/cm³		
	Number of tufts	ISO 1763	Approx. 110	0.000/m²		
	Comfort class	EN 1307	LCZ	2		
	Other remarks		Dirt absorption ca Moisture absorption Production tolerance of	capacity: 3-4 l/m <sup>2</sup>		



### Printed logo mat

Fire behaviour

Slip resistance

Personal charging

- Excellent visual quality and bright, attractive colours
- Perfect for complicated designs featuring multiple colours
- Choose from any of the colours shown plus Pantone and RAL colour matching
- Stays flat on the floor, causing less trips, due to heavy vinyl backing

All Coral products meet the requirements of EN 14041, excluding loose-laid mats and rugs

EN 13501-1

- Long lasting and high resistance to sun light
- Excellent performance in removing dirt from your shoes
- Produced with phthalate free technology

### Cut inset logo mat

- Ideal for extreme traffic conditions and maximum functional performance
- Choose from any colour from the standard Forbo Coral collection for the base background and logo colours

B<sub>ff</sub>-s1

< 2 kV

 $\epsilon$ 

- Excellent performance due to use of Coral quality products
- Easy to combine as inlay in larger Coral installations
- Produced with phthalate free technology

350 Coral Logo Coral Logo 351

# Technical specifications **COral**®

			Coral Lu	xe (29xx)	Coral Welco	ome (32xx)*	Coral Brush (57xx)*		
<u> </u>	Total thickness	ISO 1765	Approx.	8.5 mm	Approx	c. 9 mm	Approx	c. 9 mm	
Ŷ	Total thickness Coral tiles	ISO 1765		-		-	Approx	c. 9 mm	
Å W	Wear classification	EN 1307	31, comm	31, commercial light		ercial heavy	33, commercial heavy		
	Colours			5	8	3	1	8	
_			Rolls	Mats	Rolls	Mats	Rolls	Mats	
	Available sizes (all sizes are approx.) Roll sizes with 2.5 cm		105 cm	105 x 155 cm	205 cm	105 x 155 cm	105 cm	55 x 90 cm	
	edge each side		205 cm	135 x 205 cm			155 cm	90 x 155 cm	
<b>∃</b> §	Mat sizes with 2.5 cm edge all sides		Roll lengths approx. 20 m		Dell langths		205 cm	135 x 205 cm	
			ирргох. 20 пг		Roll lengths approx. 27.5 m		Roll lengths approx. 27.5 m	205 x 300 cm	
	Available in tiles	le in tiles No		o	N	lo	yes - size: 50 x 50 cm (12 tiles in a box = $3 \text{ m}^2$ )		
	Colour fastness ratings:								
泵	Light	EN ISO 105/B02		3	7	7	>5		
	Rubbing	EN ISO 105/X12	4-5		5	5	5		
	Water	EN ISO 105/E01	4-5		4	-5	4-	-5	
	Seawater	EN ISO 105/E02	4	-5	4	-5	4-	-5	
	Waterstains	EN 1307 annex G		5		5	5	5	
	Shampoo	BS 1006	4		4	-5	4-	-5	
	Organic solvents	EN ISO 105/X05			4	-5	4-5		
	Manufacturing method/type		Tufted, 5/3	Tufted, 5/32" cut-pile		32" cut-pile	Tufted, 5/32" cut-pile		
	Designs		Plain o	olored	Multi-colo	ured linear	Plain designed/ coloured blend		
	Pile material		100% po	olyamide	100% regenerate	ed Econyl® Nylon	100% regenerated Econyl® Nylon		
	Tuft base		Non-wove	Non-woven polyester		woven PET/Econyl®	Non-woven polyester		
	Backing phthalate free vinyl		EVERFO	RT vinyl	EVERFO	RT vinyl	EVERFO	RT vinyl	
R	Total weight	ISO 8543	Approx. 41	00 gram/m²	Approx. 39	50 gram/m²	Approx. 405	50 gram/m²	
S	Total weight Coral tiles	ISO 8543		-		-	Approx. 470	00 gram/m²	
	Pile installation weight	ISO 8543	Approx. 10	00 gram/m²	Approx. 75	0 gram/m²	Approx. 92	0 gram/m²	
Ă	Pile thickness	ISO 1766	Approx	5.5 mm	Approx.	6.3 mm	Approx	c. 7 mm	
	Pile density	ISO 8543	0.140 gı	ram/cm³	0.111 gr	ram/cm³	0.105 gr	ram/cm³	
	Number of tufts	ISO 1763	Approx.	93000/m²	Approx. 7	79300/m²	Approx. 5	58000/m <sup>2</sup>	
	Comfort class	EN 1307	LC	<b>23</b>	LC	<b>-</b> 3	LC	3	
	All Coral products meet the r	equirements of EN 1	4041, excluding loos	e-laid mats and rugs	;				
∭ Bπ-s1	Fire behaviour	EN 13501-1	B <sub>fi</sub>	-s1	B <sub>n</sub>	-s1	B <sub>n</sub>	-s1	
92)	Slip resistance	EN 13893	D	S	D	S	D	S	
72	Personal charging	ISO 6356	< 2	kV	< 2	kV	< 2	kV	

<sup>\*</sup> Also available with fire retardant backing.

# Technical specifications **COral**®

Coral Classic (47xx)*		Coral Duo	(97xx)*	Coral Grip	HD (61xx)	Coral Grip MD (69xx)			
Approx.	. 9 mm	Approx.	9 mm	With backing a Open structure		With backing a Open structure a			
Approx.	. 9 mm	-		-	-	- 33, commercial heavy			
33, commer	rcial heavy	33, commer	rcial heavy	33, comme	rcial heavy				
13		8		5	5	5			
Rolls Mats		Rolls	Rolls Mats		Mats	Rolls	Mats		
105 cm	55 x 90 cm	205 cm	No mats	open 122 cm, with backing 127 cm	60 x 90 cm	open 122 cm, with backing 127 cm	60 x 90 cm		
155 cm	90 x 155 cm				Mats only with		Mats only with		
205 cm	135 x 205 cm	Roll lengths			open structure		open structure		
Roll lengths approx. 27.5 m	205 x 300 cm	approx. 27.5 m		Roll lengths approx. 10 m		Roll lengths approx. 15 m			
yes - size: 50 (12 tiles in a b		No	)	N	0	No	)		
7-8		>5	5	7	,	7-8			
4-5	5	4-:	5	4-	5	4-5			
4-5	5	4-:	5	5	5	5			
4-5	5	5	5		5	5			
4-5	5	5		5	5	5			
4-5	5	4-:	5	5	5	5			
4-5	5	4-:	5	4-	5	4-5			
Tufted, 5/32	2" cut-pile	Tufted, 5/3	2" cut-pile	Non Woven scraping	Non Woven scraping mat with embossing Non		craping mat		
Multi coloured des	signed/coloured	ribb	ribbed		interconnected aments	3-dimensional ir monofila			
100% polyamide-B	BCF solution dyed		100% polyamide-BCF, where 75% is regenerated Econyl® Nylon		vinyl n dyed	100% Solution			
Non-woven	polyester	Non-woven	polyester						
EVERFOR	RT vinyl	EVERFOR	RT vinyl	Open structure or with E	EVERFORT vinyl backing	Open structure or with E	VERFORT vinyl backii		
Approx. 4000	0 gram/m²	Approx. 380	0 gram/m²	With backing: appi Open structure: app		With backing: appro			
Approx. 470	0 gram/m²	-		-		-			
Approx. 870	0 gram/m²	Approx. 670	) gram/m²						
Approx. 7 mm		Approx.	6 mm						
0.100 gra	am/cm <sup>3</sup>	0.095 gra	am/cm³						
Approx. 61	1500/m²	Approx. 3	2000/m²						
LC	3	LC	2						
							<b>C</b> (		
Bs	x1	B	:1	With back	ina: R -s1	With backi			

B <sub>n</sub> -s1	B <sub>n</sub> -s1	With backing: B <sub>ff</sub> -s1	With backing: B <sub>f</sub> -s1
DS	DS	DS: μ0,78	DS: μ0,82
< 2 kV	< 2 kV	< 2 kV	< 2 kV

352 Technical Specifications Coral Technical Specifications Coral



## Nuway

The recognised market leader in engineered entrance flooring systems, Nuway matting has been efficiently removing dirt, grit and moisture from the soles of shoes and tyre treads in heavily trafficked entrance areas for over eighty years. No entrance area is too big, too small or too awkwardly shaped for a Nuway matting system. No level of traffic or soiling is too high. Whatever type of rigid engineered system you have in mind, Nuway's experienced sales and technical teams can guide you to a solution tailored perfectly to your needs.

The tough and durable rigid engineered mats can be integrated seamlessly into your interior design scheme and once installed appear to be part of the fabric of your building. They can be supplied to meet every conceivable aesthetic and technical specification, with an almost infinite range of designs, colour ways, sizes and constructions available for internal and external entrance areas. They can also be teamed up perfectly with Coral textile entrance matting to create stunning fully integrated, colour coordinated entrance areas.

# **nuway**® tuftiguard

At the heart of the Nuway range, the standard Tuftiguard entrance mat is the most widely used rigid engineered entrance mat. It has the durability, strength and structural integrity to deliver excellent performance and appearance retention in very heavy traffic locations and where high levels of soil have to be removed from the soles of shoes and wheeltreads.

Each Tuftiguard mat is assembled according to the client's individual specification using their chosen combinations of aluminium (100% recycled), brass or PVC scraper bars, and buffed or unbuffed prime

rubber and polyamide fibre composite wiper strips. These wiper strips and PVC scraper bars are offered in a wide range of colours, enabling the Tuftiguard mat to be perfectly coordinated with a Coral clean off system or other surrounding floor finishes. The wiper bars and scraper strips are assembled in an open or closed construction with high tensile electro galvanised steel wire linkages running through the components to give the mat its structural integrity and superior load bearing capacity.

### Linkages:

High tensile steel linkages give the system an engineered, constructional integrity.



### Scraper bars:

As the name suggests scraper bars literally scrape soil from the traffic crossing the entrance system.



### Wiper stripes:

Wiper strips can be specified in both single and double format. Double offers twice the wiping area to increase moisture absorption over a shorter distance.

### Reversible:

Tuftiguard are double sided mats which can be reversible, effectively doubling their lifespan.



## **Options available:**

### Height

Standard Tuftiguard mats incorporating aluminium and PVC scraper bars are available in 12mm and 17mm heights to suit the size of the matwell. Mats incorporating brass scraper bars are available in 17mm height only.

### Wiper strips

Tuftiguard wiper strips can be specified in both single and double format. Double format offers twin wiper strips to increase moisture absorption over a shorter distance and enables more colour to be used to reflect the interior colour scheme. If the Nuway entrance system extends less than 3m into the building, we recommend that an entrance with double wiper strips is used.

### **Closed construction**

A closed construction is suitable for both interior and transitional areas. Soil removed from shoes and wheel-treads is collected within the mat itself. The gapless nature of the closed construction allows for maximum use of coloured wiper strips to complement interior design schemes.


### Open construction


An open construction provides more storage capacity for wet and dry soil and is therefore particularly suitable for external use. Removed particles and moisture can fall through the open sections in the mat to be collected in the matwell.

### Mix and match


As Tuftiguard is produced in modules to individual specifications, a single section of matting may contain any number of different combinations, including open and closed constructions, single and double wiper bars, unbuffed and buffed finishes, featuring any combination of colours.











A closed construction is suitable for both interior and transitional areas. Soil removed from shoes and wheeltreads is collected within the mat itself.



An open construction provides more storage capacity for wet and dry soil. Removed particles and moisture can fall through the open sections in the mat.

Nuway Tuftiguard 357

## **nuway**® tuftiguard HD

Nuway Tuftiguard HD is the ideal matting solution for all internal and external entrance areas where heavy duty loads and intense pedestrian and/or wheeled traffic need to be catered for.

Matting placed outside will defend against soil and the coarsest of foot-borne dirt. Inside it will defend against foot-borne moisture and finer dirt particles.

The location, type and level of traffic affects the choice of product. Tuftiguard HD is suitable for very heavy and intense traffic areas and for entrances with high point loads up to 900kg/cm<sup>2</sup>

Nuway Tuftiguard HD is double sided which means it can be reversible where the configuration of the entrance mat allows, effectively doubling its lifespan.

Nuway Tuftiguard HD offers products suitable for both internal and external entrances.

# **nuway**® flameguard

Suitable for internal and external use, Nuway flameguard is specifically designed for particularly fire sensitive areas such as underground railway stations. Nuway Flameguard is suitable for both internal and external entrance applications. Flameguard is double sided which means it can be reversible where the configuration of the entrance mat allows, effectively doubling it's lifespan.





### Linkages:

High tensile steel linkages give the system an engineered, constructional integrity.



### Scraper bars:

As the name suggests scraper bars literally scrape soil from the traffic crossing the entrance system.



### Wiper strips:

Prime rubber and polyamide fibre composite provides optimum removal of dirt and moisture.

### Reversable:

Nuway Tuftiguard HD is double sided which means it can be reversible where the configuration of the entrance mat allows, effectively doubling its lifespan.



# **nuway**<sup>®</sup>grid

Nuway Grid is a contemporary alternative to Nuway Tuftiguard and is ideal solution in very heavy traffic entrance areas where aesthetic considerations are paramount. Grid is also easy to shape on site.

Every Nuway Grid mat features 100% recycled, extruded aluminium interlocking carrier sections for durability, with infill strips joined together by rubber double connecting strips. The aluminium sections have a low-lustre anodised finish to comply with DDA requirements. Grid is constructed to spread heavy loads and to offer long lasting effective performance in demanding locations. The carrier sections can be coupled with infill materials providing maximum design flexibility, allowing beautifully colour co-ordinated entrance areas to be created with primary and secondary entrance matting products that are perfectly matched. These materials include strips of textile infill in 13 different colourways drawn from the Coral classic and brush activ ranges. Other textile inserts from the Coral range are available to special order. Rubber inlays are also available, which allow grid mats to be used outside.

	Nuway Grid rubber	Nuway Grid textiel				
Indoor application	1					
Outdoor application		/				
Wiper strip	Black rubber	Coral Classic, Brush Pure				
Scraper bars	Aluminium	and brass				
Aluminium height	12 mm or 17 mm	12 mm or 17 mm				
Inlay height	14 mm – 23 mm	14 mm – 23 mm				
Mat construction	Clo	sed				
Dirt removal	1	1				
Moisture absorption		/				
Guarentee	5 year					
Level of traffic	Very I	neavy				

### Component structure:

### Inserts:

Extensive choice of standard inserts includes a selection of thirteen different textile inserts from the Coral classic, brush activ and burford ranges and rubber inserts (for exterior entrances).

### Carrier section:

Low lustre anodised finish complies with DDA requirements as detailed in the Equality Act. Patented crimping action firmly secures textile or rubber insert within the carrier section.


### Considerations

As with all aluminium matting systems of this type, in very brightly lit entrances, the strong contrast between a light aluminium carrier and a dark coloured insert can sometimes create a strobe effect which should be prevented.

To avoid disorientating pedestrians affected by this type of visual disturbance, consider using a less contrasting insert.

If you are considering using rubber inserts for an exterior mat in an exposed entrance we recommend using a combination of rubber and bristle or Ultragrip rubber for maximum slip resistance.

Nuway Tuftiguard HD



# **nuway**<sup>®</sup> cable

Nuway cable is a versatile roll-up single sided entrance system that's available with a wide choice of inserts and accessories. It's also available in a MD format for areas that need a more robust single sided mat.

With a wide choice of inserts, Nuway cable allows the mat to be adapted to suit individual requirements. Bristles are available in single or three row options and they, along with the scraper accessory, can be used for exterior and interior entrances to remove coarse dirt. Rubber inserts are available for use in exterior entrances.

For the internal primary matting zone, Cable is available with a choice of four Coral classic inserts which allows the rigid entrance system to be colour co-ordinated to matching Coral classic sheet product used in the secondary matting zone. All four elements, Coral, bristles, scraper and rubber, can be mixed and matched to create the precise entrance system to meet your needs.

Cable is also available in a wide choice of heights from 10mm depth to 22mm with the 22mm option also available in a medium duty format. Open construction Cable mats can be rolled up for ease of cleaning of the matwell. Due to the construction of the mat, Cable mats are unsuitable for shaping on site.



### Specials

There may be times when different colourways are needed. Different colours are available at a small price premium, but there is a mininum order quantity of 10m<sup>2</sup> and the lead time will increase slightly.



	Nuway	Cable				
	Nuway Cable textile	Nuway Cable rubber and bristle				
Outdoor		1				
Indoor	1	1				
Insert	Coral Classic (4 colours)	Rubber or 3 row bristle				
Replaceable inserts	N	0				
Carrier	Alumi	nium				
Depth to height of aluminium						
Depth to height of insert	10, 17, 22 and 22mm MD (3 row bristles in 17 and 22mm only)  13, 20, 25 and 25mm MD (3 row bristles in 20 and 25mm only)  Open					
Construction	Ор	en				
Mix and match inserts	1	1				
Accessoires	3 row bristle availak product. Scraper available in 22m	and 1 row bristle				
Removes dirt	1	1				
Removes moisture	1					
Rollable	1	1				
Guarentee	1 y	ear				
Suitable for shaping on site	N	0				
Level of traffic	Very h	eavy*				

### \* Level of traffic

Heavy: school, shop, large office Very heavy: Shopping mall entrance



360 Nuway Grid

Nuway Cable 361

# **nuway**<sup>®</sup> connect

Nuway Connect is a very versatile roll-up single sided entrance system that's easy to shape on site, making it ideal for awkwardly shaped entrances. It's also available with a wide choice of inserts allowing the mat to be adapted to suit individual requirements.

- Bristles can be used for exterior and interior entrances to remove coarse dirt.
- Rubber inserts can be used for interior and exterior use.
- Ultragrip rubber inserts have been tested using the Pendulum (the HSE recommended test method) in accordance with BS7976-2 and the UK Slip Resistance Group Guidelines and offer a low slip risk in wet and dry conditions.
- Ultragrip rubber offers excellent sure footing and is ideal for multi-directional entrances. Its high rubber content prevents it getting slippy when wet.
- Ultragrip rubber offers improved underfoot comfort and moisture removal due to its 'pocket' design. It also offers excellent fire rating properties.
- A choice of 6 Coral classic inserts allows colour co-ordination with matching Coral classic sheet product used in the secondary matting zone.
- All four elements, Coral, bristles, rubber and Ultragrip rubber, can be mixed and matched to create the precise entrance system to meet your needs.
- All inserts can also be replaced on site helping to extend the wear life of the product.
- Available in a wide choice of heights from 10mm depth to 22mm and in open or closed construction.
- Open construction Connect mats can be rolled up for ease of cleaning
- The patented product design ensures that the mat can only be rolled inwardly, helping to prevent the bow wave that can occur on other rollable products.



### Technical specifications: **nuway**

### NUWAY CONNECT WITH CORAL CLASSIC TEXTILE INSERT

Combination		Textile only						•	Textile and	extile and 4 row bristle				
System		Open			Closed			Open			Closed			
	10mm	17mm	22mm	10mm	17mm	22mm	10mm	17mm	22mm	10mm	17mm	22mm		
Depth to height of aluminium (mm)	8	14	19	8	14	19	8	14	19	8	14	19		
Depth to height of insert (mm)	11	17	22	11	17	22	15	21	26	15	21	26		
Distance between the profiles (mm)		5			0			5			0			
Weight (kg)	9.5	13.2	14.9	10.5	15.1	17.1	11.1	15.1	16.9	12.4	17.4	19.4		
Max width per module (mm)		3000												
Max depth per module (mm)		Relates to the weight												
Max weight per module (kg)						2	23							
Dynamic load (kg) 2 wheels, 80mm 20,000 passes	200	200	200	200	200	200	50	50	50	50	50	50		
Static load (kg/sqcm)	200	200	200	200	200	200	100	100	100	100	100	100		
Fire behaviour EN ISO 9239-1			B <sub>f</sub>	ıs1					C <sub>f</sub>	ıs1				
Frame			A selecti	on of reces	sed matwe	I frames are	available, <sub>l</sub>	please see p	oage 4.0.2 f	or details				
Ramp frame	ARF 50	ARF 70		ARF 50	ARF 70		ARF 50	ARF 70		ARF 50	ARF 70			
Material and manufacturing method			Ano	dised alumi	nium profil	es with PVC	connector	profiles, sta	inless stee	clips				
Wiper design			Coral clear	ı-off system	ı			Coral cle	an-off syste	m and 4 ro	w bristles			
Wiper material			100% poly	ramide BCF			10	00% polyan	nide BCF fo	r both texti	le and bristl	les		

### NUWAY CONNECT WITH BRISTLE

Combination			Bristl	e only					Bristle an	d Rubber		
System		Open			Closed			Open		Closed		
	10mm	17mm	22mm	10mm	17mm	22mm	10mm	17mm	22mm	10mm	17mm	22mm
Depth to height of aluminium (mm)	8	14	19	8	14	19	8	14	19	8	14	19
Depth to height of insert (mm)	15	21	26	15	21	26	15	21	26	15	21	26
Distance between the profiles (mm)		5			0			5		0		
Weight (kg)	12.7	17.1	18.8	14.2	19.6	21.6	12.3	16.6	18.3	13.8	19.1	21.1
Max width per module (mm)		3000										
Max depth per module (mm)		Relates to the weight										
Max weight per module (kg)						2	3					
Dynamic load (kg) 2 wheels, 80mm 20,000 passes	50	50	50	50	50	50	50	50	50	50	50	50
Static load (kg/sqcm)	100	100	100	100	100	100	100	100	100	100	100	100
Fire behaviour EN ISO 9239-1			C <sub>f</sub>	ıs1					C <sub>f</sub>	s1		
Frame			A selecti	on of reces	sed matwel	l frames are	available, p	olease see p	oage 4.0.2 f	or details		
Ramp frame	ARF 50	ARF 70		ARF 50	ARF 70		ARF 50	ARF 70		ARF 50	ARF 70	
Material and manufacturing method			Ano	dised alumi	nium profil	es with PVC	connector	profiles, sta	inless stee	clips		
Wiper design			4 row	bristles				4 rov	v bristles ar	ıd ribbed ru	ıbber	
Wiper material			100% poly	ramide BCF			100% p	olyamide B	CF for brist	les and 100	% EPDM fo	r rubber

Please note EPDM rubber is Ethylene Propylene Diene Monomer.

362 Nuway Connect Technical Specifications Nuway 363

## Technical specifications: **nuway**

### NUWAY CONNECT WITH RUBBER OR ULTRAGRIP RUBBER

Combination	Rubber only						Ultragrip safety rubber only					
System	Open			Closed			Open			Closed		
	10mm	17mm	22mm	10mm	17mm	22mm	10mm	17mm	22mm	10mm	17mm	22mm
Depth to height of aluminium (mm)	8	14	19	8	14	19	8	14	19	8	14	19
Depth to height of insert (mm)	12	18	23	12	18	23	10	16	21	10	16	21
Distance between the profiles (mm)	5			0			5			0		
Weight (kg)	12	16.2	17.9	12	16.2	17.9	12	16.2	17.9	12	16.2	17.9
Max width per module (mm)	3000											
Max depth per module (mm)	Relates to the weight											
Max weight per module (kg)	23											
Dynamic load (kg) 2 wheels, 80mm 20,000 passes	100	100	100	100	100	100	100	100	100	100	100	100
Static load (kg/sq cm)	100	100	100	100	100	100	100	100	100	100	100	100
Fire behaviour EN ISO 9239-1	C <sub>fi</sub> s1						B <sub>f</sub> s1					
Frame	A selection of recessed matwell frames are available, please see page 4.0.2 for details											
Ramp frame	ARF 50	ARF 70		ARF 50	ARF 70		ARF 50	ARF 70		ARF 50	ARF 70	
Material and manufacturing method	Anodised aluminium profiles with PVC connector profiles, stainless steel clips											
Wiper design	Ribbed rubber						Coarse rubber					
Wiper material	100% EPDM						Rubber					



# **Our footprint**

How it's made





43%







recycled content in all tessera® carpet tiles made in the UK





..... ISO 14001

creating better environments

Sustainability is about the things you can't see



FLOORING SYSTEMS




















back to the floor









>70% recycled content in the backing of

100%









Forbo Flooring Systems is part of the Forbo Group, a global leader in flooring, bonding and movement systems, and offers a full range of flooring products for both commercial and residential markets. High quality linoleum, vinyl, textile, flocked and entrance flooring products combine functionality, colour and design, offering you total flooring solutions for any environment.



Forbo Flooring B.V. P.O. Box 13 1560 AA Krommenie The Netherlands T: +31 75 647 74 77 F: +31 75 647 77 01 contact@forbo.com www.forbo-flooring.com

Follow us on



