





Flocked Floor Coverings





creating better environments

FLOCKED FLOORING IN SHEET, TILE AND PLANK

Flotex is a floor covering that looks and feels like a carpet without any of the drawbacks of a textile floor covering. It has a smooth, velour like surface that is comfortable to walk on and warm underfoot, with excellent slip resistant and acoustic properties.

flotex[®] colour

Three versatile and fresh designs make up the Flotex Colour collection: Metro, Calgary and Penang. Together they offer a range of 110 unique colourways, all available in sheet and tile and all complemented by 26 Artline borders. Flotex Colour ranges have no pattern repeats due to their Green Design.



flotex[®] linear

This collection presents a comprehensive choice of five linear designs in various colourways that complement commercial and educational environments, but also deliver playful effects for leisure, hospitality or retail spaces.



Flotex, more than any of our products, fulfils our ambition to contribute to creating better indoor environments by committing to the health and well-being of all individuals living and working in indoor spaces. Flotex achieves this through excellent hygiene and sound absorbing qualities, phthalate-free products, the certification by Allergy UK for the positive effects it has on allergy sufferers, and a wide range of stimulating designs and sympathetic colours which can create inspiring interiors.



flotex[®] planks

The performance attributes of Flotex along with the design versatility of the Plank collection, make these modular floor coverings ideal for use in workspaces as well as high traffic areas such as call centres, hotels and transport hubs.

flotex[®] naturals

This special range of digitally printed Flotex delivers the appearance of a real wood floor but with improved acoustics and reduced maintenance costs.

flotex[®] vision

We've brought together an inspiring choice of over 500 digitally printed designs to suit every taste or requirement, right down to a 'colour on demand' option.







flotex®



The term 'bionic' refers to features found in nature that are replicated in man-made products and processes. This transfer of technology from living fauna and flora helps to create optimised and highly efficient products. An example of this is the development of water and dirt repellent surfaces inspired by the way the leaves of the lotus flower dispel water.

The 70 million fibres per m² in Flotex provide a slip resistant surface in both wet and dry conditions similar to the way the feet of a gecko are covered with thousands of tiny hairs that allow them to climb without slipping. They also absorb sound making Flotex a quiet floor.

Flotex fibres are flexible and comfortable underfoot and, just like moss and bamboo, their density, design and strength means they return to their original shape. Such strength creates durability and a surface which is exceptionally resistant to wear, especially from the likes of castor chairs.

Bees fly from one flower to the next collecting and releasing pollen when they need to, in the same way that Flotex traps the allergens in the tip of the nylon 6.6 fibres until easily releasing them on vacuuming. These properties mean that Flotex is approved by Allergy UK.

Advanced printing technologies used in the production of Flotex replicate the rich, vibrant and precise colourations found in nature. This means you can evolve our product to create almost limitless design possibilities with digital printing using our Flotex Vision system.



Flotex has a positive impact on the lives of allergy sufferers as daily vacuuming removes twice as many allergens compared to conventional carpets. That is why Flotex carries Allergy UK's seal of approval.

How does Flotex compare to other textile floor coverings?

	Flotex	Loop pile carpet tile	Cut pile carpet tile	Needlefelt sheet
Durability	• • • •	•••	•	••
Cleanability	• • • •	•	•	•
Ease of installation (tile)		••••	••••	•
Hygienic and 'Allergy UK' approved		-	-	-
Impermeability (sheet)	••••	-	-	-
Repairs to damage	•••	••••	••	-
Impact sound reduction	•••	••••	••••	•••
Underfoot comfort	••	•••	••••	•

FLOTEX THE HIGH TECH TEXTILE



- Straight Nylon 6.6 fibres (flock) capture fine dust and allergens which are easily released when vacuumed
- 70 million fibres per m² deliver an extremely durable and slip resistant surface
- Impervious backing makes Flotex suitable for mechanical wet cleaning Double strength glass fibre reinforcement results in excellent dimensional stability
- **FLOTEX** A CHOICE, NOT A COMPROMISE

Flotex offers a completely different dimension in flooring as it combines all the hard wearing and durable characteristics of a resilient floor with the warmth and comfort of a textile floor covering. EN 1307, the European Standard which measures the performance of textile flooring, has recently annexed extra clauses to this standard to recognise that flocked floor coverings differ from textile flooring.

EN1307 annexe F – abrasion resistance

In this new standard, the pile surface of the flocked flooring is rubbed back and forth 1,000 times with a 2cm wide pointed metal blade loaded with a 2kg weight. The aim of the test is to establish the durability of the flocked flooring. At least 50% of the pile must be retained at the end of the test for the product to meet the standard's requirement. We test Flotex for 1,500 cycles and we achieve a much higher result than 50% of pile remaining.

Cleanability

Whether it's water soluble stains such as coffee, ketchup, cola, wine etc or a greasy stain like butter, engine oil or permanent marker, it can be removed from Flotex. Just visit www.forbo-flooring.co.uk/flotex and watch our 'Clean and Care' video to see how the floor below was guickly and simply cleaned to look just like a new floor.







- Cushioned backing provides comfort and acoustic performance
- · Flotex sheet contains approximately 20% recycled content
- Flotex tile and plank contain approximately 52% recycled content









flotex[®]

WHY CHOOSE FLOTEX?

A floor covering that looks and feels like a carpet without any of the drawbacks of a textile floor covering.





flotex[®] colour flotex[®] colour metro neon metro

Flotex Metro is a versatile semi-plain design which covers a wide and modern colour bank including 8 statement neon colours. The understated pattern conveys texture without definite form, creating an authentic feel that is unique to Flotex. This collection lends itself to education, aged care or retail applications but will work in any location where a subtle textile look is desired.

There is no pattern repeat on Metro as this range has been designed with Green Design principles.

Description		Flocked flooring
Dimensions		Sheet: Roll width 2m Roll length ≤ 30m Tile: 50cm x 50cm (3m ² per box 60 x 60cm & 100 x 100cm available on request
Total thickness	ISO 1765	Sheet: 4.3mm Tile: 5.3mm
Slip resistance	Pendulum test	Wet – low slip risk
Collection size		45
Application	EN 1307	Class 33
Impact sound reduction	EN ISO 717-2	Sheet: $\Delta Lw = 20 \text{ dB}$ Tile: $\Delta Lw = 19 \text{ dB}$
Œ	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30
Body voltage	EN ISO 10965	< 2 kV





			A CONTRACTOR					東京などの一部である
s246033 t546033	emerald	LRV 11	s246019 t546019	citrus	LRV 18	s246012 t546012	sand	LR
s246037 t546037	apple	LRV 15	s246022 t546022	evergreen	LRV 6	s246021 t546021	moss	
\$246034 t546034	lilac	LRV 9	s246035 t546035	pink	LRV 7	\$246030 t546030	cinnamon	
\$246031 t546031 \$287005 t587005 \$287005	cherry graphic	LRV 6	s246026 t546026 s287002 t587002 s287002 s287002 s287002 s287008	zest	LRV 9	\$246003 \$546003 \$287004 \$287004	electric	LR
5287007 1587007 5287007 5287006 1587006		LRV 5		lava flame	LRV 7	BREEAN Flotex C	M ratings Colour – Flc Colour – Flc Type Edu	otex

For more information see page 31.

s = Sheet t = Tile





Our recommended adhesive for Flotex Sheet is 540 Eurosafe Special or 640 Eurostar Special. For Flotex tiles our recommended adhesive is S42 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.

flotex[®] colour penang

Flotex Penang offers a stunning look for any modern environment. It creates a subtle linear effect and comes in a range of rich modern shades.



s482022 amber LRV 23 t382022 s482013 | berry t382013 | LRV 5 s482114 chocolate LRV 3 s482012 red t382114 LRV 4 Description Flocked flooring Sheet: Roll width 2m Roll length ≤ 30m Tile: 50cm x 50cm (3m² per box) Dimensions 60 x 60cm & 100 x 100cm available on reques s482015 | beige LRV 12 t382015 | Sheet: 4.3mm Tile: 5.3mm Total thickness ISO 1765 Slip resistance Pendulum test Wet - low slip risk Collection size 34 Application EN 1307 Class 33 Sheet: $\Delta Lw = 20 \text{ dB}$ Tile: $\Delta Lw = 19 \text{ dB}$ Impact sound EN ISO 717-2 Œ EN 14041 Be-s1 Reaction to fire EN 13501-1 s482004 mercury LRV 10 t382004 DS: >0.30 Slip resistance EN 13893 EN ISO 10965 Body voltage < 2 kV Sheet $\begin{array}{c|c} \hline 1 & 1 \\ \hline 1 & 1 \\ \hline 1 & 1 \\ \hline \end{array} \begin{array}{c} \hline 1 & -1 \\ \hline 1 & 1 \\ \hline \end{array} \begin{array}{c} \hline 1 & 1 \\ \hline 1 & 1 \\ \hline \end{array}$ Tile s482001 | anthracite LRV 3 t382001 | s482020 | shale LRV 10 t382020 | LRV 15 s482023 dusk t382023 s482021 | silver t382021 |





LRV 8 s482016 coral LRV 16 s482024 purple t382016 0 t382024

LRV 5

flotex[®] colour calgary

Flotex Calgary offers a wide colour choice in a soft, natural design that works well in larger areas. The pattern can be easily combined with complementary Flotex or resilient ranges and is the perfect choice for application areas that require a muted ambience.





s290007 | suede LRV 23 s290013 | caramel LRV 17 s290011 | quartz LRV 28 t590007 | 10 t590013 | 10 t590011 | 10 LRV 18 t5900118

LRV 3 s290026 | linen t590026 | LRV 16 s290028 ginger t590028 LRV 15 s290020 toffee s290006 | sahara t590006 | LRV 29 s290008 | saffron LRV 28 s290003 | red t590008 | 🖸 t590003 | LRV 5 s290005 | melon t590005 | LRV 10 s290015 | azure t590015 | LRV 4 s290022 | condor LRV 10 t590022 | s290001 | sky t590001 | LRV 15 s290018 fossil t590018 LRV 24 s290021 | aqua t590021 | LRV 29 s290016 apple LRV 24 LRV 36 s290009 | moss t590009 | LRV 13 s290014 | lime t590014 | BREEAM ratings Flotex Colour – Flotex F50 tile with recycled backing (EN1307) Flotex Colour - Flotex F200 sheet with PVC backing (EN1307) Building Type Education Healthcare Multi Retail Retail Meets Ska criteria Fashion Tile A+ ~ Sheet

Usage classification

Superior appearance rating O Good appearance rating O Moderate appearance rating For more information see page 31.

s = Sheet t = Tile

Our recommended adhesive for Flotex Sheet is 540 Eurosafe Special or 640 Eurostar Special. For Flotex tiles our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369









flotex[®] artline

With Artline you are able to make borders, creative features and delineators between colourways or even different designs. Artline is available in 11 or 22cm widths and matches the base shades of the various Flotex Colour and Linear designs.



		cocoa • 211081 • 232081	
		cinnamon • 211094 • 232094	
1		chocolate • 211114 • 232114	
		brick 211073 232073	
		melon 211072 232072 	
		berry 211083 232083	
		lilac • 211100 • 232100	
		pink 211091 232091	
		red 211008 232008	
		tangerine • 211003 • 232003	
2 050 anthracite		gold 211099 232099	
BREEAM ratings			
	otex F200 sheet with PVC backi	na (EN1307)	

• 11 cm wide • 22 cm wide

pebble

. • 211076

232076

truffle

211093

232093

Dimensions		Roll width 11/22cm Roll length ≤ 15m
Total thickness	ISO 1765	4.3mm
Slip resistance	Pendulum test	Wet – low slip risk
Collection size		26
Application	EN 1307	Class 33
Impact sound reduction	EN ISO 717-2	$\Delta Lw = 20 \text{ dB}$
Œ	EN 14041	
Reaction to fire	EN 13501-1	B _{fi} -s1
Slip resistance	EN 13893	DS: ≥0.30
Body voltage	EN ISO 10965	< 2 kV

Flocked flooring

	Flotex Artline – Flotex F200 sheet with PVC backing (EN1307)								
	Building Type Office	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)			
Sheet	А	A+	A+	A	A	A+			
Usage classification									





Meets Ska

criteria

~

anthracite

211050

232050

ash

211031

232031

grey • 211046

tempest 211110 232110

sapphire 211092 232092

evergreer 211088 232088 moss

232090

flotex[®] naturals

the appearance of a real wood floor.

and colour schemes, from beech and blackened oak to

Description		Flocked flooring
Dimensions		Roll width 2m Roll length ≤ 30m
Total thickness	ISO 1765	4.3mm
Slip resistance	Pendulum test	Wet – low slip risk
Collection size		9
Application	EN 1307	Class 33
Impact sound reduction	EN ISO 717-2	$\Delta Lw = 20 \text{ dB}$
Œ	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30
Body voltage	EN ISO 10965	< 2 kV



010038 | white oak





Building Type | Education Offic Sheet А

> Usage classification For more information see page 31.

010037 blackened oak Pattern repeat: 200 x 150cm LRV 7 🖲

Description



Superior appearance rating O Good appearance rating O Moderate appearance rating

Our recommended adhesive for Flotex Sheet is 540 Eurosafe Special or 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.

flotex[®] linear integrity²

Muted colours, stylish design – Integrity² offers both. Create understated flooring designs using tessellation for this range. The effect is a subtle, sophisticated linear effect.

Available in tile format. 60cm x 60cm and 100cm x 100cm available on special request.



flotex[®] linear complexity

Whether you choose the familiar tessellated style or the more unusual brick method, Complexity will add a striking and intriguing effect to any commercial space. The linear design has been created to sit alongside Integrity² for maximum flexibility.

Available in tile format. 60cm x 60cm and 100cm x 100cm available on special request.





Tile

В

t550007 | blue LRV 11 🖸 t550006 | marine LRV 7 🖲





Description		Flocked flooring
Dimensions		Tile: 50cm x 50cm (3m ² per box) 60 x 60cm & 100 x 100cm available on request
Total thickness	ISO 1765	5.3mm
Slip resistance	Pendulum test	Wet – low slip risk
Collection size		12 (Integrity) 10 (Complexity)
Application	EN 1307	Class 33
Impact sound reduction	EN ISO 717-2	$\Delta Lw = 19 \text{ dB}$
(€	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30
Body voltage	EN ISO 10965	< 2 kV
Integrity ↑↑	Complexity	



criteria

~

flotex[®] linear pinstripe

With its subtle, tailored design, Pinstripe can be installed brick, tessellated or half-drop to achieve very different aesthetic effects. This distinctive and versatile carpet tile is equally at home in offices, retail or leisure environments as it's a style that complements contemporary floor spaces, both large and small.

Available in sheet and tile format. Tiles also available in 60cm x 60cm and 100cm x 100cm upon request. Pattern repeat for sheet is 52.5cm x 50cm.





Description		Flocked flooring
Dimensions		Sheet: Roll width 2m Roll length ≤ 30m Tile: 50cm x 50cm (3m ² per box) 60 x 60cm & 100 x 100cm available on request
Total thickness	ISO 1765	Sheet: 4.3mm Tile: 5.3mm
Slip resistance	Pendulum test	Wet – low slip risk
Collection size		12
Application	EN 1307	Class 33
Impact sound reduction	EN ISO 717-2	Sheet: ΔLw = 20 dB Tile: ΔLw = 19 dB
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30
Body voltage	EN ISO 10965	< 2 kV



Our recommended adhesive for Flotex Sheet is 540 Eurosafe Special or 640 Eurostar Special. For Flotex tiles our recommended adheisve is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.



Usage classification

Superior appearance rating Good appearance rating Moderate appearance rating For more information see page 31

s = Sheet_t = Tile

Tile

Sheet

flotex[®] linear stratus

The variety of installation methods available for Stratus opens up a huge number of flooring design options and, when used alongside colours from the contemporary Cirrus design, the creative options become almost infinite.

Available in sheet and tile format. Tiles also available in 60cm x 60cm and 100cm x 100cm upon request. Pattern repeat for sheet is 35cm x 25cm.



flotex[®] linear cirrus

The Cirrus design is ideal for large scale installations and also offers a wide choice of fitting methods for additional flexibility. When used in combination with the Stratus design, colour coordinated solutions can easily be created.



Our recommended adhesive for Flotex Sheet is 540 Eurosafe Special or 640 Eurostar Special. For Flotex tiles our recommended adheisve is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.

For more information see page 31

s = Sheet t = Tile

flotex[®] planks box-cross

With one design you can transform a space. With Box-cross every plank is unique, containing a pattern that subtly changes from cross to box, fading one into the other along the length of the plank whilst a diagonal texture plays across the width, blending the planks together.





LRV 7 💽 133011 | anthracite LRV 4 🖲



Usage classification

Superior appearance rating Good appearance rating O Moderate appearance rating For more information see page 31.

	4 ************************************	
133004 biscuit	********** **********	133015 gold LRV 17
133001 amber 133008 bluebe		133005 linen LRV 20
Description		Flocked flooring
Dimensions		100cm x 25cm (2.5m ² per box
Dimensions Total thickness	ISO 1765	100cm x 25cm (2.5m ² per box 5.3mm
	ISO 1765 Pendulum test	
Total thickness		5.3mm

Impact sound EN ISO 717-2 $\Delta Lw = 19 \text{ dB}$

EN ISO 10965

Half-drop

EN 14041

Reaction to fire EN 13501-1

Slip resistance EN 13893

Œ

Body voltage

Half-drop

installation 1

LRV 5 🖲

Our recommended adhesive for Flotex planks is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.

B_e-s1

DS: ≥0.30

Random drop Random drop installation 2 installation 1 installation 2

< 2 kV

flotex[®] planks concrete

A concrete look like never before. Highly detailed, warm and tactile but with the durability to rival a real concrete floor. Experiment with its four colourways to create a striking look or choose a single colourway for an urban, minimal aesthetic.





139003 | smoke LRV 16 LRV 18 🖲 139002 | thunder LRV 11 🖲

139004 | storm

LRV 11 💽

133014 | forest

Description		Flocked flooring
Dimensions		100cm x 25cm (2.5m ² per box)
Total thickness	ISO 1765	5.3mm
Slip resistance	Pendulum test	Wet – low slip risk
Collection size		4
Application	EN 1307	Class 33
Impact sound reduction	EN ISO 717-2	$\Delta Lw = 19 \text{ dB}$
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30
Body voltage	EN ISO 10965	< 2 kV
Half-drop installation 1 Double herringbone installation 1	Half-drop installation 2 Double herringbone installation 2	Herringbone installation 1 Weave installation 1 Weave installation 1

flotex[®] planks lava

LRV 5 🖲

LRV 8 🔳

145004 | Aqua

145008 | Koro

145017 | Fuji

LRV 5 🔳

LRV 8 🖲

LRV 18 🔳

145014 | Pelee

145011 Krakatoa LRV 7 🖲

145013 | Elbrus

Lava is all about texture and colour, giving you an opportunity to define space, highlight areas and explore creative design combinations in every way possible. From subtle shades to vibrant brights, Lava brings a palette of choice to the floor.



LRV 18 🖲

LRV 16 🔟

LRV 18 🖸

目Ш

Weave Weave installation 1 installation 2



flotex[®] planks seagrass

The ultimate playground when it comes to floor designs. Seagrass is happy when it is laid as herringbone or even double herringbone, but also as half-drop or weave. The creative options are almost limitless. Although the colourways have been designed to be easily combined, a single colour floor design looks equally sophisticated.





111001 | pearl

LRV 26 🖸 111006 | liquorice LRV 5 💽

Usage classification

Superior appearance rating O Good appearance rating O Moderate appearance rating For more information see page 31.

Our recommended adhesive for Flotex planks is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.



Flocked flooring Description 100cm x 25cm (2.5m² per box) Dimensions Total thickness ISO 1765 5.3mm Slip resistance Pendulum test Wet - low slip risk

Collection size		б	
Application	EN 1307	Class 33	
Impact sound reduction	EN ISO 717-2	$\Delta Lw = 19 \text{ dB}$	
CE	EN 14041		
Reaction to fire	EN 13501-1	B _{fl} -s1	
Slip resistance	EN 13893	DS: ≥0.30	
Body voltage	EN ISO 10965	< 2 kV	
Half-drop installation 1 Double herringbone installation 1	Half-drop installation 2	Herringbone installation 1	Herringbone installation 2 Weave installation 2

flotex[®] planks triad

This pattern offers you the creative freedom to mix and match, combining colours and installation methods easily to customise your floor. It looks great laid half-drop, herringbone or weave and has a range of exciting colourways with highlight options. There's also a unique embossed version to add more texture and tactility to your floor.

All colourways in the Triad collection feature a superior appearance rating.



Description		Flocked flooring
Dimensions		100cm x 25cm (2.5m ² per box)
Total thickness	ISO 1765	5.3mm
Slip resistance	Pendulum test	Wet – low slip risk
Collection size		19
Application	EN 1307	Class 33
Impact sound reduction	EN ISO 717-2	$\Delta Lw = 19 \text{ dB}$
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30
Body voltage	EN ISO 10965	< 2 kV
Half-drop installation 1		Herringbone installation 1

	Triad	d 131006 silv	er + 121001 embos	sed zinc
per box)		T	4	<
	131018 navy	LRV 4 🔳	131013 green line	ELRV 8 🖲
			<u>_</u>	
gbone ation 2	131012 blue line	LRV 8	131003 green	LRV 10 💽
	131002 blue	LRV 7	131010 taupe	LRV 11 🖲



LRV 7 🖲 131010 | taupe LRV 11 🖲 121001 | embossed zinc

flotex[®] planks wood

A wood pattern on a textile floor? You will be amazed how good it looks and also how it feels and performs. Soft underfoot and without the disturbance of the noise of foot traffic, it's the ideal floor for busy spaces in offices, hotels rooms, public buildings and elderly care locations. It's a mindset change. Get the looks of real wood with the advantages of a textile floor. All installation patterns are possible, simply allow your imagination free rein to create.



Usage classification

Superior appearance rating O Good appearance rating O Moderate appearance rating For more information see page 31.

Our recommended adhesive for Flotex planks is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.



	Flocked flooring		
	100cm x 25cm (2.5m ² per box)		
ISO 1765	5.3mm		
Pendulum test	Wet – low slip risk		
	6		
EN 1307	Class 33		
EN ISO 717-2	ΔLw = 19 dB		
EN 14041			
EN 13501-1	B _{fl} -s1		
EN 13893	DS: ≥0.30		
EN ISO 10965	< 2 kV		
installation 2	Herringbone installation 1 Weave installation 1 Weave installation 1 Weave installation 2		
	Pendulum test EN 1307 EN 150 717-2 EN 14041 EN 13501-1 EN 13893 EN 150 10965 Half-drop installation 2		

The digital world of Flotex vision

With Flotex Vision, Forbo offers a **unique collection** of **high definition digitally printed designs**

As Flotex has 70 million fibres per square metre, it provides a matt high density substrate for printing, enabling vibrant designs and true to life visuals that can be produced in high level photographic resolutions. All colours, tones and hues are achievable with Flotex Vision.

Fantastic effects

Endless design options

Flotex Vision offers an infinite number of design options ranging from abstracts with an intricate colour spectrum to realistic images of natural materials such as grass, sand and water. Nature can be brought indoors by creating a pebble beach or a field of clover and 3D effects or "trompe l'oeil" designs can also be produced allowing stunning effects on the floor. Flotex Vision is also well suited for patterns and designs that require a precise level of visual detail and high definition, effects that cannot easily be achieved through conventional print. The Flotex Vision collection contains over 500 individual designs, ranging from traditional to contemporary, including many with a wide choice of colourways.

Colour your own or design your floor

Do you like a design but cannot find the colour you want, or do you want to match a design to your corporate colour scheme? Flotex Vision offers a large number of designs that can be recoloured by selecting the colours you want to use. To find out more visit www.forbo-flooring.co.uk/flotexvision.







BREEAM ratings Flotex F200 HD – sheet with PVC backing (EN1307)						
Building Type Office	Education	Healthcare		Retail (Durability)	Retail (Fashion)	M
А	А	A	В	A	A+	







The Flotex vision **digital library**

With over 500 individual items to choose from, plus the option to create your own colourway of several of the designs, or even a completely bespoke design, a sample book is never able to capture all the options that are available. Therefore Flotex Vision is available in a flexible and 'always up-to-date' online digital library.

The designs in Flotex Vision fall into seven broad categories, each of them representing a different design direction. New Flotex Vision designs will be regularly added to our online library which already contains over 500 different designs and colourways.

Here are our seven design directions:

Floral

A selection of eight floral designs, ranging from abstract, graphic flower motifs to romantic images of roses and butterflies. There are also flower designs that are ideal for children's nurseries. Each of the eight design types in this category is available in a variety of colourways.







Linear

Eight line or stripe designs, each with their own characteristics, ranging from muted and sophisticated colourways to very complex and multi-colour.





Shape

A collection of organic shapes and motifs delivering beautiful all-over patterns, including both contemporary and traditional designs.







Naturals

This collection offers photorealistic images of natural materials such as wood, stone, ceramics or cork floors. The design technology creates amazingly realistic floors but with the added benefit of improved acoustics, slip resistance and reduced maintenance costs. The Naturals collection shown on page 15 represents our stocked range of wood designs.

Pattern

The intricate play of networks and patterns creates a textured, non-directional visual. Each design in this category is available in a number of colourways.



Artist Collection

A range of six designs which are based on famous paintings by Van Goqh.



Image

This design category contains a wide variety of photographic images that have been transformed into interesting and unique floors. Grass, sand, water drops, buttons or street maps are just some of the possibilities amongst the wide range of images.















Go online and discover over 500 designs for your floor

Find your design in 4 easy steps:

- 1. Access www.forbo-flooring.co.uk/flotexvision
- 2. Choose your main design entry in the library (1 out of 8 entry options)
- 3. Choose the collection you like
- 4. Choose the colour you like... and order your sample online



Q 200M



www.forbo-flooring.co.uk/flotexvision

FLOTEX USAGE CLASSIFICATION

As with any product, colour and design influence the appearance retention of the floor. Likewise, Flotex is able to "hide" any soiling or dirt to a greater or lesser degree depending on the base colour and the visual design.

Using European (EN) approved testing methodology we have graded every item in the collection on its ability to 'hide' general dirt or staining that occurs during normal use depending on the application.

> The result is a usage classification that can be referred to when taking into consideration such things as type and level of traffic in the chosen application area. The classification is shown alongside each colour and design in this brochure.

Superior appearance rating

Good appearance rating

Moderate appearance rating

Cleanable surface finish

When prescribed cleaning procedures are followed, Flotex outperforms any textile floor covering in appearance. Its smooth upright nylon 6.6 fibres allow dirt to be easily removed. No dry dirt is trapped by any loops or twists (as can happen with standard carpet) and the vacuum action reaches the very base of the pile, meaning that all dirt is removed.

The vinyl base combined with the nylon 6.6 flocked finish allows the floor covering to be fully cleaned with water and detergents. Steam cleaning or mechanical cleaning methods can also be applied resulting in cleaner floors. Flotex is therefore the only truly waterproof textile floor covering which enables the floor to be restored quickly and easily even after heavy soiling.





Vacuuming Flotex

Vacuuming conventional carpet

30 Flocked Flooring



Forbo Flooring Systems is part of the Forbo Group, a global leader in flooring and movement systems, and offers a full range of flooring products for commercial and affordable housing and new build markets. High quality linoleum, vinyl, textile, flocked and entrance flooring products combine functionality, colour and design, offering total flooring solutions for any environment.

UK

Forbo Flooring UK Limited High Holborn Road Ripley Derbyshire DE5 3NT

London EC1 showroom 79 St John Street, Clerkenwell London EC1M 4NR Tel: 0207 553 9300

For commercial enquiries:

If calling from the North, London & South East Tel: 0800 0282 162 Fax: 01772 646 912 bcs.flooring.uk@forbo.com

If calling from Scotland, Midlands & South West Tel: 0800 0935 258 Fax: 01592 643 999 kcs.flooring.uk@forbo.com Nuway enquiries: Tel: 01773 740 688 Fax: 01773 740 640 efs.flooring.uk@forbo.com

Residential enquiries: Tel: 0800 0935 846 Fax: 01592 643 999 krcs.flooring.uk@forbo.com www.forbo-flooring.co.uk

Sample orders: Tel: 0800 731 2369 Fax: 0843 319 1831 samples.uk@forbo.com

Ireland

Forbo Ireland Ltd 2 Deansgrange Business Park Blackrock Co Dublin Tel: 00353 1 2898 898 Fax: 00353 1 2898 177 info.ireland@forbo.com www.forbo-flooring.ie

Find us on



Registered office:

Forbo Flooring UK Limited High Holborn Road Ripley Derbyshire DE5 3NT Registered in England 9200318





