

Technical specifications

coral® click

	with Coral Brush insert		without Coral Brush insert	
Type	Closed 12mm	Closed 17mm	Closed 12mm	Closed 17mm
Weight tile (kg)	0.46	0.56	0.42	0.52
Weight (kg/sqm)	8.1	9.8	7.4	9.1
Content of box	24 tiles/1.37 sqm		24 tiles/1.37 sqm	
Weight of box (kg)	11.7	14.1	10.7	13.1
Tile manufacturing method	Injection moulding		Injection moulding	
Base material	UV resistant PVC		UV resistant PVC	
Base colour	Anthracite		Anthracite	
 Tile width x length per tile (cm)	24 x 24		24 x 24	
 Tile thickness (mm)	14	19	11	16
Resistance dynamic load (kg) [40,000 passes]	200*		200*	
Resistance static load (kg/sqcm)	50		50	
 Fire classification	EN ISO 13501-1	B _{fl} s1	C _{fl} s1	
 Slip safety (BS 7976-2)	'Low risk'		'Low risk'	
Temperature resistance	-30° <> +50° Celsius		-30° <> +50° Celsius	
% of surface that is textile	70%		-	
Standard available colours Coral Brush	5714 - 5721 - 5723 - 5727 - 5730		-	
Textile pile material	100% regenerated ECONYL® Nylon		-	
Textile manufacturing method	Tufted, 5/32" cut-pile		-	
Textile tuft base	Non-woven polyester		-	
 Textile light fastness	EN ISO 105/B02	>5	-	
Textile rubbing fastness	EN ISO 105/X12	5	-	
Textile water fastness	EN ISO 105/E01	4 - 5	-	
Textile sea water fastness	EN ISO 105/E02	4 - 5	-	
Textile water stains fastness	EN 1307 - G	5	-	
Textile shampoo fastness	BS 1006	4 - 5	-	
Textile organic solvents fastness	EN ISO 105/X05	4 - 5	-	
 Installation methods	Coral Click is an adhesive free tile which can be installed in the following directions; monolithic, brick, half drop, tessellated, quarter turn or quarter turn mirrored.			
 Guarantee	Coral Click is guaranteed for 5 years under heavy contract conditions provided it has been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.			

* *straight running fixed wheel test*

For the latest installation instructions, please visit www.forbo-flooring.co.uk/installation

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

Coral is manufactured in a facility certified to SA8000 and OHSAS 18001.



Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.



For more information:

e: info.flooring.uk@forbo.com

t: **0800 121 4780**

w: forbo-flooring.co.uk/coral



FLOORING SYSTEMS