





## **DSDC ACCREDITED**PRODUCTS

The Dementia Services Development centre at the University of Stirling has undertaken a review of this product and have rated its design in relation to dementia design principles and its usability within a dementia-inclusive environment. For ease of identification, the suitability of the product is classified by a number with corresponding explanation of use, within the key ratings provided.

The DSDC Accredited product logo is awarded on the merit of the individual product and colourway. This accreditation does not merit the final application. Whilst every endevour has been made to ensure the ratings are reflective of the product's suitability and applied use at the time of print, DSDC cannot be held responsible for the application of the final product, its performance or its interface with other products or finishes. For an environment to be considered 'dementia-inclusive' or 'dementia-friendly, careful consideration must be given to the specification of adjoining finishes, their performance specification, for example, light reflectance value (LRV), slip resistance and use of pattern, and their suitability for their intended use.

For more information please contact dementia@stir.ac.uk







## **DSDC** RATING SYSTEM

Dementia Design Accredited Product	2016-074 FORBO FLOORING	UNIVERSITY of STIRLING
	FORBO KITE MARKING RATING KEY	
	NOV-16	
RATING	RATING DESCRIPTION	
Class 1a	Flooring within this rating is plain and can be used indiscriminately. That said, bear in mind the need to contrast flooring and walls, skirtings, doors / frames, furniture and sanitary ware.	
	Contrast is the key word.	
	We recommend a minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.	
Class 1b	Flooring within this rating is semi-plain (minimal texture or fleck / pattern, wood effect with no knots) and in general, can be used throughout.	
	Natural patterns such as timber and stone may be used in most areas due to their familiarity but with a degree of caution.	
	Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.	
Class 2	Flooring within this rating has some pattern and needs to be used with caution. The natural patterns such as timber and stone in this range are more figured / patinated and although still familiar they need to be used with more caution than the above range.	
	Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.	

To find Forbo accredited DSDC products visit:

www.forbo-flooring.co.uk/productfinder