

Technical specifications

Inline meet the requirements of EN 1307

Description		
	Tufted multi-pile height loop carpet tile	
	Tile size	EN ISO 24342:2018
	Total thickness	ISO 1765
	Pile height	ISO 1766
	Collection size	12
	Packaging per carton tiles	16 (4 m ²)
	Commercial use	EN ISO 10874
	Pile composition	100% polyamide 6
	Dye method	100% solution dyed
	Stitch density	ISO 1763
		198,374 per m ²
	Pile weight	ISO 8543
	Total weight	ISO 8543
	Primary backing	Polyester
	Secondary backing	ProBac™ recycled mineral filler with low amount of modified bitumen and polyester fleece
	Alternative available secondary backing	SOFTbac®
	Acoustical impact noise reduction	ISO 10140-3
		25 dB
	Acoustical sound absorption	ISO 354
		aw = 0.20 (H)
	Castor chair continuous use	ISO 4918
		r ≥ 2.4
	Colour fastness to light	EN ISO 105-B02
		≥ 5
	Dimensional stability	EN 986
		≤ 0.2 %
	Indoor air emissions: TVOC after 28 days	EN 16516
		≤ 0.1 mg/m ³
	Creating Better Environments	
	Renewable Energy	All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas)
	Recycled Content	Inline carpet tiles contain 62% recycled content by weight
	Indoor air quality	Inline carpet tiles comply to Indoor Air Comfort Gold 8.0 (2022)
	Ska Rating	Inline meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes
	Prodis-GUT	www.pro-dis.info
	Installation method	Monolithic, quarter turn or tessellated

Inline carpet tiles meet the requirements of EN 14041:2004 and BS EN 14041:2004

EN 14041 BS EN 14041

	Product code	EN 14041	1170100-DOP-109
	Product code	BS EN 14041	1170100-DoP-GB109
	Reaction to fire	EN 13501-1	B _{fl} -s1, G, NCS
	Slip resistance	EN 13893	μ ≥ 0.30
	Body voltage	ISO 6356	≤ 2.0 kV
	Thermal conductivity	EN 12524	0.06 W/mK

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001. Tessera carpet tiles and planks are manufactured in a facility certified to SA8000® and ISO 45001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's).