Technical specifications

		Coral Logo (48xx)	
Meets the requirements of		EN ISO 24011	
Total thickness	ISO 1765	8 mm	
Wear classification	EN 1307	31, commercial heavy	
Available sizes (all sizes are approx.)		Standard mat sizes (sizes with edges)	Special sizes (sizes without edges)
		60 x 90 cm	width x length
Roll and mat sizes with 2,5 cm vinyl edges each side		115 x 155 cm 115 x 300 cm	Up to 195 cm up wide
		155 x 200 cm 150 x 300 cm	
		200 x 200 cm 200 x 300 cm	Up to 700 cm length
Colour fastness ratings:			
Light	EN ISO 105/B02	> 5	
Rubbing	EN ISO 105/X12	4-5	
Water	EN ISO 105/E01	4-5	
Manufacturing method/type		Tufted, 1/8" cut-pile	
Designs		Hi-definition custom print	
Pile material		100% High Twist Nylon polyamide	
Tuft base		Non-woven polyester	
Backing phthalate free vinyl		EVERFORT vinyl	
Total weight	ISO 8543	Approx. 3350 gram/m^2	
Pile installation weight	EN 1399	Approx. 680 gram/m^2	
Pile thickness	ISO 1766	Approx. 5 mm	
Pile density	ISO 8543	0.133 gram/cm^3	
Number of tufts	ISO 1763	Approx. 110.000/m^2	
Comfort class	EN 1307	LC2	
Other remarks		Dirt absorption capacity: 600 g/m2 Moisture absorption capacity: 3-4 l/m2 Production tolerance of 5% on size and colour	
Application for underfloor heating		yes	

All Coral products meet the requirements of EN 14041, excluding loose-laid mats and rugs

CE
EN 14041

Fire behaviour	EN 13501-1	B_{fl}-s1, G, NCS
Slip resistance	EN 13893	$\mu \geq 0.30$
Body voltage	EN 1815	≤ 2.0 kV

11/2026

creating better environments

forbo
FLOORING SYSTEMS