

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2018



Version number 4

Revision: 25.01.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 913 Hardener
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
FORBO Eurocol Deutschland GmbH
August-Roebling-Str. 2
D-99091 Erfurt
Tel.: +49 (0)361 73041-0
Fax: +49 (0)361 73041-92
Website: <http://www.forbo-bonding.de>
- **Further information obtainable from:**
Laboratory
Elisabeth Reinhardt
Elisabeth.Reinhardt@forbo.com
- **1.4 Emergency telephone number:** GGIZ +49-361-730730 (for Germany)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.
STOT SE 3 H335 May cause respiratory irritation.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**


 GHS07 GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**
diphenylmethanediisocyanate, isomeres and homologues
- **Hazard statements**
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2018

Version number 4

Revision: 25.01.2018



Trade name: 913 Hardener

(Contd. of page 1)

*H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.**H317 May cause an allergic skin reaction.**H351 Suspected of causing cancer.**H335 May cause respiratory irritation.**H373 May cause damage to organs through prolonged or repeated exposure.***· Precautionary statements***P201 Obtain special instructions before use.**P260 Do not breathe dust/fume/gas/mist/vapours/spray.**P280 Wear protective gloves/protective clothing/eye protection/face protection.**P302+P352 IF ON SKIN: Wash with plenty of water.**P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P308+P313 IF exposed or concerned: Get medical advice/attention.**P405 Store locked up.***· Additional information:***Restricted to professional users.**EUH204 Contains isocyanates. May produce an allergic reaction.***· 2.3 Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures**· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	75-<100%
EINECS: 202-966-0	 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;	
Index number: 615-005-00-9	 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;	
	Skin Sens. 1, H317; STOT SE 3, H335	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures**· General information:***Immediately remove any clothing soiled by the product.**Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.***· After inhalation:***Supply fresh air and to be sure call for a doctor.**In case of unconsciousness place patient stably in side position for transportation.***· After skin contact:** *Immediately wash with water and soap and rinse thoroughly.***· After eye contact:***Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.***· After swallowing:***Do not induce vomiting; call for medical help immediately.**A person vomiting while laying on their back should be turned onto their side.*

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.01.2018

Version number 4

Revision: 25.01.2018

Trade name: 913 Hardener

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide (CO)
Carbon dioxide
Nitrogen oxides (NO_x)
Hydrogen cyanide (prussic acid)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter drains/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Do not breathe vapour/aerosol.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2018

Version number 4

Revision: 25.01.2018

Trade name: 913 Hardener

(Contd. of page 3)

· **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

Store under lock and key and with access restricted to technical experts or their assistants only.

· **Recommended storage temperature:** +10 °C - +25 °C

· **Storage class:** 10

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m³

Sen; as -NCO

· **Additional Occupational Exposure Limit Values for possible hazards during processing:**

101-68-8 4,4'-methylenediphenyl diisocyanate

WEL Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m³

Sen; as -NCO

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Recommended filter device for short term use:** Combination filter A2-P2

· **Protection of hands:**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

Chloroprene rubber, CR

Recommended thickness of the material: ≥ 0.5 mm

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2018

Version number 4

Revision: 25.01.2018

Trade name: 913 Hardener

(Contd. of page 4)

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.4 mm**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

>480 min

· Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Appearance:****Form:**

Fluid

Colour:

Brown

· Odour:

Characteristic

· pH-value:

Not applicable.

· Change in condition**Melting point/freezing point:**

Undetermined.

Initial boiling point and boiling range: > 300 °C**· Flash point:**

> 200 °C

· Flammability (solid, gas):

Not applicable.

· Ignition temperature:

> 500 °C

· Decomposition temperature:

Undetermined.

· Auto-ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product does not present an explosion hazard.

· Vapour pressure:

Not determined.

· Density at 20 °C:1.24 g/cm³**· Evaporation rate**

Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water:

Undetermined.

· Viscosity:**Dynamic at 20 °C:**

160 - 200 mPas

· Solvent content:**VOC (CE)**

Not applicable.

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.01.2018

Version number 4

Revision: 25.01.2018

Trade name: 913 Hardener

(Contd. of page 5)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information**· 11.1 Information on toxicological effects****· Acute toxicity**

Harmful if inhaled.

· LD/LC50 values relevant for classification:**9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

Oral	LD50	>15000 mg/kg (rat)
Dermal	LD50	< 5000 mg/kg (rabbit)
Inhalative	LC50/4h	490 mg/l (rat)

· Primary irritant effect:**· Skin corrosion/irritation****9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

Irritation of skin	Dermal Irritation	irritating (rabbit) (OECD 404)
--------------------	-------------------	--------------------------------

Causes skin irritation.

· Serious eye damage/irritation**9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

Irritation of eyes	Eye Irritation	irritating (rabbit) (OECD 405)
--------------------	----------------	--------------------------------

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**· Germ cell mutagenicity** Based on available data, the classification criteria are not met.**· Carcinogenicity**

Suspected of causing cancer.

· Reproductive toxicity Based on available data, the classification criteria are not met.**· STOT-single exposure**

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.01.2018

Version number 4

Revision: 25.01.2018

Trade name: 913 Hardener

(Contd. of page 6)

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**EC50/24h >1000 mg/l (*Daphnia magna*) (OECD 202)LC50/96h >1000 mg/l (zebrafish (*Brachydanio rerio*)) (OECD 203)**· 12.2 Persistence and degradability** No further relevant information available.**· Degree of elimination:****9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Modified MITI Test 0 % / 28d (OECD 302C)

· 12.3 Bioaccumulative potential No further relevant information available.**· 12.4 Mobility in soil** No further relevant information available.**· Ecotoxicological effects:****· Behaviour in sewage processing plants:****· Type of test Effective concentration Method Assessment****9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

EC50/3h >100 mg/l (activated sludge) (OECD 209)

· Additional ecological information:**· General notes:**

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 12.5 Results of PBT and vPvB assessment**· PBT:** Not applicable.**· vPvB:** Not applicable.**· 12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****· 13.1 Waste treatment methods**

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Recommendation Do not allow product to reach sewage system.**· European waste catalogue 08 05 01* :** waste isocyanates**· Uncleaned packaging:****· Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****· 14.1 UN-Number****· ADR, ADN, IMDG, IATA**

Void

· 14.2 UN proper shipping name**· ADR, ADN, IMDG, IATA**

Void

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.01.2018

Version number 4

Revision: 25.01.2018

Trade name: 913 Hardener

(Contd. of page 7)

· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA	
· Class	Void
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed. (94/33/EC)
Employment restrictions concerning pregnant and lactating women must be observed. (92/85/EC)
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- **Relevant phrases**
Irritating to skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
- **Department issuing SDS:** Laboratory
- **Contact:**
Dr. Amina Chnirheb
Amina.Chnirheb@forbo.com
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.01.2018

Version number 4

Revision: 25.01.2018

Trade name: 913 Hardener

(Contd. of page 8)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
· *** Data compared to the previous version altered.**

GB