




















Technical specifications

Cloudscape carpet tiles meet the requirements of EN 1307

	Description	Tufted multi-height loop pile carpet tile	
	Dimensions	50cm x 50cm	
	Total thickness	7.2mm ± 10%	
	Pile height	4.4mm ± 0.5mm	
	Collection size	16 colourways. 4m ² per box	
	Application	EN 1307	Class 33, Suitable for any type of heavy contract application
	Pile composition	100% polyamide 6	
	Dye method	100% solution dyed	
	Tuft density	217,267 per m ² ± 10%	
	Pile weight	665gsm ± 10%	
	Total weight	4,180gsm ± 10%	
	Primary backing	Polyester	
	Secondary backing	ProBac recycled mineral filler with low amount of modified bitumen, and polyester fleece. Contains over 76% recycled content	
	Castor chair use	EN 985	Minimum R Value: ≥ 2.4
	Light fastness	EN ISO 105-B02	≥ 5
	Impact sound reduction	ISO 10140-3	ΔL _W = 26 dB
	Creating Better Environments		
	Renewable Electricity	All Tessera carpet tiles are manufactured using 100% electricity made from renewable sources	
	Recycled Content	Cloudscape carpet tiles contain 58% recycled content by weight	
	Indoor Air Quality	Cloudscape carpet tiles comply to 01350 Indoor Air Quality Standard	
	Ska Rating	Cloudscape meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes	
	Guarantee	Cloudscape carpet tiles are guaranteed for 10 years under general contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.	
	Installation method	Non-directional or monolithic	
			 EN 14041
	Cloudscape carpet tiles meet the requirements of EN 14041		
	Reaction to fire	EN 13501-1	B _{fl} -s1
	Slip resistance	EN 13893	DS: ≥ 0.30
	Electrical resistance	BS ISO 10965 & EN 1815	<1 x 10 ⁹ Ω. Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

Forbo Flooring B.V.
Postbus 13
1560 AA Krommenie
Tel: +31 75 647 78 80
contact@forbo.com
www.forbo-flooring.nl

Volg ons op



creating better environments

forbo

FLOORING SYSTEMS