






COLOURS



It is possible to create special colours for surfaces above approx. 450 m² (RAL, RGB or Pantone). Delivery time for these special colours is at least six weeks after the customer's approval. Please contact Forbo Eurocol.

betondesign

FLOOR AND WALL WITH THE LOOK
OF BASIC CONCRETE



the strong connection

eurocol

Forbo Eurocol Deutschland GmbH
August-Röbling-Str. 2 • D-99091 Erfurt
Phone: +49 361 730 41 0 • Fax: +49 361 730 41 91
info.erfurt@forbo.com • www.forbo-eurocol.de

Eurocol is part of the Forbo Group



TREND OF THE TIME

Concrete is underestimated. Concrete can do more than carry loads. It arouses excitement due to its variety of forms and colors: there are kitchens, furniture and beds made of exposed concrete. There are accessories for living rooms like noble lamps and vases in concrete design.

Even touching concrete sparks emotions. Unique and handmade BetonDesign floors are not only individual but also durable and long-lived.

FOR FLOOR AND WALL

BetonDesign surfaces are equally unique and individual. They are handmade by craftsmen from genuine Forbo Eurocol Deutschland products and in accordance with company guidelines. Create unique ground surfaces or exclusive and creative wall decorations.



Forbo Eurocol BetonDesign surfaces are unique in structure and color and are applied by certified installation companies. You can expect a long-lasting, durable and dirt-resistant BetonDesign system according to the highest possible standards. The surface can either be smooth or variously structured. Please consult one of our certified installation companies for an individual offer.

COLOURS

You can chose between ten different colours, ranging between various light, dark, subtle, cold or warm shades of grey. There are numerous options for a unique interior design. It is possible to create special RGB, Pantone or RAL colours like rust for surfaces above approx. 450 m².

chones Design nzept

Advantages

| ready to use | individual concrete look | suitable for floors and walls | dust-free, wear-resistant and dirt-resistant | layer thickness only 1–1.5 mm | low emissions

