


















# Technical specifications




In-touch carpet tiles meet the requirements of EN 1307

tessera® in-touch

Description		Tufted multi-pile height loop carpet tile plank
	Dimensions	100cm x 25cm
	Total thickness	7.4mm ± 10%
	Pile height	4.2mm ± 0.5mm
	Collection size	10 colourways, 4m <sup>2</sup> per box
	Application	EN 1307 Class 33, Suitable for any type of heavy contract application
	Pile composition	100% Invista polyamide 6.6
	Dye method	100% solution dyed
	Tuft density	217,488 per m <sup>2</sup> ± 10%
	Pile weight	840 gsm ± 10%
	Total weight	4,355 gsm ± 10%
	Primary backing	Polyester
	Secondary backing	Modified bitumen and polyester fleece
	Castor chair use	BS EN 985 Minimum R value: ≥2.4
	Light fastness	BS EN ISO 105 B02 ≥5
	Dimensional stability	BS EN 986 ≤0.2%
	Acoustical impact noise reduction	ISO 140-8 ΔL <sub>w</sub> = 27 dB
	Creating Better Environments	
	Renewable Electricity	All Tessera carpet tile planks are manufactured using 100% electricity made from renewable sources
	Recycled Content	In-touch carpet tile planks contain 60% recycled content by weight
	Indoor Air Quality	In-touch carpet tile planks meet 01350 Indoor Air Quality standard
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor
	Ska	In-touch meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes
	Guarantee	In-touch carpet tile planks are guaranteed for 10 years under heavy contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.
	Installation method	Half drop, brick, weave, herringbone, double herringbone or monolithic

In-touch carpet tiles meet the requirements of EN 14041



	Reaction to fire	EN 13501-1	B <sub>f1</sub> -s1
	Slip resistance	EN 13893	DS: ≥0.30
	Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 <sup>9</sup> Ω: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

BREEAM ratings: Tessera In-touch is a new product and is currently under assessment for BREEAM rating.

Our recommended adhesive for our collection of Tessera carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

In-touch carpet tile planks are manufactured in a facility certified to SA8000® and OHSAS 18001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's) or local building rating schemes such as BREEAM.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.