

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.11.2022 Version number 3 Revision: 24.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 543 Eurosafe Deco UK

· Article number: 5433

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / preparation

Flooring adhesive

Fixative for floorcovering

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Forbo Eurocol Nederland B.V.

Industrieweg 1-2

NL-1521 NA Wormerveer Holland

Tel. +31 75 6271600 - Fax +31 75 6283564 E-mail address: info.eurocol@forbo.com

Website: www.eurocol.com

· 1.4 Emergency telephone number:

In case of emergency please contact the Dutch National Poison Control, telephone number: 0031-(0)88-755 8000 (This number is only accessible to the physician treating the patient and only in case of accidental poisoning).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- Additional information:

Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

- G

Printing date 24.11.2022 Version number 3 Revision: 24.11.2022

Trade name: 543 Eurosafe Deco UK

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Acrylate copolymer dispersion

· Dangerous components:		
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	<1%
CAS: 55965-84-9	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	<1%
CAS: 2682-20-4 EINECS: 220-239-6	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 1, H330; Skin Corr. B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 2, H411; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	<1%
CAS: 150413-26-6	Polyethyleenglycol monoisotridecylethersulfaat, natriumzout	>1-5%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

In case of unconsciousness place patient stably in side/recovery position for transportation. Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately rinse with water.

Wash with soap and water. Remove contaminated clothing.

After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a physician.

- After swallowing: Rinse mouth with water and then drink plenty of water, consult physician immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

Printing date 24.11.2022 Version number 3 Revision: 24.11.2022

Trade name: 543 Eurosafe Deco UK

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

- · 6.2 Environmental precautions: Dilute with plenty of water.
- 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool, but frost-proof location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Recommended storage temperature between 15 and 25 ℃.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

·DNELs		
2634-33-5 1,2-benzisothiazol-3(2H)-one		
Dermal	DNEL long term	0.966 mg/kg KG/d (wrk)
	DNEL short term systemic health problems	0.345 mg/kg/d (Consumer)
Inhalative	DNEL Inhalative long terme	1.2 /mg/m³ (Consumer)
		(Contd. on page 4)

(Contd. on page 4)

Printing date 24.11.2022 Version number 3 Revision: 24.11.2022

Trade name: 543 Eurosafe Deco UK

		(Contd. of page 3
Di	NEL	6.81 mg/m³ (wrk)
	nixture of: 5-chloro-2-methyl-4-isot sothiazol-3-one [EC no. 220-239-6] (3	hiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- 3:1)
Oral Di	NEL	0.09 mg/kg (Consumer)
Inhalative DNEL Inhalative long terme		0.02 /mg/m³ (Consumer)
PNECs		
2634-33-5 1,	2-benzisothiazol-3(2H)-one	
PNEC	4.99 μg/kg (Sea Water Sediment)	
	49.9 μg/kg (Fresh Water Sediment)	
PNEC ug/l	0.403 μg/l (Sea Water)	
	4.03 μg/l (Fresh Water)	
PNEC mg/kg	3 mg/kg (Soil)	
	nixture of: 5-chloro-2-methyl-4-isot sothiazol-3-one [EC no. 220-239-6] (3	hiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H 3:1)
PNEC mg/kg	0.01 mg/kg (Soil)	
	0.027 mg/kg (Sea Water Sediment)	
	0.027 mg/kg (Fresh Water Sediment)	
Additional in	formation. The lists valid during many	ifactura ware wood on basis

- · Additional information: The lists valid during manufacture were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

- · Respiratory protection: Not required.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material is dependant on the penetration times, rates of diffusion and degradation.

Material of gloves

Suitable chemical-resistant gloves (EN 374) even with longer direct contact (recommendation: protection index 6, corresponding> 480 minutes permeation time (permeation) according to EN 374) e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) and others. Due to several factors that can influence (e.g. temperature), it must be taken into account that the service life of a chemical glove can in practice be considerably shorter than the permeation time indicated by the test.

The selection of suitable gloves does not only depend on the material, but also on further aspects of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

> 480 Minutes.

The exact break through time has to be established by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 24.11.2022 Version number 3 Revision: 24.11.2022

Trade name: 543 Eurosafe Deco UK

(Contd. of page 4)

· For prolonged contact gloves made of the following materials are suitable:

Chloroprene and butylrubber.

Nitrile rubber

· Eye/face protection Tightly sealed goggles by risk of splashing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
 Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:

Fluid

 Light blue
 Characteristic
 Not determined.
 Undetermined.

· Boiling point or initial boiling point and boiling

range 100 ℃

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.
 Flash point: Not applicable.
 Decomposition temperature: Not determined.

. pH at 20 ℃ 7

· Viscosity:

· Kinematic viscosity
 · Dynamic at 20 °C:
 Not determined.
 20,000 mPas

Solubility

• water: Fully miscible.
• Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C:

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

23 hPa

· Solvent content:

· VOC(EC%) 0.0 %

· Change in condition

· Evaporation rate Not determined.

(Contd. on page 6)

Printing date 24.11.2022 Version number 3 Revision: 24.11.2022

Trade name: 543 Eurosafe Deco UK

(Contd. of page 5)

Information with regard to physical haz classes	zard
· Explosives	Void
Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
 Self-reactive substances and mixtures 	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures Void	
 Substances and mixtures, which emit flamma 	ble
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides Voi	
· Corrosive to metals Void	
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity
- LD/LC50 values relevant for classification:

55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral LD50 64-66 mg/kg (rat)
Dermal LD50 87.12 mg/kg (rat)

- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

- GB

Printing date 24.11.2022 Version number 3 Revision: 24.11.2022

Trade name: 543 Eurosafe Deco UK

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic toxicity:		
2634-33-5 1,2-benzisothiazol-3(2H)-one		
EC50/3h	13 mg/l (Not specified)	
55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)		
LC50/96h	0.28 mg/l (LM)	
	0.188 mg/l (OM)	
EC50/48 h	0.126 mg/l (DM)	
2682-20-4 2-methyl-2H-isothiazol-3-one		
EC50/3h	34.6 mg/l (activated sludge)	
EC 20/3 H	2.8 mg/l (activated sludge)	

· 12.2 Persistence and degradability

2682-20-4 2-methyl-2H-isothiazol-3-one

OECD 308 Simulation Biodegradation Agu Sed System 1.28-2.1 days (Not specified)
OECD 307 Aerobic and Anaerobic Transfortmation Soi <0.08 days (Not specified)
OECD 309 Simulation Biodegradation Surface Water 4.1 days (Not specified)

· 12.3 Bioaccumulative potential

2682-20-4 2-methyl-2H-isothiazol-3-one

BCF 3.16 BCF (Not specified)

Verdelingscoëfficient n-octanol/water ≤0.32 [---] (log Pow) (Not specified)

- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Warm water, if necessary together with cleansing agents.

GB

Printing date 24.11.2022 Version number 3 Revision: 24.11.2022

Trade name: 543 Eurosafe Deco UK

(Contd. of page 7)

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to instruments	Not applicable.
· Transport/Additional information:	Not classified as hazardous under transpor regulations.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H301	i oxic it swallowed.
H302	Harmful if swallowed

H310 Fatal in contact with skin.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 9)

Version number 3 Printing date 24.11.2022 Revision: 24.11.2022

Trade name: 543 Eurosafe Deco UK

(Contd. of page 8)

EUH071 Corrosive to the respiratory tract.

Department issuing SDS: R&D department

· Contact: Ing. T.W. Breeuwer

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.