



















# Technical specifications

Flotex Cityscape meets the requirements of EN 1307

tile

	Total thickness	ISO 1765	5.0 mm
	Commercial use	EN 685	Class 33 heavy
	Roll width		-
	Roll length		-
	Tile size		50 x 50 cm
	Quantity of tiles per box		12 (3m <sup>2</sup> )
	Total weight	ISO 8543	4.8 kg/m <sup>2</sup>
	Dimensional stability	ISO 2551 / EN 986	< 0.1 %
	Abrasion resistance	EN 1307 annex F	>1000 cycles
	Castor chair continuous use	EN 985	r = ≥ 2.4 continuous use
	Light fastness	EN-ISO 105-B02	≥ 6
	Slip resistance	UK SRG pendulum	Dry - very low slip risk Wet - low slip risk
	Acoustical	EN-ISO 717-2	Impact sound Δlw = 19 dB
		ISO 354	Sound absorption = 0.10
	Water tightness	EN 1307 annex G	Pass
	Flotex meets the requirements of EN 14041		EN 14041  1200201-DoP-306
	Reaction to fire	EN 13501	B <sub>f1</sub> -s1
	Slip resistance	EN 13893	μ ≥ 0.30
	Body voltage	ISO 6356	< 2 kV
	Thermal conductivity	ISO 8302	0.037 m <sup>2</sup> K/W

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

