
















# Technical specifications

Flotex Cityscape tiles meet the requirements of EN 1307

			Cityscape tile
	Total thickness	ISO 1765	5.0 mm
	Commercial use	EN ISO 10874	Class 33 heavy
	Tile size		50 x 50 cm
	Quantity of tiles per box		12 (3m <sup>2</sup> )
	Total weight	ISO 8543	4.8 kg/m <sup>2</sup>
	Dimensional stability	ISO 2551 / EN 986	< 0.1 %
	Abrasion resistance	EN 1307 annex F	>1000 cycles
	Castor chair continuous use	ISO 4918	r = ≥ 2.4 continuous use - Pass
	Light fastness	EN-ISO 105-B02	≥ 6
	Slip resistance	UK SRG pendulum	Dry - very low slip risk Wet - low slip risk
	Acoustic	EN-ISO 717-2	Impact sound ΔIw ≥ 19 dB
		ISO 354	Sound absorption = 0.10
	Water tightness	EN 1307 annex G	Pass
			EN 14041 <b>CE</b> 1200201-DoP-306
Flotex meets the requirements of EN 14041			
	Reaction to fire	EN 13501	B <sub>f1</sub> -s1, L, NCS
	Slip resistance	EN 13893	μ ≥ 0.30
	Body voltage	ISO 6356	< 2 kV
	Thermal resistance	EN 12667	0.037 m <sup>2</sup> K/W

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.  
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.  
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPDs) which can be found on all of our websites.



Flotex ensures consistent protection against bacteria without degradation through cleaning or vacuuming. It also suppresses the growth of dust mite populations. Therefore Flotex has a positive impact on the lives of allergy sufferers even more as daily vacuuming cleans away twice as many allergens compared to conventional carpets. That is why Flotex carries the Allergy UK Seal of Approval™.

