## **Technical specifications**

Create Space 1 carpet tiles meet the requirements of EN 1307

Part of the eVOVe+ series product evolution for enhanced sustainability

	Description		Tufted low level loop carpet tile	
$\bigoplus$	Dimensions	EN 994	50cm x 50cm	
	Total thickness	ISO 1765	5.5mm	
	Pile height	ISO 1766	2.7mm	
	Collection size		18	
	Packaging per carton of tiles		20	
iii)	Commercial use	EN ISO 10874	Class 33, Suitable for any type of heavy contract application	
	Pile composition		100% ECONYL® regenerated polyamide 6	
	Dye method		100% solution dyed	
	Stitch density	ISO 1763	212,760 per m <sup>2</sup>	
3	Pile weight	ISO 8543	500gsm ± 10%	
	Total weight		3,815gsm	
	Primary backing		Polyester	
	Secondary backing		ProBac recycled mineral filler with low amount of modified bitumen and polyester fleece.	
	Acoustical impact noise reduction	ISO 10140-3	25 dB	
9)))	Acoustical sound absorption reduction	ISO 354	0.15	
7	Castor chair continuous use	ISO 4918	≥ 2.4	
录	Colour fastness to light	ISO 105-B02	≥5	
K ZI	Dimensional stability	EN 986	≤ 0.2 %	
	Creating Better Environments			
$\vec{\Lambda}$	Renewable energy		All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas)	
3	Recycled content		Create Space 1 carpet tiles contain 75% recycled content by weight	
1	Indoor air quality		Create Space 1 carpet tiles comply to Indoor Air Comfort Gold 8.0 (2022)	
1	Ska rating		Create Space 1 meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education scl	hemes
	Prodis-GUT	www.pro-dis.info	3B5DACDB	
	Installation method		Monolithic, quarter turn or tessellated	
	Create Space 1 carpet tiles meet the req	uirements of EN 14041	:2004 and BS EN 14041:2004 EN 140	
(€	Product code	EN 14041	1170100-DoP-109	
UK CA	Product code	BS EN 14041:2004	1170100-DoP-GB109	
G	Reaction to fire	ISO 9239.1	CRF >2.2 kW/m <sup>2</sup>	
ncs M	Slip resistance	AS 4586:2013	R12, P5	
DS			· ·	

 $All Forbo Flooring \ Systems' sales \ organisations \ and \ manufacturing \ sites \ worldwide \ have \ certified \ Quality \ Management \ Systems \ in \ accordance \ with \ ISO \ 9001.$ 

< 2.0 kV (antistatic)

 $All\ Forbo\ Flooring\ Systems' manufacturing\ plants\ have\ certified\ Environmental\ Management\ Systems\ in\ accordance\ with\ ISO\ 14001.$ 

Tessera Create Space 1 carpet tiles are manufactured in a facility certified to SA8000® and ISO 45001.

ISO 6356

 $The \ Life \ Cycle \ Assessment \ (LCA) \ of \ Forbo \ Flooring \ Systems' \ products \ is \ documented \ in \ individual \ Environmental \ product \ declarations \ (EPD's).$ 



Thermal conductivity

Body voltage